

Häfele Free Up



- > For one-piece wood or aluminum doors
- > Ideal for upper cabinets or front panels
- > Modern design with clear-cut contours
- > Minimum opening resistance, multi-position stop function and soft opening and soft closing mechanism
- > Time-saving assembly provided by plugs, pre-mounted Euro screws and clip mounting of front panel and cross bar, eccentric adjustment of front panel
- > Adjustment facility: Height adjustment ± 1.5 mm, side adjustment ± 1.5 mm, tilting angle $\pm 1.5^\circ$, holding power
- > Material: Plastic, Steel; Finish: nickel-plated
Cover Cap: Plastic; Color: gray

→ Parallel Lift-up Front Fitting



Door height	Door weight lbs.	Model	Item No.
320–360 (12 5/8"–14 3/16")	6.6–12.5 10.6–20.5	O1us O2us	372.33.500 372.33.501
345–420 (13 9/16"–16 9/16")	5.3–10.6 9–17.6 16.3–30.8	P1us P2us P3us	372.33.510 372.33.511 372.33.512
	4.4–8.4	Q1us	372.33.520
380–500 (14 15/16"–19 11/16")	7.5–14.7 13.9–26 20.5–38.3	Q2us Q3us Q4us	372.33.521 372.33.522 372.33.523
	3.5–7.3	R1us	372.33.530
430–600 (16 15/16"–23 5/8")	5.7–12.1 11–21.3 16.3–32.1	R2us R3us R4us	372.33.531 372.33.532 372.33.533

Supplied With

2 Fittings (right/left)
Front mounting material for wood or wide aluminum frame doors
Installation instructions
Paper drilling template
2 Cover caps for fitting (right/left)

Note

Cross bars are mandatory to synchronize Left/Right fittings,
see next page.
See next page for aluminum framed doors adapter.