

→ Häfele Slido F-Line21 40C Set

	Version	Supplied with	Item No.
For 2 doors	With clip-in door stopper	4 running gears 4 door stoppers with clip-in door stopper 1 door follower 2 service ports 2 guides 1 mounting aid	402.33.026
	With soft closing mechanism on one side, 40 kg (88 lbs.)	4 running gears (2 with soft closing mechanism) 4 door stoppers (2 with clip-in door stopper, 2 for soft closing mechanism) 1 door follower 2 guides 1 mounting aid	402.33.027
	With soft closing mechanism on both sides, 40 kg (88 lbs.)	4 running gears with soft closing mechanism 4 door stoppers for soft closing mechanism 1 door follower 2 guides 1 mounting aid	402.33.028

Supplied With

1 set

Note

Please order running and guide tracks separately. The pitch length of the running gears must be min. 245 mm (9 5/8") with soft closing mechanism on one side and min. 425 mm (16 3/4") with soft closing mechanism on both sides. Service port cannot be used in combination with running gear with soft closing mechanism.

→ Tracks and Accessories

Description		Min. cabinet top thickness	Material	Finish	Length	Item No.
Single upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.642
		30 (1 3/16") (screw mount)			3.5 m (11' 5 13/16")	402.33.643
Double upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.652
		30 (1 3/16") (screw mount)				
Single upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.642
Double upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.652
Lower guide channel, for glue mounting into 6 mm (1/4") groove		–	Plastic	gray	2.5 m (8' 2 7/16")	402.30.802
					3.5 m (11' 5 13/16")	402.30.803
Flat head screw 3.0 x 1/2", Phillips drive, for screw mounted upper running tracks		–	Steel	zinc-plated	12 mm (1/2")	402.33.010

Note

Polyurethane glue recommended for groove mounted tracks.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Flat head screws	pages 12.7–12.8, 12.10, 12.13
Planofit Straightening Fitting	page 7.91

→ Häfele Slido F-Line21 20C Set

	Version	Supplied with	Item No.
For 2 doors	With clip-in door stopper	4 running gears 4 door stoppers with clip-in door stopper 1 door follower 2 service ports 2 guides 1 mounting aid	402.33.018
	With soft closing mechanism on one side	4 running gears (2 with soft closing mechanism) 4 door stoppers (2 with clip-in door stopper, 2 for soft closing mechanism) 1 door follower 2 guides 1 mounting aid	402.33.019
	With soft closing mechanism on both sides	4 running gears with soft closing mechanism 4 door stoppers for soft closing mechanism 1 door follower 2 guides 1 mounting aid	402.33.020

Supplied With

1 set

Note

Please order running and guide tracks separately. The pitch length of the running gears must be min. 245 mm (9 5/8") with soft closing mechanism on one side and min. 425 mm (16 3/4") with soft closing mechanism on both sides. Service port cannot be used in combination with running gear with soft closing mechanism.

→ Tracks and Accessories

Description		Min. cabinet top thickness	Material	Finish	Length	Item No.
Single upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.642
		30 (1 3/16") (screw mount)			3.5 m (11' 5 13/16")	402.33.643
Double upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.652
		30 (1 3/16") (screw mount)				
Single upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.642
Double upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.652
Lower guide channel, for glue mounting into 6 mm (1/4") groove		–	Plastic	gray	2.5 m (8' 2 7/16")	402.30.802
					3.5 m (11' 5 13/16")	402.30.803
Flat head screw 3.0 x 1/2", Phillips drive, for screw mounted upper running tracks		–	Steel	zinc-plated	12 mm (1/2")	402.33.010

Note

Polyurethane glue recommended for groove mounted tracks.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Flat head screws pages 12.7–12.8, 12.10, 12.13

→ Häfele Slido F-Line21 12C Set

	Version	Supplied with	Item No.
For 2 doors	With clip-in door stopper	4 running gears 4 door stoppers with clip-in door stopper 1 door follower 2 service ports 2 guides 1 mounting aid	402.33.013
	With soft closing mechanism on one side	4 running gears (2 with soft closing mechanism left/right) 4 door stoppers (2 with clip-in door stopper/2 for soft closing mechanism) 1 door follower 2 guides 1 mounting aid	402.33.014
	With soft closing mechanism on both sides	4 running gears with soft closing mechanism 4 door stoppers for soft closing mechanism 1 door follower 2 guides 1 mounting aid	402.33.015

Supplied With

1 set

Note

Please order running and guide tracks separately. The pitch length of the running gears must be min. 225 mm (8 7/8") with soft closing mechanism on one side and min. 415 mm (16 5/16") with soft closing mechanism on both sides. Service port cannot be used in combination with running gear with soft closing mechanism (service port cannot be ordered separately).

→ Tracks and Accessories

Description		Min. cabinet top thickness	Material	Finish	Length	Item No.
Single upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.642
		30 (1 3/16") (screw mount)			3.5 m (11' 5 13/16")	402.33.643
Double upper running track, for glue mounting into 16 mm (5/8") groove or for screw mounting with 3.0 mm flat head screws		19 (3/4") (gluing)	Aluminum	mill	2.5 m (8' 2 7/16")	402.33.652
		30 (1 3/16") (screw mount)				
Single upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.642
Double upper running track, for screw mounting		–	Aluminum	silver colored anodized	2.5 m (8' 2 7/16")	402.30.652
Lower guide channel, for glue mounting into 6 mm (1/4") groove		–	Plastic	gray	2.5 m (8' 2 7/16")	402.30.802
					3.5 m (11' 5 13/16")	402.30.803
Flat head screw 3.0 x 1/2", Phillips drive, for screw mounted upper running tracks		–	Steel	zinc-plated	12 mm (1/2")	402.33.010

Note

Polyurethane glue recommended for groove mounted tracks.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Flat head screws pages 12.7–12.8, 12.10, 12.13