

### → Häfele Slido F-Line21 20D Set

|             | Version                                                    | Supplied With                                                                                                                                                                                      | Item No.   |
|-------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| For 1 door  | With clip-in door stopper                                  | 2 running gears<br>2 door stoppers with clip-in door stopper<br>1 set of guides, cover caps and mounting aid                                                                                       | 402.33.032 |
|             | With soft closing mechanism on both sides, 20 kg (44 lbs.) | 2 running gears with soft closing mechanism<br>2 door stoppers for soft closing mechanism<br>1 set of guides, cover caps and mounting aid                                                          | 402.33.033 |
| For 2 doors | With clip-in door stopper                                  | 4 running gears<br>4 door stoppers with clip-in door stopper<br>1 door follower<br>2 sets of guides, cover caps and mounting aid                                                                   | 402.33.034 |
|             | With soft closing mechanism on one side, 20 kg (44 lbs.)   | 4 running gears (2 with soft closing mechanism)<br>4 door stoppers (2 with clip-in door stopper, 2 for soft closing mechanism)<br>1 door follower<br>2 sets of guides, cover caps and mounting aid | 402.33.035 |
|             | With soft closing mechanism on both sides, 20 kg (44 lbs.) | 4 running gears with soft closing mechanism<br>4 door stoppers for soft closing mechanism<br>1 door follower<br>2 sets of guides, cover caps and mounting aid                                      | 402.33.036 |



#### Supplied With

1 set

#### Note

Please order running and guide tracks separately. For cabinets with more than 3 doors, please order following sets: 1 set for 1 door and 1 set for 2 doors. The pitch length of the running gears must be min. 245 mm (9 11/16") with soft closing mechanism on one side and min. 425 mm (16 3/4") with soft closing mechanism on both sides.

### → Tracks and Accessories

| Description                                                                                                                                              |                                                                                     | Min. cabinet top thickness                                          | Material | Finish                                           | Length               | Item No.   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|----------|--------------------------------------------------|----------------------|------------|
| Single top running track, for press fitting and glue mounting into groove 16 mm (5/8") or for screw mounting with countersunk head screws 3 mm (1/8")    |  | Glue mounting: Min. 19 (3/4");<br>Screw mounting: Min. 30 (1 3/16") | Aluminum | mill, visible areas grooved                      | 2.5 m (8' 2 7/16")   | 402.33.642 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.643 |
| Double top running track, for press fitting and glue mounting into groove 16 mm (5/8") or for screw mounting with countersunk head screws Ø3.5 mm (1/8") |  | Glue mounting: Min. 19 (3/4");<br>Screw mounting: Min. 30 (1 3/16") | Aluminum | mill, visible areas grooved                      | 2.5 m (8' 2 7/16")   | 402.33.600 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.601 |
| Single top running track, for screw mounting with countersunk head screws Ø3.5 mm (1/8")                                                                 |  | -                                                                   | Aluminum | silver colored anodized                          | 2.5 m (8' 2 7/16")   | 402.30.642 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.30.643 |
| Glass door profile, for top and bottom                                                                                                                   |  | -                                                                   | Aluminum | Front: silver colored, anodized<br>Back: brushed | 2.5 m (8' 2 7/16")   | 402.33.700 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.701 |

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Sliding and Roller Shutter Systems

### → Häfele Slido F-Line21 12D Set

|             | Version                                                    | Supplied With                                                                                                                                                                                      | Item No.   |
|-------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| For 1 door  | With clip-in door stopper                                  | 2 running gears<br>2 door stoppers with clip-in door stopper<br>1 set of guides, cover caps and mounting aid                                                                                       | 402.33.032 |
|             | With soft closing mechanism on both sides, 12 kg (26 lbs.) | 2 running gears with soft closing mechanism<br>2 door stoppers for soft closing mechanism<br>1 set of guides, cover caps and mounting aid                                                          | 402.33.037 |
| For 2 doors | With clip-in door stopper                                  | 4 running gears<br>4 door stoppers with clip-in door stopper<br>1 door follower<br>2 sets of guides, cover caps and mounting aid                                                                   | 402.33.034 |
|             | With soft closing mechanism on one side, 12 kg (26 lbs.)   | 4 running gears (2 with soft closing mechanism)<br>4 door stoppers (2 with clip-in door stopper, 2 for soft closing mechanism)<br>1 door follower<br>2 sets of guides, cover caps and mounting aid | 402.33.038 |
|             | With soft closing mechanism on both sides, 12 kg (26 lbs.) | 4 running gears with soft closing mechanism<br>4 door stoppers for soft closing mechanism<br>1 door follower<br>2 sets of guides, cover caps and mounting aid                                      | 402.33.039 |



#### Supplied With

1 set

#### Note

Please order running and guide tracks separately. For cabinets with more than 3 doors, please order following sets: 1 set for 1 door and 1 set for 2 doors. The pitch length of the running gears must be min. 245 mm (9 5/8") with soft closing mechanism on one side and min. 425 mm (16 3/4") with soft closing mechanism on both sides.

### → Tracks and Accessories

| Description                                                                                                                                              |                                                                                     | Min. cabinet top thickness                                          | Material | Finish                                           | Length               | Item No.   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------|----------|--------------------------------------------------|----------------------|------------|
| Single top running track, for press fitting and glue mounting into groove 16 mm (5/8") or for screw mounting with countersunk head screws 3 mm (1/8")    |  | Glue mounting: Min. 19 (3/4");<br>Screw mounting: Min. 30 (1 3/16") | Aluminum | mill, visible areas grooved                      | 2.5 m (8' 2 7/16")   | 402.33.642 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.643 |
| Double top running track, for press fitting and glue mounting into groove 16 mm (5/8") or for screw mounting with countersunk head screws Ø3.5 mm (1/8") |  | Glue mounting: Min. 19 (3/4");<br>Screw mounting: Min. 30 (1 3/16") | Aluminum | mill, visible areas grooved                      | 2.5 m (8' 2 7/16")   | 402.33.600 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.601 |
| Single top running track, for screw mounting with countersunk head screws Ø3.5 mm (1/8")                                                                 |  | -                                                                   | Aluminum | silver colored anodized                          | 2.5 m (8' 2 7/16")   | 402.30.642 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.30.643 |
| Glass door profile, for top and bottom                                                                                                                   |  | -                                                                   | Aluminum | Front: silver colored, anodized<br>Back: brushed | 2.5 m (8' 2 7/16")   | 402.33.700 |
|                                                                                                                                                          |                                                                                     |                                                                     |          |                                                  | 3.5 m (11' 5 13/16") | 402.33.701 |

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Sliding and Roller Shutter Systems