

Häfele Slido R-Aluflex 80A

→ Top Guide Tracks

Description		Material	Length	silver anodized	bronze	white	black
Single top guide track		Aluminum	2 m (6' 6 3/4")	403.36.902	403.36.102	–	–
			3 m (9' 10 1/8")	403.36.903	403.36.103	–	–
			6 m (19' 8 1/4")	403.36.906	403.36.106	403.36.810	403.36.813
Double top guide track		Aluminum	2 m (6' 6 3/4")	403.36.912	403.36.112	–	–
			3 m (9' 10 1/8")	403.36.913	403.36.113	–	–
			6 m (19' 8 1/4")	403.36.916	403.36.116	403.36.811	403.36.814
Triple top guide track		Aluminum	6 m (19' 8 1/4")	403.36.926	403.36.126	403.36.812	403.36.815

→ Bottom Running Tracks

Description		Material	Length	silver anodized	bronze	white	black
Single bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.932	403.36.132	–	–
			3 m (9' 10 1/8")	403.36.933	403.36.133	–	–
			6 m (19' 8 1/4")	403.36.936	403.36.136	403.36.600	403.36.603
Double bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.942	403.36.142	–	–
			3 m (9' 10 1/8")	403.36.943	403.36.143	–	–
			6 m (19' 8 1/4")	403.36.946	403.36.146	403.36.601	403.36.604
Triple bottom running track		Aluminum	6 m (19' 8 1/4")	403.36.956	403.36.156	403.36.602	403.36.605

→ Frame Profiles

Description		Material	Length	silver anodized	bronze	white	black
Top frame profile		Aluminum	2 m (6' 6 3/4")	403.62.962	403.62.172	–	–
			3 m (9' 10 1/8")	403.62.963	403.62.173	–	–
			6 m (19' 8 1/4")	403.62.960	403.62.176	403.36.715	403.36.725
Bottom frame profile		Aluminum	2 m (6' 6 3/4")	403.61.920	403.61.122	–	–
			3 m (9' 10 1/8")	403.61.930	403.61.123	–	–
			6 m (19' 8 1/4")	403.61.960	403.61.126	403.36.710	403.36.720
Vertical frame profile 10		Aluminum	2.1 m (6' 10 11/16")	403.63.972	403.63.102	–	–
			3.1 m (10' 2 1/16")	403.63.973	403.63.103	–	–
			5.25 m (17' 2 11/16")	403.63.975	403.63.105	403.36.711	403.36.721
Vertical frame profile 10-C		Aluminum	5.25 m (17' 2 11/16")	403.82.915	403.82.175	403.36.712	403.36.722
Vertical frame profile 50		Aluminum	5.25 m (17' 2 11/16")	403.82.955	403.36.730	403.36.713	403.36.723

Häfele Slido R-Aluflex 80 W

	Supplied with	Item No.
For 1 door	Running gear with plastic guide rollers	403.50.941

Note

Please order top guide and bottom running tracks, soft closing mechanism and other accessories separately.

→ Top Guide and Bottom Running Tracks

Description		Material	Length	silver	bronze	white	black
Single top guide track		Aluminum	2 m (6' 6 3/4")	403.36.902	403.36.102	–	–
			3 m (9' 10 1/8")	403.36.903	403.36.103	–	–
			6 m (19' 8 1/4")	403.36.906	403.36.106	403.36.810	403.36.813
Double top guide track		Aluminum	2 m (6' 6 3/4")	403.36.912	403.36.112	–	–
			3 m (9' 10 1/8")	403.36.913	403.36.113	–	–
			6 m (19' 8 1/4")	403.36.916	403.36.116	403.36.811	403.36.814
Triple top guide track		Aluminum	6 m (19' 8 1/4")	403.36.926	403.36.126	403.36.812	403.36.815
Single bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.932	403.36.132	–	–
			3 m (9' 10 1/8")	403.36.933	403.36.133	–	–
			6 m (19' 8 1/4")	403.36.936	403.36.136	403.36.600	403.36.603
Double bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.942	403.36.142	–	–
			3 m (9' 10 1/8")	403.36.943	403.36.143	–	–
			6 m (19' 8 1/4")	403.36.946	403.36.146	403.36.601	403.36.604
Triple bottom running track		Aluminum	6 m (19' 8 1/4")	403.36.956	403.36.156	403.36.602	403.36.605

→ Accessories

Description		Material	Finish	Item No.
End bracket for all guide tracks, for covering the sides, screw mounted		Steel	gray	403.55.991
			white	403.55.300
			bronze	403.55.100
			black	403.55.301
Center door stopper for mounting into the top guide track		Plastic	gray	403.50.945
Cover cap, for single running bottom track		Stainless steel	gray	403.55.060
			white	403.55.400
			bronze	403.55.160
			black	403.55.401
Wall mounting bracket, for top guide track, required every 400 mm (15 3/4")		Steel	gray	403.55.980
			white	403.55.780
			bronze	403.55.101
			black	403.55.180
Soft and self-closing mechanism, for door weights up to 15 kg (33 lbs.)		Plastic	black/gray	403.50.988
Soft and self-closing mechanism, for door weights up to 40 kg (88 lbs.)			black/green	403.50.999
Soft and self-closing mechanism, for door weights up to 80 kg (176 lbs.)			black/yellow	403.50.989

Note

Minimum door width with one soft and self-closing mechanism is 500 mm (19 5/8") and 830 mm (36 5/8") with 2.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.