













Häfele Slido R-Aluflex 80A

→ Door Components

Description		Material	Finish	Length	Item No.
Gasket, for infill panel thickness 5–6.4 mm (3/16"–1/4")		Plastic	transparent	2.5 m (8' 2 7/16")	403.56.925
				3.5 m (11' 5 13/16")	403.56.935
				6 m (19' 8 1/4")	403.56.960
Gasket, for infill panel thickness 7.7–8.3 mm (19/64"–21/64")		Plastic	transparent	2.5 m (8' 2 7/16")	403.79.925
				3.5 m (11' 5 13/16")	403.79.935
				6 m (19' 8 1/4")	403.79.960
Sliding brush set, for cleaning of running tracks, with Häfele logo, (2 pcs.)		Aluminum	silver colored	–	403.55.988
Sliding brush set, for cleaning of running tracks, without Häfele logo, (2 pcs.)		Aluminum	silver colored	–	403.55.997
Brush seal, self-adhesive, mounted onto front edge of the door to create a seal between the door and jamb		Synthetic	gray	10 m (32' 9 11/16")	403.54.531

→ Accessories

Description		Material	Finish	Length	Item No.
Brush seal, self-adhesive, for protecting the inside from dust, mounted between 2 overlapping vertical frame profiles		Synthetic	gray	10 m (32' 9 11/16")	403.54.530
				175 m (574' 1 3/4")	403.54.513
End bracket for all top guide tracks, for covering ends, screw mounted		Steel	silver colored	–	403.55.991
			bronze	–	403.55.100
			black	–	403.55.301
			white	–	403.55.300
Cover cap, for single bottom running track		Stainless steel	silver colored	–	403.55.060
			bronze	–	403.55.160
			black	–	403.55.401
			white	–	403.55.400
Wall mounting bracket, for top guide track, includes mounting screw and set nut, mounted every 400 mm (15 3/4")		Steel	silver colored	–	403.55.980
			bronze	–	403.55.101
			black	–	403.55.180
			white	–	403.55.780
Center door stop for mounting into the top guide track		Plastic	gray	–	403.50.945
Roller pin for joining top guide tracks and bottom running tracks		Steel	–	–	403.50.965
Follower set for door, includes mounting screws, suitable for frame profile 10 and 50		Aluminum	silver colored	–	403.50.979
			bronze	–	403.50.119
			black	–	403.50.401
			white	–	403.50.402

Häfele Slido R-Aluflex 80 W

	Supplied with	Item No.
For 1 door	Running gear with plastic guide rollers	403.50.941

Note

Please order top guide and bottom running tracks, soft closing mechanism and other accessories separately.

→ Top Guide and Bottom Running Tracks

Description		Material	Length	silver	bronze	white	black
Single top guide track		Aluminum	2 m (6' 6 3/4")	403.36.902	403.36.102	–	–
			3 m (9' 10 1/8")	403.36.903	403.36.103	–	–
			6 m (19' 8 1/4")	403.36.906	403.36.106	403.36.810	403.36.813
Double top guide track		Aluminum	2 m (6' 6 3/4")	403.36.912	403.36.112	–	–
			3 m (9' 10 1/8")	403.36.913	403.36.113	–	–
			6 m (19' 8 1/4")	403.36.916	403.36.116	403.36.811	403.36.814
Triple top guide track		Aluminum	6 m (19' 8 1/4")	403.36.926	403.36.126	403.36.812	403.36.815
Single bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.932	403.36.132	–	–
			3 m (9' 10 1/8")	403.36.933	403.36.133	–	–
			6 m (19' 8 1/4")	403.36.936	403.36.136	403.36.600	403.36.603
Double bottom running track		Aluminum	2 m (6' 6 3/4")	403.36.942	403.36.142	–	–
			3 m (9' 10 1/8")	403.36.943	403.36.143	–	–
			6 m (19' 8 1/4")	403.36.946	403.36.146	403.36.601	403.36.604
Triple bottom running track		Aluminum	6 m (19' 8 1/4")	403.36.956	403.36.156	403.36.602	403.36.605

→ Accessories

Description		Material	Finish	Item No.
End bracket for all guide tracks, for covering the sides, screw mounted		Steel	gray	403.55.991
			white	403.55.300
			bronze	403.55.100
			black	403.55.301
Center door stopper for mounting into the top guide track		Plastic	gray	403.50.945
Cover cap, for single running bottom track		Stainless steel	gray	403.55.060
			white	403.55.400
			bronze	403.55.160
			black	403.55.401
Wall mounting bracket, for top guide track, required every 400 mm (15 3/4")		Steel	gray	403.55.980
			white	403.55.780
			bronze	403.55.101
			black	403.55.180
Soft and self-closing mechanism, for door weights up to 15 kg (33 lbs.)		Plastic	black/gray	403.50.988
Soft and self-closing mechanism, for door weights up to 40 kg (88 lbs.)			black/green	403.50.999
Soft and self-closing mechanism, for door weights up to 80 kg (176 lbs.)			black/yellow	403.50.989

Note

Minimum door width with one soft and self-closing mechanism is 500 mm (19 5/8") and 830 mm (36 5/8") with 2.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.