

Häfele Slido R-Aluflex 80A

→ Door Components

| Description | Image | Material | Finish | Length | Item No. |
|---|-------|-----------|----------------|----------------------|------------|
| Gasket, for infill panel thickness 5–6.4 mm (3/16"–1/4") | | Plastic | transparent | 2.5 m (8' 2 7/16") | 403.56.925 |
| Gasket, for infill panel thickness 7.7–8.3 mm (19/64"–21/64") | | | | 3.5 m (11' 5 13/16") | 403.56.935 |
| Sliding brush set, for cleaning of running tracks, with Häfele logo, (2 pcs.) | | | | 6 m (19' 8 1/4") | 403.56.960 |
| Sliding brush set, for cleaning of running tracks, without Häfele logo, (2 pcs.) | | Aluminum | silver colored | 2.5 m (8' 2 7/16") | 403.79.925 |
| Brush seal, self-adhesive, mounted onto front edge of the door to create a seal between the door and jamb | | | | 3.5 m (11' 5 13/16") | 403.79.935 |
| Brush seal, self-adhesive, for protecting the inside from dust, mounted between 2 overlapping vertical frame profiles | | | | 6 m (19' 8 1/4") | 403.79.960 |
| End bracket for all top guide tracks, for covering ends, screw mounted | | Synthetic | gray | 10 m (32' 9 11/16") | 403.54.531 |

→ Accessories

| Description | Image | Material | Finish | Length | Item No. |
|---|----------|-----------------|----------------|---------------------|------------|
| Brush seal, self-adhesive, for protecting the inside from dust, mounted between 2 overlapping vertical frame profiles | | Synthetic | gray | 10 m (32' 9 11/16") | 403.54.530 |
| End bracket for all top guide tracks, for covering ends, screw mounted | | | | 175 m (574' 1 3/4") | 403.54.513 |
| Cover cap, for single bottom running track | | Stainless steel | silver colored | — | 403.55.991 |
| Wall mounting bracket, for top guide track, includes mounting screw and set nut, mounted every 400 mm (15 3/4") | | | bronze | — | 403.55.100 |
| Center door stop for mounting into the top guide track | | | black | — | 403.55.301 |
| Roller pin for joining top guide tracks and bottom running tracks | | | white | — | 403.55.300 |
| Follower set for door, includes mounting screws, suitable for frame profile 10 and 50 | | Aluminum | silver colored | — | 403.55.060 |
| | | | bronze | — | 403.55.160 |
| | | | black | — | 403.55.401 |
| | | | white | — | 403.55.400 |
| | | Steel | silver colored | — | 403.55.980 |
| | | | bronze | — | 403.55.101 |
| | | | black | — | 403.55.180 |
| | | | white | — | 403.55.780 |
| | Plastic | gray | — | — | 403.50.945 |
| | Steel | — | — | — | 403.50.965 |
| | Aluminum | silver colored | — | — | 403.50.979 |
| | | bronze | — | — | 403.50.119 |
| | | black | — | — | 403.50.401 |
| | | white | — | — | 403.50.402 |

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.