

## Häfele Slido R-Aluflex 80A

### → Door Components

| Description                                                                                               |  | Material  | Finish         | Length               | Item No.   |
|-----------------------------------------------------------------------------------------------------------|--|-----------|----------------|----------------------|------------|
| Gasket, for infill panel thickness 5–6.4 mm (3/16"–1/4")                                                  |  | Plastic   | transparent    | 2.5 m (8' 2 7/16")   | 403.56.925 |
|                                                                                                           |  |           |                | 3.5 m (11' 5 13/16") | 403.56.935 |
|                                                                                                           |  |           |                | 6 m (19' 8 1/4")     | 403.56.960 |
| Gasket, for infill panel thickness 7.7–8.3 mm (19/64"–21/64")                                             |  | Plastic   | transparent    | 2.5 m (8' 2 7/16")   | 403.79.925 |
|                                                                                                           |  |           |                | 3.5 m (11' 5 13/16") | 403.79.935 |
|                                                                                                           |  |           |                | 6 m (19' 8 1/4")     | 403.79.960 |
| Sliding brush set, for cleaning of running tracks, with Häfele logo, (2 pcs.)                             |  | Aluminum  | silver colored | –                    | 403.55.988 |
| Sliding brush set, for cleaning of running tracks, without Häfele logo, (2 pcs.)                          |  | Aluminum  | silver colored | –                    | 403.55.997 |
| Brush seal, self-adhesive, mounted onto front edge of the door to create a seal between the door and jamb |  | Synthetic | gray           | 10 m (32' 9 11/16")  | 403.54.531 |

### → Accessories

| Description                                                                                                           |  | Material        | Finish         | Length              | Item No.   |
|-----------------------------------------------------------------------------------------------------------------------|--|-----------------|----------------|---------------------|------------|
| Brush seal, self-adhesive, for protecting the inside from dust, mounted between 2 overlapping vertical frame profiles |  | Synthetic       | gray           | 10 m (32' 9 11/16") | 403.54.530 |
|                                                                                                                       |  |                 |                | 175 m (574' 1 3/4") | 403.54.513 |
| End bracket for all top guide tracks, for covering ends, screw mounted                                                |  | Steel           | silver colored | –                   | 403.55.991 |
|                                                                                                                       |  |                 | bronze         | –                   | 403.55.100 |
|                                                                                                                       |  |                 | black          | –                   | 403.55.301 |
|                                                                                                                       |  |                 | white          | –                   | 403.55.300 |
| Cover cap, for single bottom running track                                                                            |  | Stainless steel | silver colored | –                   | 403.55.060 |
|                                                                                                                       |  |                 | bronze         | –                   | 403.55.160 |
|                                                                                                                       |  |                 | black          | –                   | 403.55.401 |
|                                                                                                                       |  |                 | white          | –                   | 403.55.400 |
| Wall mounting bracket, for top guide track, includes mounting screw and set nut, mounted every 400 mm (15 3/4")       |  | Steel           | silver colored | –                   | 403.55.980 |
|                                                                                                                       |  |                 | bronze         | –                   | 403.55.101 |
|                                                                                                                       |  |                 | black          | –                   | 403.55.180 |
|                                                                                                                       |  |                 | white          | –                   | 403.55.780 |
| Center door stop for mounting into the top guide track                                                                |  | Plastic         | gray           | –                   | 403.50.945 |
| Roller pin for joining top guide tracks and bottom running tracks                                                     |  | Steel           | –              | –                   | 403.50.965 |
| Follower set for door, includes mounting screws, suitable for frame profile 10 and 50                                 |  | Aluminum        | silver colored | –                   | 403.50.979 |
|                                                                                                                       |  |                 | bronze         | –                   | 403.50.119 |
|                                                                                                                       |  |                 | black          | –                   | 403.50.401 |
|                                                                                                                       |  |                 | white          | –                   | 403.50.402 |

## Häfele Slido R-Aluflex 80 W

|            | Supplied with                           | Item No.   |
|------------|-----------------------------------------|------------|
| For 1 door | Running gear with plastic guide rollers | 403.50.941 |

### Note

Please order top guide and bottom running tracks, soft closing mechanism and other accessories separately.

### → Top Guide and Bottom Running Tracks

| Description                 |  | Material | Length           | silver     | bronze     | white      | black      |
|-----------------------------|--|----------|------------------|------------|------------|------------|------------|
| Single top guide track      |  | Aluminum | 2 m (6' 6 3/4")  | 403.36.902 | 403.36.102 | –          | –          |
|                             |  |          | 3 m (9' 10 1/8") | 403.36.903 | 403.36.103 | –          | –          |
|                             |  |          | 6 m (19' 8 1/4") | 403.36.906 | 403.36.106 | 403.36.810 | 403.36.813 |
| Double top guide track      |  | Aluminum | 2 m (6' 6 3/4")  | 403.36.912 | 403.36.112 | –          | –          |
|                             |  |          | 3 m (9' 10 1/8") | 403.36.913 | 403.36.113 | –          | –          |
|                             |  |          | 6 m (19' 8 1/4") | 403.36.916 | 403.36.116 | 403.36.811 | 403.36.814 |
| Triple top guide track      |  | Aluminum | 6 m (19' 8 1/4") | 403.36.926 | 403.36.126 | 403.36.812 | 403.36.815 |
| Single bottom running track |  | Aluminum | 2 m (6' 6 3/4")  | 403.36.932 | 403.36.132 | –          | –          |
|                             |  |          | 3 m (9' 10 1/8") | 403.36.933 | 403.36.133 | –          | –          |
|                             |  |          | 6 m (19' 8 1/4") | 403.36.936 | 403.36.136 | 403.36.600 | 403.36.603 |
| Double bottom running track |  | Aluminum | 2 m (6' 6 3/4")  | 403.36.942 | 403.36.142 | –          | –          |
|                             |  |          | 3 m (9' 10 1/8") | 403.36.943 | 403.36.143 | –          | –          |
|                             |  |          | 6 m (19' 8 1/4") | 403.36.946 | 403.36.146 | 403.36.601 | 403.36.604 |
| Triple bottom running track |  | Aluminum | 6 m (19' 8 1/4") | 403.36.956 | 403.36.156 | 403.36.602 | 403.36.605 |

### → Accessories

| Description                                                                 |  | Material        | Finish       | Item No.   |
|-----------------------------------------------------------------------------|--|-----------------|--------------|------------|
| End bracket for all guide tracks, for covering the sides, screw mounted     |  | Steel           | gray         | 403.55.991 |
|                                                                             |  |                 | white        | 403.55.300 |
|                                                                             |  |                 | bronze       | 403.55.100 |
|                                                                             |  |                 | black        | 403.55.301 |
| Center door stopper for mounting into the top guide track                   |  | Plastic         | gray         | 403.50.945 |
| Cover cap, for single running bottom track                                  |  | Stainless steel | gray         | 403.55.060 |
|                                                                             |  |                 | white        | 403.55.400 |
|                                                                             |  |                 | bronze       | 403.55.160 |
|                                                                             |  |                 | black        | 403.55.401 |
| Wall mounting bracket, for top guide track, required every 400 mm (15 3/4") |  | Steel           | gray         | 403.55.980 |
|                                                                             |  |                 | white        | 403.55.780 |
|                                                                             |  |                 | bronze       | 403.55.101 |
|                                                                             |  |                 | black        | 403.55.180 |
| Soft and self-closing mechanism, for door weights up to 15 kg (33 lbs.)     |  | Plastic         | black/gray   | 403.50.988 |
| Soft and self-closing mechanism, for door weights up to 40 kg (88 lbs.)     |  |                 | black/green  | 403.50.999 |
| Soft and self-closing mechanism, for door weights up to 80 kg (176 lbs.)    |  |                 | black/yellow | 403.50.989 |

### Note

Minimum door width with one soft and self-closing mechanism is 500 mm (19 5/8") and 830 mm (36 5/8") with 2.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.