

Häfele Slido R-Aluflex 80A

→ Door Components

Description		Material	Finish	Length	Item No.
Gasket, for infill panel thickness 5–6.4 mm (3/16"–1/4")		Plastic	transparent	2.5 m (8' 2 7/16")	403.56.925
				3.5 m (11' 5 13/16")	403.56.935
				6 m (19' 8 1/4")	403.56.960
Gasket, for infill panel thickness 7.7–8.3 mm (19/64"–21/64")		Plastic	transparent	2.5 m (8' 2 7/16")	403.79.925
				3.5 m (11' 5 13/16")	403.79.935
				6 m (19' 8 1/4")	403.79.960
Sliding brush set, for cleaning of running tracks, with Häfele logo, (2 pcs.)		Aluminum	silver colored	–	403.55.988
Sliding brush set, for cleaning of running tracks, without Häfele logo, (2 pcs.)		Aluminum	silver colored	–	403.55.997
Brush seal, self-adhesive, mounted onto front edge of the door to create a seal between the door and jamb		Synthetic	gray	10 m (32' 9 11/16")	403.54.531

→ Accessories

Description		Material	Finish	Length	Item No.
Brush seal, self-adhesive, for protecting the inside from dust, mounted between 2 overlapping vertical frame profiles		Synthetic	gray	10 m (32' 9 11/16")	403.54.530
				175 m (574' 1 3/4")	403.54.513
End bracket for all top guide tracks, for covering ends, screw mounted		Steel	silver colored	–	403.55.991
			bronze	–	403.55.100
			black	–	403.55.301
			white	–	403.55.300
Cover cap, for single bottom running track		Stainless steel	silver colored	–	403.55.060
			bronze	–	403.55.160
			black	–	403.55.401
			white	–	403.55.400
Wall mounting bracket, for top guide track, includes mounting screw and set nut, mounted every 400 mm (15 3/4")		Steel	silver colored	–	403.55.980
			bronze	–	403.55.101
			black	–	403.55.180
			white	–	403.55.780
Center door stop for mounting into the top guide track		Plastic	gray	–	403.50.945
Roller pin for joining top guide tracks and bottom running tracks		Steel	–	–	403.50.965
Follower set for door, includes mounting screws, suitable for frame profile 10 and 50		Aluminum	silver colored	–	403.50.979
			bronze	–	403.50.119
			black	–	403.50.401
			white	–	403.50.402