

→ **HAWA Clipo 36 G IF Set**

	<b>Supplied With</b>	<b>Item No.</b>
For 1 door	2 running gears 1 bottom guide 2 clamp shoes for glass 2 door stoppers with clip-in door stopper Mounting material	405.02.409






**Supplied With**

1 set

**Note**

Only use tempered safety glass. Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set separately.

→ **Tracks and Accessories**

	<b>Description</b>	<b>Material</b>	<b>Finish</b>	<b>Length/Door weight</b>	<b>Item No.</b>
	Upper track, pre-drilled, for screw mounting	Aluminum	anodized	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
	Upper track, pre-drilled, surface mounted	Aluminum	anodized	2.5 m (8' 2 7/16")	405.00.632
	Soft closing mechanism, optional One set includes two mechanisms. Two sets are required for dual soft closing of two doors.	Plastic and Aluminum	–	15.4–26 kg (34–57 lbs.)	405.10.074
				26–36 kg (57–79 lbs.)	940.48.045
	Service port for upper track (To access running gear after installation)	Plastic	gray	–	405.00.072
	Clip-on fascia	Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.23.902
	End cap set	Plastic	–	–	405.02.050