

→ HAWA Clipo 36 GPK/GPPK IF Set





	Version	Supplied With	Item No.
For 1 door	Clipo 36 GPK	2 running gears 1 clear threshold floor guide 2 door stoppers with clip-in door stopper Mounting material	405.02.410
	Clipo 36 GPPK	2 running gears 1 bottom guide 3 covers 2 door stoppers with clip-in door stopper Mounting material	405.02.411

Supplied With
1 set

Order Reference

Please order running and guide tracks and glass fixing profiles (GPK: top, GPPK: top and bottom) separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set separately.

→ Tracks and Accessories

	Description	Material	Finish	Length/Door weight	Item No.
	Glass fixing profile, for top and bottom of door, for glue mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.03.202
				3.5 m (11' 5 13/16")	405.03.203
	Upper track, pre-drilled, for screw mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
	Double upper track, pre-drilled, for screw mounting	Aluminum	anodized, silver	2.5 m (8' 2 7/16")	405.02.622
				3.5 m (11' 5 13/16")	405.02.623
	Soft closing mechanism, optional for screw mounting to housing. One set includes two mechanisms. Two sets are required for dual soft closing of two doors.	Plastic	gray	up to 15 kg (33 lbs.)	405.10.073
				15–27 kg (34–57 lbs.)	405.10.074
				26–36 kg (57–79 lbs.)	940.48.045
	Service port for upper track (to access running gear after installation)	Plastic	gray	–	405.00.072
	Service port for double upper track (to access running gear after installation)	Plastic	gray	–	405.00.074

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.