

→ HAWA Combino 65 H IF

	Version	Supplied with	Item No.
For 2 sliding doors	With clip-in door stopper	4 running gears 4 door stoppers (2 with clip-in door stopper/2 stoppers) 2 guides 1 door follower 1 set of mounting material	405.71.004
For 3 doors*		6 running gears 4 door stoppers (3 with clip-in door stopper/1 stopper) 3 guides 1 buffer set 1 set of mounting material	405.71.005

Note



Please order running and guide track separately.

*For a 3 door application the max. door width is 1350 mm (53 1/8")

→ Soft Closing Mechanism Set

	Version	Door weight	Supplied with	Item No.
For 2 or 3 doors	For 2 doors 1 set: For soft close on one side 2 sets: For soft close on both sides For 3 doors order 2 sets 1 set: Provides soft close for front center door into both directions 1 set: Provides soft close for 2 rear doors into one direction	Up to 65 kg (143 lbs.)	2 soft closing mechanism units 2 activators	405.11.323

→ Tracks and Accessories

Description		Material	Finish	Length	Item No.
Double running track, pre-drilled, guide track for glue mounting		Aluminum	anodized	2.5 m (8' 2 7/16")	405.70.713
				4.0 m (13' 1 1/2")	405.70.714
Single running track, pre-drilled, for door thickness > 28 mm (1 1/8")		Aluminum	anodized	2.5 m (8' 2 7/16")	405.69.603
				4.0 m (13' 1 1/2")	405.69.604
Guide track, bottom, for glue mounting		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Fixing profile for wood panel, pre-drilled, for clipping into single or double running track every 700–800 mm (27 9/16"–31 1/2")		Aluminum	anodized	–	406.31.400

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.