

EKU Divido 100 H Set


- For 1 sliding door without upper track

Item No.
941.00.111

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels	Plastic	white	2 pcs.
	Suspension bolt, M8 x 32 mm	Steel	zinc-plated	2 pcs.
	Set nut, M8	Steel	zinc-plated	2 pcs.
	Suspension plate	Steel	zinc-plated	2 pcs.
	Door stopper with adjustable retention spring	Plastic	gray	2 pcs.
	Lower guide	Plastic	anthracite gray	1 pc.
	Fixing screws	–	–	–

Individual Components

	Description	Material	Finish	Length	Item No.
	Single upper track, 39 x 41 mm (1 9/16" x 1 5/8")	Aluminum	unanodized	2.5 m (8' 2 7/16")	941.00.253
				3.5 m (11' 5 13/16")	941.00.353
				6 m (19' 8 1/4")	941.00.603
	Dual upper track, 73 x 31 mm (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 13/16")	941.12.935
				6 m (19' 8 1/4")	941.12.960
	Triple upper track 111 x 31 mm (4 3/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.425
				3.5 m (11' 5 13/16")	941.13.435
				6 m (19' 8 1/4")	941.13.460
	Spacer profile for wall mounting of single upper track 11 x 36 mm (7/16" x 1 7/16")	Plastic	gray	2 m (6' 6 3/4")	941.13.220
	Clip-in skirt, 10 x 42 mm (3/8" x 1 11/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.325
				3.5 m (11' 5 13/16")	941.12.335
				6 m (19' 8 1/4")	941.12.360
	Clip-on fascia to upper track, 7 x 60 mm (5/16" x 2 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.425
				3.5 m (11' 5 13/16")	941.12.435
				6 m (19' 8 1/4")	941.12.460
	Brush seal for clip-on fascia, 5 x 5 mm (3/16" x 3/16")	Plastic	gray	10 m (32' 9 11/16")	405.80.501
	End piece to fascia, one-sided, wall mounted, 51 x 60 mm (2" x 2 3/8")	Aluminum	anodized	–	941.12.060
	Clip piece for wood fascia, 97 x 29 x 9.5 mm (3 13/16" x 1 1/8" x 3/8"), mounted every 500 mm (19 11/16")	Aluminum	unanodized	–	940.60.065
	Soft close	–	–	10 - 60 kg (22 - 132 lbs.)	940.60.045
				61 - 100 kg (133 - 200 lbs.)	940.60.010
	Cover cap, for soft close	–	–	–	940.60.094
	Milling jig, for soft close	–	–	–	940.60.095

Dimensional data not binding. We reserve the right to alter specifications without notice.


Dimensions in mm
Inches are approximate

EKU Divido 100 GR Set




- For 1 sliding door without upper track

Item No.
941.12.000

Individual Components

	Description	Material	Finish	Qty.
	Running gear with four wheels	Plastic	white	2 pcs.
	Suspension bolt, M8 x 35 mm	Steel	zinc-plated	2 pcs.
	Set nut, M8	Steel	zinc-plated	2 pcs.
	Suspension plate	Aluminum	–	2 pcs.
	Door stopper with adjustable retention spring	Plastic	gray	2 pcs.
	Lower guide with plastic horizontal wheels	Steel	zinc-plated	1 pc.
	Fixing screws	–	–	1 set

Individual Components

	Description	Material	Finish	Length	Item No.
	Single upper track, 39 x 41 mm (1 9/16" x 1 5/8")	Aluminum	unanodized	2.5 m (8' 2 7/16")	941.00.253
				3.5 m (11' 5 25/32")	941.00.353
				6 m (19' 8 1/4")	941.00.603
	Dual upper track, 73 x 31 mm (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 25/32")	941.12.935
				6 m (19' 8 1/4")	941.12.960
	Spacer profile for wall mounting of single upper running track, 11 x 36 mm (7/16" x 1 7/16")	Plastic	gray	2 m (6' 6 3/4")	941.13.220
	Clip-in skirt, 10 x 42 mm (13/32" x 1 11/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.325
				3.5 m (11' 5 25/32")	941.12.335
				6 m (19' 8 1/4")	941.12.360
	Clip-on fascia to upper running track, 7 x 60 mm (5/16" x 2 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.425
				3.5 m (11' 5 25/32")	941.12.435
				6 m (19' 8 1/4")	941.12.460
	Brush seal for clip-on fascia, 5 x 5 mm (3/16" x 3/16")	Plastic	gray	10 m (32' 9 11/16")	405.80.501
	End piece to fascia, one-sided, wall mounted, 51 x 60 mm (2" x 2 3/8")	Aluminum	anodized	–	941.12.060
	Soft close 10 – 60 kg (22 – 132 lbs.)	–	–	–	940.60.045
	Soft close 61 – 100 kg (135 – 220 lbs.)				940.60.010
	Cover cap for notched service access in track				940.60.094
	Drill jig for notched service access in track				940.60.095

Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.

Aluminum frame profiles pages 1.226-1.227

Dimensions in mm
Inches are approximate

EKU Divido

Individual Components

	Description	Material	Finish	Length	Item No.
	Frame profile, horizontal, 26 x 60 mm (1" x 2 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.125
				3.5 m (11' 5 25/32")	941.12.135
				6 m (19' 8 1/4")	941.12.160
	Frame profile, vertical, 30 x 29 mm (1 3/16" x 1 1/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.225
				3 m (9' 10 1/8")	941.12.230
				6 m (19' 8 1/4")	941.12.260
	Mullion for front separation, 26 x 35 mm (1" x 1 3/8")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.625
				3.5 m (11' 5 25/32")	941.12.635
				6 m (19' 8 1/4")	941.12.660
	Cover profile for vertical frame profile, 15 x 14 mm (5/8" x 9/16")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.525
				3 m (9' 10 1/8")	941.12.530
				6 m (19' 8 1/4")	941.12.560
	Glass holding profile, 10 x 8 mm (13/32" x 5/16")	Plastic	transparent	20 m (65' 7 13/32")	941.13.091
	Sealing profile, 17 x 11 mm (11/16" x 7/16")	Rubber	gray	10 m (32' 9 11/16")	941.13.090
	Cover profile with integrated brush seal groove, 10 x 32 mm (13/32" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.725
				3 m (9' 10 1/8")	941.12.730
				6 m (19' 8 1/4")	941.12.760
	Brush seal for cover profile, 5 x 5 mm (3/16" x 3/16")	Plastic	gray	10 m (32' 9 11/16")	405.80.501
	Centering piece for 8 mm (5/16") thick glass or wood in-fill panel, 10 x 8 x 10 mm (3/8" x 5/16" x 13/32")	Plastic	transparent	–	941.12.061
	Drilling and mortise jig for aluminum frame profiles. Used to produce the fixing holes and the cutouts Required tools for the router: 10 mm (13/32") carbide-tipped router bit 17 mm (11/16") diameter collar	–	–	–	941.12.090
	Screw set for aluminum frame profile	–	–	–	941.12.091
	Flush handle for gluing onto glass sliding doors, square shape	Plastic	lacquered aluminum color	–	941.12.051
	Flush handle for gluing onto glass sliding doors, rectangular shape	Plastic	lacquered aluminum color	–	941.12.050

Supplied With

- 2 Gripping plates
- 2 Blue laminated inserts
- 2 Double-adhesive tape

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate