

→ HAWA Clipo 16 H IF Set

	Version	Supplied with	Item No.
For 2 doors	With clip-in door stopper	4 running gears with housings 1 door follower 2 door stoppers with clip-in door stopper 2 floor guides	405.82.216

**Supplied With**

1 set

**Note**

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description		Min. cabinet top thickness	Material	Finish	Length/Door weight	Item No.
Upper track, for gluing into groove (polyurethane glue recommended)		19 (3/4")	Aluminum	bright	2.5 m (8' 2 7/16")	405.87.042
					3.5 m (11' 5 13/16")	405.87.043
Upper track, with rotating fasteners (not suitable for hard wood)		19 (3/4")	Aluminum	bright	2.5 m (8' 2 7/16")	405.87.092
					3.5 m (11' 5 13/16")	405.87.093
Upper track, pre-drilled, for screw mounting		30 (1 3/16")	Aluminum	bright	2.5 m (8' 2 7/16")	405.87.082
					3.5 m (11' 5 13/16")	405.87.083
Double upper track, pre-drilled, for screw mounting		19 (3/4")	Aluminum	bright	2.5 m (8' 2 7/16")	405.90.032
					3.5 m (11' 5 13/16")	405.90.033
Lower guide channel, with harpoon ribs		–	Plastic	anthracite	2.5 m (8' 2 7/16")	405.98.517
Soft closing mechanism, optional for screw mounting to housing  One set includes two mechanisms. Two sets are required for dual soft closing of two doors.		–	Plastic	gray	<8 kg (17.6 lbs.)	405.10.077
					8 kg–16 kg (17.6–35 lbs.)	405.10.075
Service port, for upper track with rotating fasteners (access running gear after installation)		–	Plastic	gray	–	405.83.180
Service port, for upper track for screw mounting (access running gear after installation)		–	Plastic	gray	–	405.83.181