

→ HAWA Combino 20/35 H IF

	Version	Supplied with	Model series	Item No.
For 2 doors	With clip-in door stopper	4 running gears with housings 2 guides 4 door stoppers (2 with clip-in door stopper, 2 stoppers) 1 door follower 1 set of mounting material	Combino 20 H IF	405.91.625
			Combino 35 H IF	405.91.723
For 3 doors		6 running gears 3 guides 4 door stoppers (3 with clip-in door stopper, 1 stopper) 1 buffer set 1 set of mounting material	Combino 35 H IF	405.91.724

Supplied With

1 set

Note

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Soft Closing Mechanism Set

	Door weight	Supplied with	Item No.
For 2 doors	For up to 18 kg (39 lbs.)	2 soft closing mechanism units	405.10.003
	For up to 18–40 kg (39–88 lbs.)	2 door followers, wide	405.10.005








Supplied With

1 set

Note

Please order the adapter set for soft closing mechanism. It is required!

→ Tracks and Accessories

Description		Material	Finish	Length	Item No.
Single running track, pre-drilled		Aluminum	mill	2.5 m (8' 2 7/16")	406.30.967
				3.5 m (11' 5 13/16")	406.30.976
Double running track, pre-drilled		Aluminum	mill	2.5 m (8' 2 7/16")	406.31.964
				3.5 m (11' 5 13/16")	406.31.973
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Clip-on fascia		Aluminum	anodized	2.5 m (8' 2 7/16")	406.34.942
				3.5 m (11' 5 13/16")	406.34.943
Clip-on adapter for wood fascia W x H: 40 x 24 (1 9/16" x 15/16")		Aluminum	mill	–	406.35.900
Center door stopper, required only on 3 door application		Steel/ Plastic	–	–	406.32.080
Adapter set for soft closing mechanism		Steel	zinc-plated	–	405.10.092

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.