

→ HAWA Clipo 36 H IF Set

	Supplied with	Item No.
For 2 doors	4 running gears with housings 1 door follower 2 guides 4 door stoppers with clip-in door stopper Mounting material	405.02.404
For 3 doors	6 running gears with housings 3 guides 4 door stoppers with clip-in door stopper 2 buffers Mounting material	405.02.405

**Supplied With**

1 set

**Note**

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description	Image	Material	Finish	Length/Door weight	Item No.
Upper track, pre-drilled, for screw mounting		Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Soft closing mechanism, optional for screw mounting to housing		Plastic	gray	up to 26 kg (57 lbs.)	405.10.074
One set includes two mechanisms. Two sets are required for dual soft closing of two doors.				26–36 kg (57–79 lbs.)	940.48.045
Service port for upper track (access running gear after installation)		Plastic	gray	–	405.00.072

→ HAWA Clipo 36 HM IF Set

	Version	Supplied with	Item No.
For 1 door	With clip-in door stopper	2 running gears with housings 2 door stoppers 1 floor guide	405.02.408

**Supplied With**

1 set

**Note**

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Tracks and Accessories

Description	Image	Material	Finish	Length/Door weight	Item No.
Upper track, pre-drilled, for screw mounting		Aluminum	anodized silver	2.5 m (8' 2 7/16")	405.00.622
				3.5 m (11' 5 13/16")	405.00.623
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Soft closing mechanism, optional for screw mounting to housing		Plastic	-	up to 15 kg (33 lbs.)	405.10.073
				15.4–26 kg (34–57 lbs.)	405.10.074
Service port for upper track (to access running gear after installation)		Plastic	gray	-	405.00.072
Soft stop, for screw mounting to the back of the front door Optional for a two door application		-	-	-	405.93.012

→ HAWA Combino 20/35 H IF

	Version	Supplied with	Model series	Item No.
For 2 doors	With clip-in door stopper	4 running gears with housings 2 guides 4 door stoppers (2 with clip-in door stopper, 2 stoppers) 1 door follower 1 set of mounting material	Combino 20 H IF	405.91.625
		6 running gears 3 guides 4 door stoppers (3 with clip-in door stopper, 1 stopper) 1 buffer set 1 set of mounting material	Combino 35 H IF	405.91.723
For 3 doors			Combino 35 H IF	405.91.724

**Supplied With**

1 set

**Note**

Please order running and guide tracks separately. Soft closing mechanism on one side is possible from pitch length of min. 260 mm (10 1/4"), both sides from 460 mm (18 1/8"). Please order soft closing mechanism set for soft closing on both sides separately.

→ Soft Closing Mechanism Set

	Door weight	Supplied with	Item No.
For 2 doors	For up to 18 kg (39 lbs.)	2 soft closing mechanism units	405.10.003
	For up to 18–40 kg (39–88 lbs.)	2 door followers, wide	405.10.005





**Supplied With**

1 set

**Note**

Please order the adapter set for soft closing mechanism. It is required!

→ Tracks and Accessories

Description	Image	Material	Finish	Length	Item No.
Single running track, pre-drilled		Aluminum	mill	2.5 m (8' 2 7/16")	406.30.967
				3.5 m (11' 5 13/16")	406.30.976
Double running track, pre-drilled		Aluminum	mill	2.5 m (8' 2 7/16")	406.31.964
				3.5 m (11' 5 13/16")	406.31.973
Lower guide channel		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
				3.5 m (11' 5 13/16")	406.73.804
Clip-on fascia		Aluminum	anodized	2.5 m (8' 2 7/16")	406.34.942
				3.5 m (11' 5 13/16")	406.34.943
Clip-on adapter for wood fascia W x H: 40 x 24 (1 9/16" x 15/16")		Aluminum	mill	–	406.35.900
Center door stopper, required only on 3 door application		Steel/ Plastic	–	–	406.32.080
Adapter set for soft closing mechanism		Steel	zinc-plated	–	405.10.092

→ HAWA Combino 65 H IF

	Version	Supplied with	Item No.
For 2 sliding doors		4 running gears 4 door stoppers (2 with clip-in door stopper/2 stoppers) 2 guides 1 door follower 1 set of mounting material	405.71.004
With clip-in door stopper		6 running gears 4 door stoppers (3 with clip-in door stopper/1 stopper) 3 guides 1 buffer set 1 set of mounting material	
For 3 doors*			405.71.005

**Note**

Please order running and guide track separately.

\*For a 3 door application the max. door width is 1350 mm (53 1/8")

→ Soft Closing Mechanism Set

	Version	Door weight	Supplied with	Item No.
For 2 or 3 doors	<b>For 2 doors</b> 1 set: For soft close on one side 2 sets: For soft close on both sides <b>For 3 doors order 2 sets</b> 1 set: Provides soft close for front center door into both directions 1 set: Provides soft close for 2 rear doors into one direction	Up to 65 kg (143 lbs.)	2 soft closing mechanism units 2 activators	405.11.323

→ Tracks and Accessories

Description	Image	Material	Finish	Length	Item No.
Double running track, pre-drilled, guide track for glue mounting		Aluminum	anodized	2.5 m (8' 2 7/16")	405.70.713
Single running track, pre-drilled, for door thickness > 28 mm (1 1/8")				4.0 m (13' 1 1/2")	405.70.714
Guide track, bottom, for glue mounting		Plastic	gray	2.5 m (8' 2 7/16")	406.73.803
Fixing profile for wood panel, pre-drilled, for clipping into single or double running track every 700–800 mm (27 9/16"–31 1/2")				3.5 m (11' 5 13/16")	406.73.804
		Aluminum	anodized	–	406.31.400