


Häfele Slido F-Flush52 20A




- > For flush, inset doors
- > Door height: <1,600 mm (63")
- > Door width: 450–900 mm (17 11/16"–35 7/16")
- > Door thickness: 18–22 mm (23/32"–7/8")
(including handle: 45 mm (1 3/4"))
- > Door offset: 50 or 70 mm (1 31/32" or 2 3/4")
- > Installation depth: 70 mm (2 3/4")
- > Material thickness: Min. 18 mm (23/32")
- > Bottom running
- > Adjustment facility: ±2 mm (3/32") via knurled screw without tools
- > Suitable for 2 symmetrical doors
- > Without handle, with recessed grip profiles or flush pull handles
- > Running and guide tracks for groove mounting, running gears for groove mounting and screw mounting




→ Häfele Slido F-Flush52 20A Set

Version	Supplied with	Internal cabinet width	For door width	black anodized	silver colored anodized
For 2 doors	2 running tracks 4 running gears, bottom 4 guide parts, top Spacer plates for door thickness 18 and 20 mm (23/32" and 25/32")	908 (35 3/4") 1208 (47 9/16") 1508 (59 3/8") 1808 (71 3/16")	450 (17 11/16") 600 (23 5/8") 750 (29 1/2") 900 (35 7/16")	407.40.097 407.40.096 407.40.095 407.40.094	407.40.093 407.40.092 407.40.091 407.40.090

Running distance of door



Starting point



End position