

Hawa Bifold 30 Sets

Description	Weight capacity/panel	Fitting set type	Supplied with	Item No.
Without upper track and guide channel	40 kg (88 lbs.)	2 doors	1 running gear 2 suspension plates 1 lower pivot 1 upper pivot 1 stop bracket 3 butt hinges, steel galvanized 1 height adjustment pin	407.58.003
	30 kg (66 lbs.)	4 doors	2 running gears 2 suspension plates 1 lower pivot 1 upper pivot 2 stop brackets 9 butt hinges, steel galvanized 1 height adjustment pin 2 lower guides	407.58.004
	30 kg (66 lbs.)	6 doors	3 running gears 3 suspension plates 1 lower pivot 1 upper pivot 3 stop brackets 15 butt hinges, steel galvanized 1 height adjustment pin 3 lower guides	407.58.006

Installation Plan

For a 4 door opening where 2 doors fold to the left and 2 doors fold to the right side of opening, please order 2 sets of the 2 door set.

→ Individual Components

Description	Image	Material	Finish	Length	Item No.
Upper tracks, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	940.80.140
				1.6 m (5' 3")	940.80.160
				1.8 m (5' 10 7/8")	940.80.180
				2 m (6' 6 3/4")	940.80.200
				2.2 m (7' 2 5/8")	940.80.220
				2.5 m (8' 2 7/16")	940.80.250
				3 m (9' 10 1/8")	940.80.300
				4 m (13' 1 1/2")	940.80.400
Butt hinge		Steel	galvanized	–	407.78.989
			nickel-plated, dull brushed	–	407.78.685
			brass-plated, dull brushed	–	407.78.881
Lower guide channel, pre-drilled 20 x 20 mm (25/32" x 25/32")		Aluminum	clear anodized	2.5 m (8' 2 7/16")	941.00.925
				6 m (19' 8 1/4")	941.00.960

Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.

Note

Butt hinges included in fitting set are for a maximum panel height of 2.2 m (7' 2 5/8"), order additional hinges based on the chart below

up to 2.2 m (7' 2 5/8")	=	3
up to 2.7 m (8' 10 5/16")	=	4
up to 3.2 m (10' 6")	=	5

Flush pulls	pages 1.394–1.396
Pull handles	pages 2.4–2.29