

LUTRON STAND ALONE

WALL DIMMING CONTROLS 2 WIRE FORWARD PHASE (CL)

0  100%

Diva and Ariadni Wall Dimmer

Diva

Ariadni



Diva	820.66.351	820.66.451	820.66.651	820.66.751
SRP	\$82.50	\$82.50	\$82.50	\$82.50
Ariadni	-	820.66.454	820.66.654	820.66.754
SRP	-	\$66.00	\$66.00	\$66.00
L x W x H	115 x 57 x 55 (4 1/2" x 2 1/4" x 2 3/16")			
Wattage	150			
Material	Plastic, Aluminum			
Color				
	black	light almond	ivory	white
Supplied with	Mounting screws, wire nuts, installation instructions			



Diva and Ariadni Wall Plate

Diva

Ariadni



Diva	820.66.353	820.66.453	820.66.653	820.66.753
SRP	\$12.10	\$12.10	\$12.10	\$12.10
Ariadni	-	820.66.456	820.66.656	820.66.756
SRP	-	\$11.55	\$11.55	\$11.55
L x W x H	120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8")			
Material	Plastic			
Color				
	black	light almond	ivory	white
Supplied with	Mounting screws, cover plate			



- > Control up to 150 W of LED light bars, LED strip lights or pucks
- > Great for dining rooms, bedrooms, bathrooms, closets and kitchens
- > Dimming offers energy savings over standard wall switches
- > Dimming to 1% with smooth, continuous, flicker-free performance
- > Arrives ready to install
- > Input voltage: 110 - 120 VAC, 60 Hz
- > Operate between 32 °F (0 °C) and 104 °F (40 °C)
- > 0% to 90% humidity, non-condensing
- > 12 VDC E-Series drivers see page 145
- > 24 VDC E-Series drivers see page 147
- > Lutron drivers see pages 144, 146, 148, 149



Note

For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. **Compatible with E-series and Lutron Low Voltage Drivers.** DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.