


LUTRON STAND ALONE

WALL DIMMING CONTROLS 2 WIRE LOW VOLTAGE (LV)



Wall Dimming Controls, 110 - 120 VAC Diva 820.66.352 820.66.452 820.66.652 820.66.752 Diva Ariadni SRP \$159.50 \$159.50 \$159.50 \$159.50 Ariadni 820.66.455 820.66.655 820.66.755 SRP \$110.00 \$110.00 \$110.00 115 x 57 x 55 (4 1/2" x 2 1/4" x 2 3/16") LxWxHWattage Material Plastic, Aluminum Color light almond ivory white black Supplied Mounting screws, wire nuts, installation instructions with

Wall Plates



| Diva | 820.66.353 | 820.66.453 | 820.66.653 | 820.66.753 |
|-----------------------|--|-----------------|------------|------------|
| SRP | \$12.10 | \$12.10 | \$12.10 | \$12.10 |
| Ariadni | - | 820.66.456 | 820.66.656 | 820.66.756 |
| SRP | - | \$11.55 | \$11.55 | \$11.55 |
| $L \times W \times H$ | 120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8") | | | |
| Material | Plastic | | | |
| Color | | | | |
| | black | light almond | ivory | white |
| Supplied with | Mounting screv | vs, cover plate | | |



- > Control multiple LED light bars, LED strip lights and pucks up to 600 W
- > Great for dining rooms, bedrooms, bathrooms, and kitchens
- > Dimming offers energy savings over standard wall switches
- > Dimming to 1% with smooth, continuous, flicker-free performance
- > Arrives ready to install
- Input voltage: 110 120 VAC, 60 Hz, 600 VA / 450 W
- > Operate between 32 °F (0 °C) and 104 °F (40 °C)
- > 0% to 90% humidity, non-condensing
- > 12 VDC E-Series drivers see page 145
- > 24 VDC E-Series drivers see page 147
- > Lutron drivers see pages 144, 146, 148, 149



Note

For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. **Compatible with E-series and Lutron Low Voltage Drivers**. DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.



LUTRON STAND ALONE

WALL DIMMING CONTROLS 2 WIRE FORWARD PHASE (CL)




Diva and Ariadni Wall Dimmer Diva 820.66.351 820.66.451 820.66.651 820.66.751 Diva Ariadni **SRP** \$82.50 \$82.50 \$82.50 \$82.50 Ariadni 820.66.454 820.66.654 820.66.754 SRP \$66.00 \$66.00 \$66.00 115 x 57 x 55 (4 1/2" x 2 1/4" x 2 3/16") LxWxHWattage Plastic, Aluminum Material Color light almond | ivory white black Supplied Mounting screws, wire nuts, installation instructions with

Diva and Ariadni Wall Plate









| Diva | 820.66.353 | 820.66.453 | 820.66.653 | 820.66.753 |
|----------|--|------------|------------|------------|
| SRP | \$12.10 | \$12.10 | \$12.10 | \$12.10 |
| Ariadni | - | 820.66.456 | 820.66.656 | 820.66.756 |
| SRP | - | \$11.55 | \$11.55 | \$11.55 |
| LxWxH | 120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8") | | | |
| Material | Plastic | | | |
| | | | | |

Color

black light almond ivory white

Supplied with Mounting screws, cover plate



- > Control up to 150 W of LED light bars, LED strip lights or pucks
- > Great for dining rooms, bedrooms, bathrooms, closets and kitchens
- Dimming offers energy savings over standard wall switches
- > Dimming to 1% with smooth, continuous, flicker-free performance
- > Arrives ready to install
- > Input voltage: 110 120 VAC, 60 Hz
- > Operate between 32 °F (0 °C) and 104 °F (40 °C)
- > 0% to 90% humidity, non-condensing
- > 12 VDC E-Series drivers see page 145
- > 24 VDC E-Series drivers see page 147
- > Lutron drivers see pages 144, 146, 148, 149



Note

For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. **Compatible with E-series and Lutron Low Voltage Drivers**. DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.



Diva Wall Dimmer

LUTRON STAND ALONE

WALL DIMMING CONTROLS 2 WIRE CASÉTA PRO




| Item No. | 820.66.300 | 820.66.400 | 820.66.410 | 820.66.780 |
|-----------------------|-------------------|---------------------|---------------------|------------|
| SRP | \$242.00 | \$242.00 | \$242.00 | \$242.00 |
| $L \times W \times H$ | 115 x 57 x 55 (4 | 1 1/2" x 2 1/4" x 2 | 2 3/16") | |
| Wattage | 250 | | | |
| Material | Plastic, Aluminum | | | |
| Color | | | | |
| | black | light almond | ivory | white |
| Supplied with | Mounting screv | vs, wire nuts, ins | tallation instructi | ons |

Diva Wall Plate



| Diva | 820.66.353 | 820.66.453 | 820.66.653 | 820.66.753 |
|-----------------------|--|-----------------|------------|------------|
| SRP | \$12.10 | \$12.10 | \$12.10 | \$12.10 |
| $L \times W \times H$ | 120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8") | | | |
| Material | Plastic | | | |
| | | | | |
| Color | | | | |
| Coloi | | | | |
| | black | light almond | ivory | white |
| Supplied with | Mounting screv | vs, cover plate | | |







- > Control multiple LED light bars, LED strip lights and pucks up to 250 W
- > Great for dining rooms, bedrooms, bathrooms, closets and kitchens
- > Dimming to 1% offers energy savings over standard wall switches
- > Single pole/multi-location
- > 250 W dimmable LED/CFL
- > 1000 W incandescent/halogen; 1000 VA MLV
- > Neutral optional
- > 434 MHz
- > Works with Remote and Gateway for multiple Control locations
- > Operate between 32 °F (0 °C) and 104 °F (40 °C)
- > 0% to 90% humidity, non-condensing
- > 12 VDC E-Series drivers see page 145
- > 24 VDC E-Series drivers see page 147
- > Lutron drivers see pages 144, 146, 148, 149



Note

For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. **Compatible with E-series and Lutron Low Voltage Drivers**. DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.





LUTRON STAND ALONE

CASÉTA WALL DIMMER



Remote Control for Caséta Wall Dimmer















- > Dimming control
- > 4-button with raise/lower and light icon engraving
- > Pair additional remotes to main wall dimmer for added dimming control locations
- > 3 V- 10 mA
- > Uses single CR 2032 battery

| Diva Wall Plate | | | | | |
|-----------------|---------------|--|--------------|------------|------------|
| | Diva | 820.66.353 | 820.66.453 | 820.66.653 | 820.66.753 |
| | SRP | \$12.10 | \$12.10 | \$12.10 | \$12.10 |
| | LxWxH | 120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8") | | | |
| | Material | Plastic | | | |
| Turn screws | Color | black | light almond | ivory | white |
| to loosen. | Supplied with | Mounting screv | | | 1 |
| | | | | | |





Gateway smart bridge for Caséta Pro. 5 V

W x H x D: 70 x 70 x 30 mm (2 3/4" x 2 3/4" x 1 3/16") Plastic. white

> Item No. 830.69.887 SRP \$374.00 Supplied With

120 V - 5 V, 300 mA Power supply



- > Enables control of lights, shades, and temperature using the Lutron App
- > Compatible with Caséta® Wireless dimmers and switches, Serena® battery-powered shades, Lutron Wireless Thermostat, Nest Learning Thermostat, and select Honeywell® Wi-Fi thermostats
- > Easy to install; just plugs into your Wi-Fi router
- > Uses Clear Connect® wireless technology no callbacks



Mounting bracket for remote control, allows for easy installation of a remote control over an existing wall box or directly on any wall surface.

W x H x D: 95 x 35 x 10 mm (3 3/4" x 1 3/8" x 3/8") Plastic, clear

> Item No. 825.73.775 SRP \$18.17



Lutron App for Smart Devices

- > Works in conjunction with the Caséta® Pro Wall Dimmer and Smart Bridge PRO
- > Control individual lights, shades, and thermostats—even when you're away from home
- > Add scenes to control multiple lights and shades with a
- > Schedule scenes to adjust lights and shades automatically
- > Download for free from the App StoreSM or Google Play™

