


LUTRON STAND ALONE

WALL DIMMING CONTROLS 2 WIRE LOW VOLTAGE (LV)



Wall Dimming Controls, 110 - 120 VAC Diva 820.66.352 820.66.452 820.66.652 820.66.752 Diva Ariadni SRP \$159.50 \$159.50 \$159.50 \$159.50 Ariadni 820.66.455 820.66.655 820.66.755 SRP \$110.00 \$110.00 \$110.00 115 x 57 x 55 (4 1/2" x 2 1/4" x 2 3/16") LxWxHWattage Material Plastic, Aluminum Color light almond ivory white black Supplied Mounting screws, wire nuts, installation instructions with

Wall Plates



Diva	820.66.353	820.66.453	820.66.653	820.66.753
SRP	\$12.10	\$12.10	\$12.10	\$12.10
Ariadni	-	820.66.456	820.66.656	820.66.756
SRP	-	\$11.55	\$11.55	\$11.55
$L \times W \times H$	120 x 70 x 10 (4 3/4" x 2 3/4" x 3/8")			
Material	Plastic			
Color				
	black	light almond	ivory	white
Supplied with	Mounting screws, cover plate			



- > Control multiple LED light bars, LED strip lights and pucks up to 600 W
- > Great for dining rooms, bedrooms, bathrooms, and kitchens
- > Dimming offers energy savings over standard wall switches
- > Dimming to 1% with smooth, continuous, flicker-free performance
- > Arrives ready to install
- Input voltage: 110 120 VAC, 60 Hz, 600 VA / 450 W
- > Operate between 32 °F (0 °C) and 104 °F (40 °C)
- > 0% to 90% humidity, non-condensing
- > 12 VDC E-Series drivers see page 145
- > 24 VDC E-Series drivers see page 147
- > Lutron drivers see pages 144, 146, 148, 149



Note

For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. **Compatible with E-series and Lutron Low Voltage Drivers**. DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.



Lutron stand alone

Wall dimming controls 2 wire low voltage (LV)



Wall dimming controls - 110-120 VAC









> Material: Plastic, Aluminum

> Wattage: 600

 $> L \times W \times H$: 115 x 57 x 55 mm

(4 1/2" x 2 1/4" x 2 3/16")


> Supplied with: Mounting screws, wire nuts, installation

instructions

Color	Diva	Ariadni
Light almond	820.66.452	820.66.455
Ivory	820.66.652	820.66.655
White	820.66.752	820.66.755

light almond	ivory	white	

Wall plates



Control multiple LED light bars, LED strip lights and pucks up to 600

Great for dining rooms, bedrooms, bathrooms, and kitchens.

Dimming offers energy savings over standard wall switches.

Dimming to 1% with smooth, continuous, flicker-free performance. Arrives ready to install.

Input voltage: 110 - 120 VAC, 60 Hz, 600 VA / 450 W

Operate between 32 °F (0 °C) and 104 °F (40 °C).

0% to 90% humidity, non-condensing 12 VDC E-Series drivers see page 134. 24 VDC E-Series drivers see page 136. Lutron drivers see pages 133, 135, 137, 138.

> Material: Plastic

 $> L \times W \times H$: 120 x 70 x 10 mm

(4 3/4" x 2 3/4" x 3/8")


> Supplied with: Mounting screws, cover plate

Color	Diva	Ariadni
Light almond	820.66.453	820.66.456
lvory	820.66.653	820.66.656
White	820.66.753	820.66.756

	ı		
		l	
light almond	ivory	white	
ng. it can riorica	,	***	



For installation by a qualified electrician in accordance with all local and national electrical codes. Use copper conductors only. For indoor use only. Check to see that the driver type and rating are suitable for the application. Compatible with E-series and Lutron Low Voltage Drivers. DO NOT install if product has any visible damage. If moisture or condensation is evident, allow the product to dry completely before installation.



Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice