

LUTRON

LED DRIVER

Wireless Receiver, required



Item No.	833.01.818
SRP	\$130.00
Output voltage	120 VAC
Mounting	Surface/threaded
Material/Finish	Plastic, white



- > Controls up to 3 Eco-system drivers
- > Uses Lutron Clear Connect® RF technology
- > Designed to give a linear response to changes in viewed light level
- > 2 wire connection between optional sensor and control module – the wires are interchangeable to eliminate miswiring
- > Programmed rapid start design ensures full rated lamp life
- > Lamps turn on to any dimmed level without flashing to full brightness
- > End-of-lamp-life protection circuitry ensures safe operation
- > Ultra-quiet operation
- > Non-volatile memory restores all ballast settings after power failure
- > 100% performance tested at factory

Note

Drivers and receivers must be installed by licensed electrician and are subject to applicable national, state and local electrical codes.



LOX5

Lutron

LED driver

Wireless receiver - required



Material/Color: Plastic, white
Output voltage: 120 VAC
Mounting: Surface/threaded

Item No.
833.01.818

•

Controls up to 3 Ecosystem® drivers.

Uses Lutron Clear Connect® RF technology.

Designed to give a linear response to changes in viewed light level. 2 wire connection between optional sensor and control module – the wires are interchangeable to eliminate miswiring.

Programmed rapid start design ensures full rated lamp life. Lamps turn on to any dimmed level without flashing to full brightness.

End-of-lamp-life protection circuitry ensures safe operation. Ultra-quiet operation

Non-volatile memory restores all ballast settings after power failure. 100% performance tested at factory.

Note

Drivers and receivers must be installed by licensed electrician and are subject to applicable national, state and local electrical codes.



Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to atter specifications without notice