

LED 2048

RECESS/SURFACE MOUNTED LIGHT, MULTI-WHITE



12 V SYSTEM

IP20

- > Light color and brightness can be adjusted for any area of the house via multi white mixer
- > Optional surface mounted housing provides flexibility in installation
- > Dimmable via multi-white mixer only
- > Multi-white mixer can handle up to 30 W;
Max. 10 multi-white mixers with 1-10 remote controls within a radius of 15 m (49')

2700 K	5000 K	120°
290 lx	345 lx	250 mm (9 13/16")
110 lx	130 lx	500 mm (19 11/16")
60 lx	70 lx	750 mm (29 1/2")
40 lx	45 lx	1000 mm (39 3/8")

Item No.	833.72.310		833.72.311	833.72.400
SRP	\$30.00		\$30.00	\$30.00
Light Color (K)	2700 warm white to 5000 cool white			
Drill hole	Ø55 mm (2 3/16")			
Ø x H	65 x 12 mm (2 9/16" x 1/2")			
Wattage	3			
LEDs	60			
Lumen	255			
Lumen per watt	85			
CRI	2700 K: 90; 5000 K: 83			
Energy Efficiency class	A+			
Weighted energy consumption (kWh/1.000 h)	3.30			
Material	Steel			
Finish	polished chrome plated	silver colored	stainless steel colored	
Supplied with	2 m (78 3/4") lead			
Note Loox Lights and Drivers are "Suitable for use within Closet Storage Spaces"				

Recess/surface mounted lights

Multi-white, drill hole Ø: 55 mm (2 3/16")


Häfele Loox LED 2048/3039

Voltage V	Number of LEDs	Color temperature K	Wattage W	Luminous flux lm	Luminous efficacy lm/W	Color rendering index CRI R _a	Weighted energy consumpt. kWh/1000 h	Stainless steel colored	Silver colored	Polished chrome- plated
12 V	Häfele Loox LED 2048									
	60	2700 5000	3	255	85	90 83	3.3	833.72.400	833.72.311	833.72.310
24 V	Häfele Loox LED 3039									
	60	2700 5000	3	258	85	90 83	3.3	833.75.160	833.75.131	833.75.130




> Housing, Plastic

Color	Item No.
Stainless steel colored	833.72.804
Silver colored	833.72.803
Polished chrome-plated	833.72.802



Recess mounting



Surface mounting



Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.