

Recess/surface mounted lights

Monochrome, drill hole Ø: 58 mm (2 5/16"), 12 V/24 V

Häfele Loox LED 2094/3094


> LEDs:	6
> Wattage:	2.5 W

Voltage V	Quantity LEDs	Color temperature K	Wattage W	Luminous flux lm	Luminous efficacy lm/W	Chrome colored	Black	White	Bronze colored	Nickel colored
5 12 V	LED 2094									
	120	2700	2.5	135	54	833.72.530	833.72.534	833.72.538	833.72.542	833.72.546
		3000	2.5	150	60	833.72.531	833.72.535	833.72.539	833.72.543	833.72.547
		4000	2.5	160	64	833.72.532	833.72.536	833.72.540	833.72.544	833.72.549
		5000	2.5	165	66	833.72.533	833.72.537	833.72.541	833.72.545	833.72.548
5 24 V	LED 3094									
	120	2700	2.5	140	56	833.75.320	833.75.324	833.75.328	833.75.332	833.75.546
		3000	2.5	160	64	833.75.321	833.75.325	833.75.329	833.75.333	833.75.547
		4000	2.5	165	66	833.75.322	833.75.326	833.75.330	833.75.334	833.75.548
		5000	2.5	175	70	833.75.323	833.75.327	833.75.331	833.75.335	833.75.549




> Surface mounted trim ring, Aluminum

Finish	Item No.
Chrome colored	833.72.809
Black	833.72.806
White	833.72.807
Bronze colored	833.72.808
Nickel colored	833.72.528



Recess mounting



Surface mounting

