





Profiles for recess mounting

Aluminum

Häfele Loox profile - for recess mounting



End cap



End cap

- > Material: Aluminum
- > Finish: Silver colored anodized
- > L x W: 2500 x 18 mm (98 7/16" x 11/16")
- > Height: 8.5 mm (5/16")
- > Supplied with: 1 profile, 1 diffuser

| Cover | Item No. |
|---------|------------|
| Milk | 833.72.864 |
| Frosted | 833.72.865 |



LED points are always visible when this profile is used



End cap with cable outlet for 833.72.864 and 833.72.865

- > Material/Finish: Plastic, silver colored
- > Supplied with: 2 pcs.

| Item No. |
|------------|
| 833.72.855 |



Switch for aluminum profiles 16 mm (5/8") see page 88.
Diffusers see page 40

- > Material: Aluminum
- > Finish: Silver colored anodized
- > L x W: 2500 x 18 mm (98 7/16" x 11/16")
- > Height: 13 mm (1/2")
- > Supplied with: 1 profile, 1 diffuser

| Cover | Item No. |
|---------|------------|
| Milk | 833.72.866 |
| Frosted | 833.72.867 |



End cap with cable outlet for 833.72.866 and 833.72.867

- > Material/Finish: Plastic, silver colored
- > Supplied with: 2 pcs.

| Item No. |
|------------|
| 833.72.854 |



Switches for aluminum profiles 16 mm (5/8") see page 88.
Diffusers see page 40

LED 3028

FLEXIBLE STRIP LIGHT, TWO ROWS

0° 100%

24 V SYSTEM

IP20

- > Dimmable
- > Can be shortened every 25 mm (1")
- > Installation only with aluminum profile
- > All aluminum profiles are suitable except 833.72.860, 833.72.863, 833.72.864, 833.72.865, 833.74.809 and 833.74.835
- > Max. strip light length per lead: 3.8 m (12' 5 5/8")
- > Max. watt per lead: 72 W



- > Driver see page 92
- > Aluminum profiles see pages 108 - 112

| 2700 K | 3000 K | 4000 K | 5000 K | 120° |
|---------|---------|---------|---------|--------------------|
| 4180 lx | 4307 lx | 4436 lx | 4533 lx | 250 (9 13/16") |
| 1045 lx | 1077 lx | 1109 lx | 1133 lx | 500 (19 11/16") |
| 464 lx | 478 lx | 493 lx | 503 lx | 750 (29 1/2") |
| 261 lx | 269 lx | 277 lx | 283 lx | 1000 (39 3/8") |

Note

The chart values apply to a strip light length of 0.5 m (19 11/16").



| Item No. | 833.77.220 | 833.77.221 | 833.77.222 | 833.77.223 |
|-----------------------------|--|-------------------|-------------------|-------------------|
| SRP | \$300.00 | \$300.00 | \$300.00 | \$300.00 |
| Light Color (K) | 2700 (warm white) | 3000 (warm white) | 4000 (cool white) | 5000 (cool white) |
| L x W x H | 5000 x 12 x 1.3 mm (196 7/8" x 1/2" x 1/32") | | | |
| Wattage | 96 (19.2 per meter) [5.9 per foot] | | | |
| LEDs | 1200 (240 per meter) (72 per foot) | | | |
| Lumen | 7700 | 8090 | 8110 | 8140 |
| Lumen per watt | 80 | 84 | 84 | 84 |
| CRI | 82 | | | |
| Energy Efficiency class | A+ | | | |
| Weighted energy consumption | 21.12 | | | |
| Material/Finish | Plastic, white | | | |
| Supplied with | 2 m (78 3/4") lead | | | |

Note Loox Lights and Drivers are "Suitable for use within Closet Storage Spaces"

ALUMINUM PROFILES

RECESS MOUNTED

Profiles for recess mounting




| Item No. | 833.72.866 | 833.72.867 |
|-----------------|--|------------|
| SRP | \$56.00 | \$56.00 |
| Material/Finish | Aluminum, silver colored anodized | |
| Cover | milk | frosted |
| L x W x H | 2500 x 18.5 x 13 (98 3/8" x 3/4" x 1/2") | |
| Application | For recess mounting, 11.3 (7/16") deep | |



End cap with cable outlet
Plastic, silver colored anodized; 2 pcs.

> Item No. 833.72.854

SRP \$4.00



| Item No. | 833.72.864 | 833.72.865 |
|-----------------|--|------------|
| SRP | \$56.00 | \$56.00 |
| Material/Finish | Aluminum, silver colored anodized | |
| Cover | milk | frosted |
| L x W x H | 2500 x 18.5 x 8.5 (98 3/8" x 3/4" x 5/16") | |
| Application | For recess mounting, 6.8 (1/4") deep | |



Note

Shallow profiles are not suitable for operation with LED 3028.



End cap with cable outlet
Plastic, silver colored anodized; 2 pcs.

> Item No. 833.72.855

SRP \$4.00