

## LED strip lights


Monochrome, 8 mm (5/16"), 12 V



### Häfele Loox5 LED 2072/2062/2065/2068


Voltage V	Quantity LEDs/m	Color temperature K	Wattage W/m	Luminous flux lm/m	Luminous efficacy lm/W	Color rendering index CRI		Weighted energy consumpt. kWh/1000 h	Section length C	Length of contact surface P	Max. strip length (visual)	Available length		
						R <sub>a</sub>	R <sub>9</sub>					5 m (196 7/8")	50 m (1968 1/2")	
<b>5 12V</b>	<b>LED 2072</b>													
			*	*										
	120	2700	2.4	220	92	>90	>50	2.64	25 (1")	4 (3/16")	7 (275 19/32")	<b>833.74.400</b>	<b>833.74.404</b>	
		3000	2.4	230	96	>90	>50	2.64	25 (1")	4 (3/16")	7 (275 19/32")	<b>833.74.401</b>	<b>833.74.405</b>	
		4000	2.4	240	100	>90	>50	2.64	25 (1")	4 (3/16")	7 (275 19/32")	<b>833.74.402</b>	<b>833.74.406</b>	
		5000	2.4	240	100	>90	>50	2.64	25 (1")	4 (3/16")	7 (275 19/32")	<b>833.74.403</b>	<b>833.74.407</b>	
	<b>LED 2062</b>													
	60	2700	4.8	440	92	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	<b>833.74.336</b>	<b>833.74.340</b>	
		3000	4.8	465	97	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	<b>833.74.337</b>	<b>833.74.341</b>	
		4000	4.8	490	102	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	<b>833.74.338</b>	<b>833.74.342</b>	
		5000	4.8	495	103	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	<b>833.74.339</b>	<b>833.74.343</b>	
	<b>LED 2065</b>													
	120	2700	4.8	440	92	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	<b>833.74.354</b>	<b>833.74.358</b>	
		3000	4.8	465	97	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	<b>833.74.355</b>	<b>833.74.359</b>	
		4000	4.8	490	102	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	<b>833.74.356</b>	<b>833.74.360</b>	
		5000	4.8	495	103	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	<b>833.74.357</b>	<b>833.74.361</b>	
	<b>LED 2068</b>													
	120	2700	9.6	920	96	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	<b>833.74.362</b>	<b>833.74.366</b>	
		3000	9.6	970	101	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	<b>833.74.363</b>	<b>833.74.367</b>	
		4000	9.6	1000	104	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	<b>833.74.364</b>	<b>833.74.368</b>	
5000		9.6	1040	108	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	<b>833.74.365</b>	<b>833.74.369</b>		

\*See page 221 for conversion chart.




> 5 A/18 AWG lead for 8 mm (5/16") LED strip light

Voltage	Length	Item No.
<b>5 12V</b>	100 (4")	<b>833.93.736</b>
	500 (19 11/16")	<b>833.95.701</b>
	2000 (78 3/4")	<b>833.95.700</b>



> 5 A/18 AWG interconnecting lead for 8 mm (5/16") LED strip light

Length	Item No.
50 (2")	<b>833.89.191</b>
500 (19 11/16")	<b>833.89.192</b>
2000 (78 3/4")	<b>833.89.193</b>



> 5 A/18 AWG lead with female socket and clip for 8 mm (5/16") LED strip light

Voltage	Length	Item No.
<b>5 12V</b>	100 (4")	<b>833.93.746</b>



> 5 A Clip connector for 8 mm (5/16") LED strip light

> Supplied with: 10 pcs.

Item No.
<b>833.89.206</b>



> 5 A Corner connector, 90° rigid, left or right, for 8 mm (5/16") LED strip light

> Supplied with: 10 pcs.

Item No.
<b>833.89.187</b>



Luminous flux lm/m	Luminous efficacy lm/W	Section length mm	Color rendering index CRI		Available length			Max. strip length (visual) m	Max. strip length wattage- dependent m on the Loox5 driver			
			R <sub>a</sub>	R <sub>9</sub>	5 m (196 7/8")	15 m (590 9/16")	50 m (1968 1/2")		20 W	40 W	60 W	90W
440	92	50 (2")	>90	>50	<b>833.74.336</b>	-	<b>833.74.340</b>	6.0 (236 1/4")				
465	97	50 (2")	>90	>50	<b>833.74.337</b>	-	<b>833.74.341</b>	6.0 (236 1/4")	4.10	8.30	12.50	-
490	102	50 (2")	>90	>50	<b>833.74.338</b>	-	<b>833.74.342</b>	6.0 (236 1/4")				
495	103	50 (2")	>90	>50	<b>833.74.339</b>	-	<b>833.74.343</b>	6.0 (236 1/4")				
220	92	25 (1")	>90	>50	<b>833.74.400</b>	-	<b>833.74.404</b>	7.0 (275 9/16")				
230	96	25 (1")	>90	>50	<b>833.74.401</b>	-	<b>833.74.405</b>	7.0 (275 9/16")	8.30	16.80	-	25.00
240	100	25 (1")	>90	>50	<b>833.74.402</b>	-	<b>833.74.406</b>	7.0 (275 9/16")				
240	100	25 (1")	>90	>50	<b>833.74.403</b>	-	<b>833.74.407</b>	7.0 (275 9/16")				
440	92	25 (1")	>90	>50	<b>833.74.354</b>	-	<b>833.74.358</b>	6.0 (236 1/4")	4.10	8.30	12.50	-
465	97	25 (1")	>90	>50	<b>833.74.355</b>	-	<b>833.74.359</b>	6.0 (236 1/4")				
490	102	25 (1")	>90	>50	<b>833.74.356</b>	-	<b>833.74.360</b>	6.0 (236 1/4")				
495	103	25 (1")	>90	>50	<b>833.74.357</b>	-	<b>833.74.361</b>	6.0 (236 1/4")				
920	96	25 (1")	>90	>50	<b>833.74.362</b>	-	<b>833.74.366</b>	4.0 (154 1/2")	2.00	4.10	6.20	-
970	101	25 (1")	>90	>50	<b>833.74.363</b>	-	<b>833.74.367</b>	4.0 (154 1/2")				
1000	104	25 (1")	>90	>50	<b>833.74.364</b>	-	<b>833.74.368</b>	4.0 (154 1/2")				
1040	108	25 (1")	>90	>50	<b>833.74.365</b>	-	<b>833.74.369</b>	4.0 (154 1/2")				
210	88	50 (2")	>90	>50	<b>833.75.220</b>	-	<b>833.75.225</b>	15.5 (610 1/4")	8.30	16.80	-	25.00
230	96	50 (2")	>90	>50	<b>833.75.221</b>	-	<b>833.75.226</b>	15.5 (610 1/4")				
240	100	50 (2")	>90	>50	<b>833.75.222</b>	-	<b>833.75.227</b>	15.5 (610 1/4")				
240	100	50 (2")	>90	>50	<b>833.75.223</b>	-	<b>833.75.228</b>	15.5 (610 1/4")				
440	92	50 (2")	>90	>50	<b>833.76.316</b>	-	<b>833.76.320</b>	12.0 (472 7/16")	4.10	8.30	-	18.70
465	97	50 (2")	>90	>50	<b>833.76.317</b>	-	<b>833.76.321</b>	12.0 (472 7/16")				
490	102	50 (2")	>90	>50	<b>833.76.318</b>	-	<b>833.76.322</b>	12.0 (472 7/16")				
495	103	50 (2")	>90	>50	<b>833.76.319</b>	-	<b>833.76.323</b>	12.0 (472 7/16")				
920	96	50 (2")	>90	>50	<b>833.76.334</b>	-	<b>833.76.338</b>	8.0 (314 15/16")	2.00	4.10	-	9.30
970	101	50 (2")	>90	>50	<b>833.76.335</b>	-	<b>833.76.339</b>	8.0 (314 15/16")				
1000	104	50 (2")	>90	>50	<b>833.76.336</b>	-	<b>833.76.340</b>	8.0 (314 15/16")				
1040	108	50 (2")	>90	>50	<b>833.76.337</b>	-	<b>833.76.341</b>	8.0 (314 15/16")				
1270	88	50 (2")	>90	>50	<b>833.76.352</b>	-	<b>833.76.356</b>	6.2 (244 1/8")	1.30	2.70	-	6.20
1305	91	50 (2")	>90	>50	<b>833.76.353</b>	-	<b>833.76.357</b>	6.2 (244 1/8")				
1340	93	50 (2")	>90	>50	<b>833.76.354</b>	-	<b>833.76.358</b>	6.2 (244 1/8")				
1430	99	50 (2")	>90	>50	<b>833.76.355</b>	-	<b>833.76.359</b>	6.2 (244 1/8")				



For quick selection of linear light, see page 22