

LOOX LED DRIVER

CONSTANT VOLTAGE 12 V

12 V SYSTEM

**THIN
PROFILE**


1 Item No. 833.74.960
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 20 \text{ W}$

2 Item No. 833.74.962
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 40 \text{ W}$

3 Item No. 833.74.913
 $\otimes_1 + \otimes_2 + \dots + \otimes_6 < 60 \text{ W}$

max. 42 W per light output

max. 30 W per light output for 833.74.913



Parallel connection



- > Suitable for all of the world's power systems
- > With an integrated port for a wide selection of switches
- > Max. 42 W per light output
- > Lead length from driver to switch: Max.: 6 m (236 1/4")
- > Drivers must be mounted in well ventilated area



- > Class 2
- > Efficiency Level VI
- > Degree of Protection: IP20
- > Loxx drivers cannot be controlled by a dimmer wall switch

Item No.	833.74.960 1	833.74.962 2	833.74.913 3
SRP	\$36.00	\$60.00	\$72.00
L x W	140 x 50 x 16 (5 1/2" x 2" x 5/8")	190 x 60 x 16 (7 1/2" x 2 3/8" x 5/8")	208 x 56.5 x 30 (8 13/16" x 2 1/4" x 1 3/16")
Wattage	0 – 20	0 – 40	0 – 60
Standby Power Consumption Wattage	<0.1	<0.1	<0.2
Input voltage	100 – 240 V~; 50 – 60 Hz		
Output voltage	12 V DC		
Output current	1.67 A	3.33 A	5.0 A
Number of slots	6 for lights, 1 for switch, 1 for power cord		
Material/Finish	Plastic, black		
Supplied with	Mounting accessories, US power cord		

Note

Loxx Lights and Drivers are "Suitable for use within Closet Storage Spaces"



- > Switches see pages 113 - 116
- > Extension leads see page 127



- Power cord with 90° plug
2 m (78 3/4")
- > Item No. 833.89.017 **SRP \$5.00**



- 90° Plug adapter
- > Item No. 833.89.018 **SRP \$7.00**

Country-specific 2 m (78 3/4") primary leads

3 m (118")

Item No.	833.89.000	833.89.001	833.89.002	833.89.003	833.89.016	833.89.005	833.89.050	833.89.008
SRP	\$10.00	\$4.00	\$4.00	\$4.00	\$4.00	\$4.00	\$4.00	\$6.00
Plug design								
Designation	UK	AU	EU	US	JP	CN	US	US
Voltage (V)	250	250	250	120	100	250	120	120

Drivers

12 V

Häfele Loox wall plug driver 12 V




Driver 15 W US
833.74.936


- > Material/Color: Plastic, black
- > Degree of protection: IP20
- > Input voltage: 100–240 V~; 50–60 Hz
- > Output voltage: DC 12 V
- > Standby power consumption: 0.1 W
- > Supplied with: 1 wall plug driver

Plug design/ designation	Output power W	L x W x H	Item No.
US	6	61 x 37 x 43 (2 3/8" x 1 1/2" x 1 11/16")	833.74.934
	15	78 x 46 x 54 (3 1/16" x 1 13/16" x 2 1/8")	833.74.936
	27	84 x 50 x 72 (3 5/16" x 2" x 2 7/8")	833.74.938


Häfele Loox leads 12 V




833.74.749



833.74.748



833.74.709



833.74.746

- > Length: 4000 mm (157 1/2")

12 V	Plug design/ designation	Item No.
	2.5 A/22 AWG with 2 slots	833.74.749
	2.5 A/22 AWG with 6-way distributor	833.74.748
	2.5 A/22 AWG with dimmer and 6-way distributor	833.74.709
	2.5 A/22 AWG with rocker switch and 6-way distributor	833.74.746

- > Length: 2000 mm (78 3/4")

12 V	Plug design/ designation	Item No.
	2.5 A/22 AWG with 1 slot	833.74.791



12 V 5 12 V

All sockets for 12 V Loox. Please order 6-piece adapter set 833.95.752 for Loox5 devices separately, see page 117.



Note

Loox lights and drivers are "Suitable for use within closet storage spaces"