

Recess/surface mounted lights


Modular multi-white, drill hole Ø: 58 mm (2 5/16")

Häfele Loox5 LED 2091 / 3091


Voltage V	Quantity LEDs	Color temperature K	Wattage W	Luminous flux lm	Luminous efficacy lm/W	Color rendering index CRI	R _a	Weighted energy consumpt. kWh/1000 h	Item No.
LED 2091									
5 12 V	12	2700 5000	3.4	240 270	72 80	>90	>55	3.74	833.72.478
LED 3091									
5 24 V	12	2700 5000	3.4	240 270	72 80	>90	>55	3.74	833.75.178




Recess mount housing




Square




Round




Surface mount housing



Square



Round



- > Lead, 1.5 A/24 AWG, with snap-in connector for multi-white lights
- > Length: 2000 mm (78 3/4")

Voltage	Item No.
5 12 V	833.95.787
5 24 V	833.95.790



- > Housing, recess mounted, Plastic

Color	Round	Square
Black	833.72.168	833.72.172
Anthracite	833.72.380	833.72.383
Brown	833.72.381	833.72.384
Matt nickel-plated	833.72.170	833.72.174
Stainless steel colored	833.72.382	833.72.385
Silver colored	833.72.126	833.72.127
White, RAL 9003	833.72.171	833.72.175



- > Housing, surface mounted, Plastic

Color	Round	Square
Black	833.72.160	833.72.164
Anthracite	833.72.193	833.72.195
Brown	833.72.192	833.72.196
Matt nickel-plated	833.72.162	833.72.166
Stainless steel colored	833.72.194	833.72.197
Silver colored	833.72.124	833.72.125
White, RAL 9003	833.72.163	833.72.167

Housings are suitable for monochrome and multi-white lights.

* valid for multi-white plugs.