


Surface mounted light bars

With linkable cable, 24 V

Profile 2191 with Loox LED 3045



- > CRI 90 light are Title 24 compliant and offer more vibrant, true color rendering than lower CRI products
- > Life time: 50,000 hours
- > Supplied ready to install
- > Optimal lengths for installing under your wall cabinets to brighten up your countertop workspace
- > Linkable to other light bars



Loox 24 V drivers see pages 176–177



Note

Designed for use within closet storage spaces.

Components

- > Profile: 2191 - see page 56.
- > LED strip: 3045 - see page 33.
- > Mounting brackets: see page 56.
- > Lead cable: 100 mm (4") male and female 833.89.291

Material: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	3000							
Item No.	833.88.850	833.88.851	833.88.852	833.88.853	833.88.854	833.88.855	833.88.856	833.88.857
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.88.858	833.88.859	833.88.860	833.88.861	833.88.862	833.88.863	—	—
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	—	—
Wattage	7.3	7.6	8.8	9.0	10.2	10.5	—	—
LEDs	84	93	102	111	120	129	—	—
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							

Material/Finish: Aluminum, silver; Lens: Plastic, opal

Light Color (K)	4000							
Item No.	833.88.864	833.88.865	833.88.866	833.88.867	833.88.868	833.88.869	833.88.870	833.88.871
Length	152 (6")	229 (9")	305 (12")	381 (15")	457 (18")	533 (21")	610 (24")	686 (27")
Wattage	1.0	1.7	2.9	3.2	3.9	4.6	5.8	6.1
LEDs	12	21	30	39	48	57	66	75
Item No.	833.88.872	833.88.873	833.88.874	833.88.875	833.88.876	833.88.877	—	—
Length	762 (30")	832 (33")	915 (36")	991 (39")	1067 (42")	1143 (45")	—	—
Wattage	7.3	7.6	8.8	9.0	10.2	10.5	—	—
LEDs	84	93	102	111	120	129	—	—
CRI	>90							
Supplied with	100 mm (4") male lead, 100 mm (4") female lead, mounting brackets							