

Drivers

24 V

Häfele Loox5 driver constant voltage 24 V



- > Version: With overload protection
- > Material/Color: Plastic, black
- > Degree of protection: IP20
- > Input voltage: 100–240 V~; 50–60 Hz
- > Output voltage: DC 24 V
- > Number of connections: 1x socket Loox5 24 V
- > Life time: >70,000 hours
- > Safety: Class 2
- > Supplied with: 1 driver with mounting accessories
1 US power cord

5 ^{24V}	Output power	Output current	Standby power consumpt.	L x W x H	Item No.
	W	A	W		
1	20	0.83	≤0.2 W	140 x 50 x 16 (5 1/2" x 2" x 5/8")	833.95.008
2	40	1.67	≤0.3 W	191 x 60 x 16 (7 1/2" x 2 3/8" x 5/8")	833.95.010
3	90	3.75	≤0.3 W	316 x 70 x 16 (12 7/16" x 2 3/4" x 5/8")	833.95.011

! Ambient temperature –25 °C to +45 °C
Ensure that there is a sufficient air supply and circulation at the mounting location.

! Maximum lead length from the Loox5 driver to the device is 10,000 mm (393 11/16"). Long cable lengths in combination with large loads (strip light lengths) can result in voltage losses in the cable. These lead to visible loss of brightness in the lights. The illuminance listed with the lights has been determined with the rated output voltage of the driver. (12 V or 24 V).

! **Note**
Loox lights and drivers are "Suitable for use within closet storage spaces"



Country-specific power cords - 2000 mm (78 3/4") lead length, socket at the cable: C7

									3000 mm (118")
Plug design									
Description	US	UK	AU	EU	JP	CN	KR	US	US
Supplied with	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.	1 pc.
Item No.	833.89.003	833.89.000	833.89.001	833.89.002	833.89.016	833.89.005	833.89.006	833.89.050	833.89.008

Power cord - with 90° plug



- > Length: 2000 mm (78 3/4")
- > Material/Color: Plastic, black
- > Supplied with: 1 pc.

Item No.
833.89.017



90° plug adapter

- > Material/Color: Plastic, black
- > Supplied with: 1 pc.

Item No.
833.89.018