

LED strip lights

Monochrome, 8 mm (5/16")

HÄFELE

ILLUMINATING



EXTENDING



SWITCHING



NETWORKING



DISTRIBUTING




SUPPLYING



Häfele Loox5 LED 2062/2065/2068/3042/3045/3048

Voltage	Quantity	Color temperature	Wattage	Luminous flux	Luminous efficacy	Color rendering index CRI		Weighted energy consumpt.	Section length C	Length of contact surface P	Max. strip length (visual)	Available length	
						R _a	R ₉					5 m (196 7/8")	50 m (1968 1/2")
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉	kWh/ 1000 h					
5 12V	LED 2062		*	*									
	60	2700	4.8	440	92	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	833.74.336	833.74.340
		3000	4.8	465	97	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	833.74.337	833.74.341
		4000	4.8	490	102	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	833.74.338	833.74.342
		5000	4.8	495	103	>90	>50	5.28	50 (2")	4 (3/16")	6.0 (236 1/4")	833.74.339	833.74.343
	LED 2065												
	120	2700	4.8	440	92	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	833.74.354	833.74.358
		3000	4.8	465	97	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	833.74.355	833.74.359
		4000	4.8	490	102	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	833.74.356	833.74.360
		5000	4.8	495	103	>90	>50	5.28	25 (1")	4 (3/16")	6.0 (236 1/4")	833.74.357	833.74.361
	LED 2068												
	120	2700	9.6	920	96	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	833.74.362	833.74.366
		3000	9.6	970	101	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	833.74.363	833.74.367
		4000	9.6	1000	104	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	833.74.364	833.74.368
		5000	9.6	1040	108	>90	>50	10.56	25 (1")	4 (3/16")	4.0 (157 1/2")	833.74.365	833.74.369
5 24V	LED 3042												
	120	2700	4.8	440	92	>90	>50	5.28	50 (2")	4 (3/16")	12.0 (472 7/16")	833.76.316	833.76.320
		3000	4.8	465	97	>90	>50	5.28	50 (2")	4 (3/16")	12.0 (472 7/16")	833.76.317	833.76.321
		4000	4.8	490	102	>90	>50	5.28	50 (2")	4 (3/16")	12.0 (472 7/16")	833.76.318	833.76.322
		5000	4.8	495	103	>90	>50	5.28	50 (2")	4 (3/16")	12.0 (472 7/16")	833.76.319	833.76.323
	LED 3045												
	120	2700	9.6	920	96	>90	>50	10.56	50 (2")	4 (3/16")	8.0 (314 15/16")	833.76.334	833.76.338
		3000	9.6	970	101	>90	>50	10.56	50 (2")	4 (3/16")	8.0 (314 15/16")	833.76.335	833.76.339
		4000	9.6	1000	104	>90	>50	10.56	50 (2")	4 (3/16")	8.0 (314 15/16")	833.76.336	833.76.340
		5000	9.6	1040	108	>90	>50	10.56	50 (2")	4 (3/16")	8.0 (314 15/16")	833.76.337	833.76.341
	LED 3048												
	120	2700	14.4	1270	88	>90	>50	15.84	50 (2")	4 (3/16")	6.2 (244 1/8")	833.76.352	833.76.356
		3000	14.4	1305	91	>90	>50	15.84	50 (2")	4 (3/16")	6.2 (244 1/8")	833.76.353	833.76.357
		4000	14.4	1340	93	>90	>50	15.84	50 (2")	4 (3/16")	6.2 (244 1/8")	833.76.354	833.76.358
		5000	14.4	1430	99	>90	>50	15.84	50 (2")	4 (3/16")	6.2 (244 1/8")	833.76.355	833.76.359



> 5 A/18 AWG lead
for 8 mm (5/16") LED strip light


Voltage	Length	Item No.
5 12 V	100 (4")	833.93.736
	500 (19 11/16")	833.95.701
	2000 (78 3/4")	833.95.700
5 24 V	100 (4")	833.75.743
	500 (19 11/16")	833.95.707
	2000 (78 3/4")	833.95.706



> 5 A Clip connector
for 8 mm (5/16") LED strip light

> Supplied with: 10 pcs.

Item No.
833.89.206



> 5 A/18 AWG interconnecting lead
for 8 mm (5/16") LED strip light

Length	Item No.
50 (2")	833.89.191
500 (19 11/16")	833.89.192
2000 (78 3/4")	833.89.193



> 5 A Corner connector, 90° rigid,
left or right, for 8 mm (5/16") LED strip light

> Supplied with: 10 pcs.

Item No.
833.89.187

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

*See page 158 for conversion chart.

Illuminating / 11