

HAWA Junior 40/GP

Set



- For 1 sliding door without upper track and lower guide channel

Item No.
940.41.008

Supplied With

Mounting instructions


Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	940.41.100
	Suspension bolt, M8, including mounting screws	–	–	2 pcs.	940.41.022
	Patch suspension	–	–	2 pcs.	940.40.038
	Track stopper with adjustable retention spring	–	–	2 pcs.	940.40.041
	One-way drilling jig	–	–	1 pc.	940.40.089
	Wall buffer	Rubber	black	1 pc.	940.40.051
	Height adjusting pin	–	–	1 pc.	940.40.090

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.

Individual Components



	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	1.4 m (4' 7 1/8")	940.40.140
				1.6 m (5' 3")	940.40.160
				1.8 m (5' 10 7/8")	940.40.180
				2 m (6' 6 3/4")	940.40.200
				3 m (9' 10 1/8")	940.40.300
				4 m (13' 1 1/2")	940.40.400
				6 m (19' 8 1/4")	940.40.600

Angle profile	page 1.288
Toplock	pages 1.352-1.356
Floor mounted door stop	page 1.290
Glass edge protection profiles	page 1.291
Junior/GP/Fixed glass	pages 1.272-1.273
Sliding door locks	pages 1.357, 1.364-1.367

Dimensions in mm
Inches are approximate

HAWA Junior 40/GP

Individual Components

	Description	Material	Finish	Length	Item No.
Installation option 1					
	Patch suspension	–	–	–	940.40.038
	Lower guide, spring loaded, for single guide track	–	–	–	940.40.039
	Single lower guide track for clip or glue mounting	Aluminum	anodized	2.5 m (8' 2 7/16")	940.41.725
				3.5 m (11' 5 13/16")	940.41.735
	Fixing set, for single lower guide track. 5 pcs. each, 2 pcs. per meter required	Plastic	black	–	404.97.990
Installation option 2					
	Patch suspension	–	–	–	940.40.038
	Lower guide with mounting screws, suitable for patch suspension unit	–	–	–	940.40.035
	Lower guide channel, 24 x 24 mm (15/16" x 15/16"), not drilled	Aluminum	anodized	6 m (19' 8 1/4")	940.81.600
	End stop for lower guide channel 24 x 24 mm (15/16" x 15/16")	Aluminum	anodized	–	940.80.051
Installation option 3					
	Lower guide, rattle-free for glass thickness 8, 10 and 12.7 mm (3/16", 13/32", 1/2")	Steel	chrome-plated matt	–	940.40.032
Installation option 4					
	Lower guide channel, 20 x 20 mm (25/32" x 25/32")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.925
	Lower guide channel, 20 x 20 mm (25/32" x 25/32")			6 m (19' 8 1/4")	941.00.960
	Gliders, self adhesive, for 8 mm (5/16") thick glass	Plastic	–	–	940.40.033
	Gliders, self adhesive, for 10 mm (13/32") thick glass	Plastic	–	–	940.40.034

Flush pulls	pages 1.363, 1.371-1.373
Pull handles	pages 2.10-2.32
Sliding door locks	pages 1.357, 1.364-1.367

HAWA Junior 80/GP

Set




- For 1 sliding door without upper track and lower guide channel

	Item No.
	940.81.006

Supplied With

Mounting instructions


Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	940.80.012
	Suspension bolt, M10 including mounting screws	–	–	2 pcs.	940.81.023
	Patch suspension	–	–	2 pcs.	940.40.038
	Track stopper with adjustable retention spring	–	–	1 pc.	940.80.040
	One-way drilling jig	–	–	1 pc.	940.40.089
	Wall buffer	Rubber	black	1 pc.	940.40.051
	Height adjusting pin	–	–	1 pc.	940.40.090

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.

Individual Components



	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	1.4 m (4' 7 1/8")	940.80.140
				1.6 m (5' 3")	940.80.160
				1.8 m (5' 10 7/8")	940.80.180
				2 m (6' 6 3/4")	940.80.200
				2.2 m (7' 2 5/8")	940.80.220
				2.5 m (8' 2 7/16")	940.80.250
				3 m (9' 10 1/8")	940.80.300
				4 m (13' 1 1/2")	940.80.400
				6 m (19' 8 1/4")	940.80.600

Angle profile	page 1.288
Toplock	pages 1.352-1.356
Floor mounted door stop	page 1.290
Glass edge protection profiles	page 1.291
Soft close	page 1.287
Fixed glass panel for 80/GP	pages 1.260-1.261

Dimensions in mm
Inches are approximate

HAWA Junior 80/GP

Individual Components

	Description	Material	Finish	Length	Item No.
Installation option 1					
	Patch suspension	–	–	–	940.40.038
	Lower guide, spring loaded, for single guide track	–	–	–	940.40.039
	Single lower guide track for clip fixing or glue fixing	Aluminum	anodized	2.5 m (8' 2 7/16")	940.41.725
				3.5 m (11' 5 13/16")	940.41.735
	Fixing set, for single lower guide track. 5 pcs each, 2 pcs. per meter required	Plastic	black	–	404.97.990
Installation option 2					
	Patch suspension	–	–	–	940.40.038
	Lower guide with mouting screws, suitable for patch suspension unit	–	–	–	940.40.035
	Lower guide channel, 24 x 24 mm (15/16" x 15/16"), not drilled	Aluminum	anodized	6 m (19' 8 1/4")	940.81.600
	End stop for guide channel 24 x 24 mm (15/16" x 15/16")	Aluminum	anodized	–	940.80.051
Installation option 3					
	Lower guide, rattle-free for glass thickness 8, 10 and 12.7 mm (3/16", 13/32", 1/2")	Steel	chrome plated matt	–	940.40.032
Installation option 4					
	Lower guide channel, 20 x 20 mm (25/32" x 25/32")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.925
	Lower guide channel, 20 x 20 mm (25/32" x 25/32")			6 m (19' 8 1/4")	941.00.960
	Gliders, self adhesive, for 8 mm (5/16") thick glass	Plastic	–	–	940.40.033
	Gliders, self adhesive, for 10 mm (13/32") thick glass	Plastic	–	–	940.40.034

Fixed glass panel for 80/GP	pages 1.260-1.261
Flush pulls	pages 1.363, 1.371-1.373
Pull handles	pages 2.10-2.32
Sliding door locks	pages 1.357, 1.364-1.367

HAWA Junior 120/GP

Set




- For 1 sliding door without upper track

Item No.
941.20.010

Supplied With

Mounting instructions


Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	941.20.100
	Suspension bolt, M12, including mounting screws	–	–	2 pcs.	941.20.023
	Patch suspension	–	–	2 pcs.	940.40.038
	Track stopper with adjustable retention spring	–	–	2 pcs.	941.20.041
	One-way drilling jig	–	–	1 pc.	940.40.089
	Wall buffer	Rubber	black	1 pc.	940.40.051
	Height adjusting pin	–	–	1 pc.	940.40.090

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.

Individual Components



	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	3 m (9' 10 1/8")	941.20.300
				4 m (13' 1 1/2")	941.20.400
				6 m (19' 8 1/4")	941.20.600
	Cover cap to upper track	Zinc die-cast	chrome matt	–	941.20.029

Toplock	pages 1.352-1.356
Junior/GP/Fixed Glass	pages 1.272-1.273
Angle profile	page 1.288
Glass edge protection profiles	page 1.291
Floor mounted door stop	page 1.290

Dimensions in mm
Inches are approximate

HAWA Junior 120/GP

Individual Components

	Description	Material	Finish	Length	Item No.
Installation option 1					
	Patch suspension	–	–	–	940.40.038
	Lower guide, spring loaded, for single guide track	–	–	–	940.40.039
	Single lower guide track for clip fixing or glue fixing	Aluminum	anodized	2.5 m (8' 2 7/16")	940.41.725
				3.5 m (11' 5 13/16")	940.41.735
	Fixing set, for single lower guide track. 5 pcs., 2 pcs. per meter required	Plastic	black	–	404.97.990
Installation option 2					
	Patch suspension	–	–	–	940.40.038
	Lower guide with mounting screws, suitable for patch suspension unit	–	–	–	940.40.035
	Lower guide channel, 24 x 24 mm (15/16" x 15/16"), not drilled	Aluminum	anodized	6 m (19' 8 1/4")	940.81.600
	End stop for guide channel 24 x 24 mm (15/16" x 15/16")	Aluminum	anodized	–	940.80.051
Installation option 3					
	Lower guide, rattle-free for glass thickness 8, 10 and 12.7 mm (3/16", 13/32", 1/2")	Steel	chrome plated matt	–	940.40.032
Installation option 4					
	Guide channel, 20 x 20 x 3 mm (13/16" x 13/16" x 1/8"), pre-drilled	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.925
				6 m (19' 8 1/4")	941.00.960
	Self-adhesive sliders, for lower guide channel 20 x 20 x 3 mm (13/16" x 13/16" x 1/8"), for glass thickness 8 mm (5/16")	–	–	–	940.40.033
	Self-adhesive sliders, for lower guide channel 20 x 20 x 3 mm (13/16" x 13/16" x 1/8"), for glass thickness 10 mm (13/32")	–	–	–	940.40.034

Junior 40/GP/Fixed Glass	pages 1.272-1.273
Flush pulls	pages 1.363, 1.371-1.373
Pull handles	pages 2.10-2.32
Sliding door locks	pages 1.357, 1.364-1.367

HAWA Junior 160/GP

Set




- For 1 sliding door without upper track

Item No.
941.60.005

Supplied With

Mounting instructions

Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	–	–	2 pcs.	941.60.012
	Suspension bolt, M14, including mounting screws	–	–	2 pcs.	941.60.023
	Patch suspension	–	–	2 pcs.	940.40.038
	Track stopper with adjustable retention spring	–	–	2 pcs.	941.60.041
	One-way drilling jig	–	–	1 pc.	940.40.089
	Wall buffer	Rubber	black	1 pc.	940.40.051
	Height adjusting pin	–	–	1 pc.	940.40.090

Note

Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount. For 2 bi-parting sliding glass doors, please order 2 sets.



Individual Components

	Description	Material	Finish	Length	Item No.
	Upper track, pre-drilled	Aluminum	clear anodized	3 m (9' 10 1/8")	941.60.301
				4 m (13' 1 1/2")	941.60.401
				6 m (19' 8 1/4")	941.60.601

Dimensional data not binding. We reserve the right to alter specifications without notice.

HAWA Junior 160/GP

Individual Components

	Description	Material	Finish	Length	Item No.
Installation option 1					
	Patch suspension	–	–	–	940.40.038
	Lower guide, spring loaded, for single guide track	–	–	–	940.40.039
	Single lower guide track for clip fixing or glue fixing	Aluminum	anodized	2.5 m (8' 2 7/16")	940.41.725
				3.5 m (11' 5 13/16")	940.41.735
	Fixing set, for single lower guide track. 5 pcs., 2 pcs. per meter required	Plastic	black	–	404.97.990
Installation option 2					
	Patch suspension	–	–	–	940.40.038
	Lower guide with mounting screws, suitable for patch suspension unit	–	–	–	940.40.035
	Lower guide channel, 24 x 24 mm (15/16" x 15/16"), not drilled	Aluminum	anodized	6 m (19' 8 1/4")	940.81.600
	End stop for guide channel 24 x 24 mm (15/16" x 15/16")	Aluminum	anodized	–	940.80.051
Installation option 3					
	Lower guide, rattle-free for glass thickness 8, 10 and 12.7 mm (3/16", 13/32", 1/2")	Steel	chrome plated matt	–	940.40.032
Installation option 4					
	Guide channel, 20 x 20 x 3 mm (13/16", 13/16" x 1/8"), pre-drilled	Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.925
				6 m (19' 8 1/4")	941.00.960
	Self-adhesive sliders, for lower guide channel 20 x 20 x 3 mm (13/16" x 13/16" x 1/8"), for glass thickness 8 mm (5/16")	–	–	–	940.40.033
	Self-adhesive sliders, for lower guide channel 20 x 20 x 3 mm (13/16" x 13/16" x 1/8"), for glass thickness 10 mm (13/32")	–	–	–	940.40.034

Flush pulls	pages 1.363, 1.371-1.373
Pull handles	pages 2.10-2.32
Sliding door locks	pages 1.357, 1.364-1.367