

Hawa Junior 40 B Sets

Description	Model	Door weight	Supplied with	Item No.
For 1 sliding door without upper track	Junior 40 B with 1 track stopper	≤40 kg (88 lbs.)	2 running gears 2 carrier profiles with suspension plates incl. M8 bolts 2 end caps for carrier profile 1 track stopper with retaining spring 1 wall buffer 1 rattle-free floor guide 1 adjustment wrench for suspension assembly 1 hex key, 4mm	940.41.007
	Junior 40 B with 2 track stoppers	≤40 kg (88 lbs.)	2 running gears 2 carrier profiles with suspension plates incl. M8 bolts 2 end caps for carrier profile 2 track stoppers with retaining springs 1 wall buffer 1 rattle-free floor guide 1 adjustment wrench for suspension assembly 1 hex key, 4mm	940.41.017

Note

Order 2 sets for a bi-parting sliding door application.

→ Upper Tracks and Accessories

Description	Image	Material	Finish	Length	Item No.
Upper track, pre-drilled 47.5 x 31 mm (1 7/8" x 1 7/32")		Aluminum	clear anodized	1.4 m (4' 7 1/8")	940.40.140
				1.6 m (5' 3")	940.40.160
				1.8 m (5' 10 7/8")	940.40.180
				2.0 m (6' 6 3/4")	940.40.200
				2.5 m (8' 2 7/16")	940.80.633
				3.0 m (9' 10 1/8")	940.40.300
				4.0 m (13' 1 1/2")	940.40.400
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	940.41.130
End cap for upper track		Plastic	anthracite	—	940.40.066
Track stopper with adjustable retaining spring		—	—	—	940.40.041
SoftMove 40, soft close mechanism, maximum capacity 40 kg (88 lbs.)		—	—	—	940.80.330

Note

Each Hawa SoftMove 40 requires a track stopper. For applications that require a SoftMove in both directions either order the fitting set that includes two track stoppers or one additional track stopper. For additional information on SoftMove 40, see page **1.229**.

Hawa angle profile	page 1.230
Hawa SoundEx bracket	page 1.231
Hawa confort guides	page 1.232
Pull handles	pages 2.3–2.29
Flush pulls	pages 1.394–1.396
Sliding door locks	pages 1.389–1.394