



## HAWA Purolino-Plus 80

### Individual Components

Description	Material	Finish	Length	Item No.	
Wall mounting					
	Tracks and profiles:	anodized	2.5 m (8' 2 7/16)	940.83.325	
	Aluminum				
	Gap closing profile:	stainless steel		940.83.326	
	Rubber	colored			
Ceiling installation without fixed glass panel					
	Tracks and profiles:	anodized	2.5 m (8' 2 7/16)	940.83.425	
	Aluminum				
	Gap closing profile:	stainless steel		940.83.426	
	Rubber	colored			
Ceiling installation for fixed glass panel					
	Tracks and profiles:	anodized	2.5 m (8' 2 7/16)	940.83.525	
	Aluminum				
	Gap closing profile:	stainless steel		940.83.526	
	Rubber	colored			
Ceiling installation, integrated, for/without fixed glass panel					
	Tracks and profiles:	anodized	2.5 m (8' 2 7/16)	940.83.625	
	Aluminum				
	Gap closing profile:	stainless steel		940.83.626	
	Rubber	colored			
Profile set for fixed glass panel					
	Profile set for fixed glass panel, with cover profile and special countersunk screws 5.5 x 19 mm (7/32" x 3/4")	anodized	2.5 m (8' 2 7/16)	940.83.825	
		stainless steel		940.83.826	
		colored			
Individual profiles					
	Floor/wall profile, for fixed glass panel	anodized	4 m (13' 1 15/32")	940.41.540	
			6 m (19' 8 7/32")	940.41.560	
		stainless steel	4 m (13' 1 15/32")	940.41.541	
			6 m (19' 8 7/32")	940.41.561	
	Fixed glass gasket, 10 – 12.7 mm (13/32" – 1/2")	Rubber	black	10 m (32' 9 11/16")	940.41.063
	Bottom/wall glass retainer, pre-drilled, for fixed glass panel, 10 – 12 mm (13/32" – 15/32"), with rubber profile	anodized	50 mm (1 15/16")	940.41.054	
		stainless steel		940.41.055	
		colored			

#### Order reference

Individual upper tracks and profiles in other lengths also available on request.



Pull handles	pages 2.10-2.32
Door seals and accessories	page 1.290
Sliding door locks	pages 1.357, 1.364-1.367
Flush pulls	pages 1.363, 1.371-1.373

Dimensions in mm  
Inches are approximate



## HAWA Junior for Fixed Glass

### Individual Components



#### Junior 40 Upper Track with Pocket

Description	Material	Finish	Length	Item No.
 Upper track with pocket	Aluminum	clear anodized	2 m (6' 6 3/4")	940.40.206
			6 m (19' 8 1/4")	940.40.606
 Cover profile for upper track with pocket	Aluminum	clear anodized	1.25 m (4' 1 3/16")	940.40.132
			2 m (6' 6 3/4")	940.40.207
			3 m (9' 10 1/8")	940.40.307




#### Junior 80 Upper Track with Pocket

Description	Material	Finish	Length	Item No.
 Upper track with pocket	Aluminum	clear anodized	2.5 m (8' 2 7/16")	940.80.256
			4 m (13' 1 1/2")	940.80.406
			6 m (19' 8 1/4")	940.80.606
 Cover profile for upper track with pocket	Aluminum	clear anodized	1.25 m (4' 1 3/16")	940.40.132
			2 m (6' 6 3/4")	940.40.207
			3 m (9' 10 1/8")	940.40.307

#### Junior 120 Upper Track with Pocket


Description	Material	Finish	Length	Item No.
 Upper track with pocket	Aluminum	clear anodized	3 m (9' 10 1/8")	941.20.306
			4 m (13' 1 1/2")	941.20.406
			6 m (19' 8 1/4")	941.20.606
 Cover profile for upper track with pocket	Aluminum	clear anodized	2 m (6' 6 3/4")	940.40.207
			3 m (9' 10 1/8")	940.40.307

#### Bottom/Wall Profile and Rubber Gasket

Description	Material	Finish	Length	Item No.
 Bottom/wall profile, pre-drilled	Aluminum	clear anodized	4 m (13' 1 1/2")	940.41.540
			6 m (19' 8 1/4")	940.41.560
 Fixed glass gasket, for 10 – 12.7 mm (13/32" – 1/2") glass	Rubber	black	10 m (32' 9 11/16")	940.41.063
 Bottom/wall glass retainer piece, pre-drilled	Aluminum	clear anodized	50 mm (2")	940.41.054

#### Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.



Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm  
Inches are approximate