





Slido Classic 80-L to 120-L, upper tracks, mounting rails and fixed glass fixing profiles

	Description	For door weights	Material	Finish	Length	Item No.
1 	Single upper track, pre-drilled W x H: 31 x 33 mm (1 1/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	mill	2 m (6' 6 3/4")	940.43.921
					3 m (9' 10 1/8")	940.43.931
					6 m (19' 8 1/4")	940.43.961
				clear anodized	2 m (6' 6 3/4")	940.43.922
					3 m (9' 10 1/8")	940.43.932
					6 m (19' 8 1/4")	940.43.962
2 	Single upper track, pre-drilled W x H: 47.5 x 47 mm (1 7/8" x 1 27/32"), wall mounted	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	940.43.920
					3 m (9' 10 1/8")	940.43.930
					6 m (19' 8 1/4")	940.43.960
3 	Double upper track, pre-drilled W x H: 70 x 33 mm (2 3/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.02.920
					3 m (9' 10 1/8")	941.02.930
					6 m (19' 8 1/4")	941.02.960
5 	Single upper track, wall mounted	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.602
					3 m (9' 10 1/8")	941.25.603
					6 m (19' 8 1/4")	941.25.606
16 	Mounting rail, width 19 mm (3/4") for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.821
					3 m (9' 10 1/8")	941.25.831
					6 m (19' 8 1/4")	941.25.861
17 	Mounting rail, width 8 mm (5/16") for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.820
					3 m (9' 10 1/8")	941.25.830
					6 m (19' 8 1/4")	941.25.860
18 	Mounting rail, high, width 19 mm (3/4") for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.823
					3 m (9' 10 1/8")	941.25.833
19 	Mounting rail, high, width 8 mm (5/16") for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.822
					3 m (9' 10 1/8")	941.25.832
	Retaining bolts and retaining screws, for single upper track	For upper track 5 and mounting rail 16, 17, 18 or 19	Steel	zinc-plated	–	941.25.090
6 	Fixed glass fixing profile	For upper track 1, 2, 3 , for glass thickness 10 – 12.7 mm (3/8" – 1/2")	Aluminum	clear anodized	2 m (6' 6 3/4")	940.43.820
					3 m (9' 10 1/8")	940.43.830
					6 m (19' 8 1/4")	940.43.860
	Cover for unused aperture in fixed glass fixing profile	–	Rubber	gray	5 m (10' 4 7/8")	940.43.038
14 	Fixed glass fixing profile	For wall or floor, for glass thickness 10 – 12.7 mm (3/8" – 1/2"). Note Gasket available for glass thickness 10 mm (3/8"), wet glazing for glass thickness 12.7 mm (1/2").	Aluminum	clear anodized	2 m (6' 6 3/4")	940.43.822
					3 m (9' 10 1/8")	940.43.832
					6 m (19' 8 1/4")	940.43.862
15 	Gasket	For glass thickness 10 mm (3/8")	Rubber	transparent	10 m (32' 9 11/16")	940.43.035
	End cap for fixed glass fixing profile (1 pc.)	–	Plastic	silver colored	–	940.43.059

Note

Aluminum mill finish upper tracks cannot be used in combination with clip-on fascia.

Please order retaining bolts and screws for upper track **5** and mounting rails **16, 17, 18** and **19** separately. When using the retaining bolts these bolts have to be glued in place while the retaining screws have to be countersunk before they are screwed in. For wall to wall applications the upper track and the mounting rail have to be fixed in place with glue points. Either two retaining bolts or two retaining screws are needed to hold one upper track in place.