


## Slido Classic 40-I to 120-I Components

|                                                                                   | Description                                           | Material           | Finish     | For Version                        | Qty.   | Item No.   |
|-----------------------------------------------------------------------------------|-------------------------------------------------------|--------------------|------------|------------------------------------|--------|------------|
|  | Floor guide, rattle-free                              | Plastic            | black      | A, B, E                            | 1 pc.  | 940.42.030 |
|  | Track stopper with retaining spring and rubber bumper | Plastic/<br>Rubber | -          | A for 40 – 60 kg (88 - 132 lbs.)   | 2 pcs. | 940.42.040 |
|                                                                                   |                                                       |                    |            | B for 40 – 60 kg (88 - 132 lbs.)   | 1 pc.  |            |
|                                                                                   |                                                       |                    |            | A for 80 – 120 kg (176 - 264 lbs.) | 2 pcs. | 940.42.041 |
|                                                                                   |                                                       |                    |            | B for 80 – 120 kg (176 - 264 lbs.) | 1 pc.  |            |
|  | Release device with stopper                           | Steel              | galvanized | B for 40 and 80 kg (88 - 176 lbs.) | 1 pc.  | 940.42.042 |
|                                                                                   |                                                       |                    |            | E for 40 and 80 kg (88 - 176 lbs.) | 2 pcs. |            |
|                                                                                   |                                                       |                    |            | B for 120 kg (264 lbs.)            | 1 pc.  | 940.42.082 |
|                                                                                   |                                                       |                    |            | E for 120 kg (264 lbs.)            | 2 pcs. |            |

### Note

Item numbers are valid only for 1 piece, when ordering individual components, please state the desired amount.

## Upper Tracks

|                                                                                               | Description                                                              | For door weights               | Material | Finish            | Length           | Item No.   |
|-----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------------------|----------|-------------------|------------------|------------|
| <b>1</b>     | Single upper track, pre-drilled<br>W x H: 31 x 33 mm (1 1/4" x 1 5/16")  | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | mill              | 2 m (6' 6 3/4")  | 940.43.921 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 940.43.931 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 940.43.961 |
|                                                                                               |                                                                          |                                |          | clear<br>anodized | 2 m (6' 6 3/4")  | 940.43.922 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 940.43.932 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 940.43.962 |
| <b>3</b>    | Double upper track, pre-drilled<br>W x H: 70 x 33 mm (2 3/4" x 1 5/16")  | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")  | 941.02.920 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 941.02.930 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 941.02.960 |
| <b>4</b>   | Double upper track, pre-drilled<br>W x H: 81 x 33 mm (3 3/16" x 1 5/16") | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")  | 941.02.820 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 941.02.830 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 941.02.860 |
| <b>5</b>   | Single upper track, wall mounted                                         | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")  | 941.25.920 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 941.25.930 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 941.25.960 |
| <b>16</b>  | Mounting rail, width 19 mm (3/4"), for<br>track #5                       | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")  | 941.25.821 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 941.25.831 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 941.25.861 |
| <b>17</b>  | Mounting rail, width 8 mm (5/16"), for<br>track #5                       | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")  | 941.25.820 |
|                                                                                               |                                                                          |                                |          |                   | 3 m (9' 10 1/8") | 941.25.830 |
|                                                                                               |                                                                          |                                |          |                   | 6 m (19' 8 1/4") | 941.25.860 |

### Note

Aluminum mill finish upper track cannot be used in combination with a clip-on fascia. Please order threaded end insert for upper track and mounting rail separately, refer to page **1.9**.

### Installation Reference

Slide in threaded end insert at rail ends. When the running track and the mounting rail are installed between walls the threaded end inserts cannot be used; instead use glue points to fix the running track to the mounting rail.

## Slido Classic Upper Tracks

|                                                                                               | Description                                                                              | For door weights               | Material | Finish         | Length/Qty.      | Item No.   |
|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------|----------|----------------|------------------|------------|
| <b>1</b>     | Single upper track, pre-drilled<br>W x H: 31 x 33 mm (1 1/4" x 1 5/16")                  | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | mill           | 2 m (6' 6 3/4")  | 940.43.921 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 940.43.931 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 940.43.961 |
|                                                                                               |                                                                                          |                                |          | clear anodized | 2 m (6' 6 3/4")  | 940.43.922 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 940.43.932 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 940.43.962 |
| <b>2</b>     | Single upper track, pre-drilled<br>W x H: 47.5 x 47 mm (1 7/8" x 1 27/32"), wall mounted | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 940.43.920 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 940.43.930 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 940.43.960 |
| <b>3</b>     | Double upper track, pre-drilled<br>W x H: 70 x 33 mm (2 3/4" x 1 5/16")                  | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 941.02.920 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 941.02.930 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 941.02.960 |
| <b>4</b>     | Double upper track, pre-drilled<br>W x H: 81 x 33 mm (3 3/16" x 1 5/16")                 | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 941.02.820 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 941.02.830 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 941.02.860 |
| <b>5</b>     | Single upper track, wall mounted                                                         | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 941.25.602 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 941.25.603 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 941.25.606 |
| <b>16</b>   | Mounting rail, width 19 mm (3/4"), for track #5                                          | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 941.25.821 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 941.25.831 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 941.25.861 |
| <b>17</b>  | Mounting rail, width 8 mm (5/16"), for track #5                                          | 40 – 120 kg<br>(88 – 264 lbs.) | Aluminum | clear anodized | 2 m (6' 6 3/4")  | 941.25.820 |
|                                                                                               |                                                                                          |                                |          |                | 3 m (9' 10 1/8") | 941.25.830 |
|                                                                                               |                                                                                          |                                |          |                | 6 m (19' 8 1/4") | 941.25.860 |




### Note

Aluminum mill finish upper track cannot be used in combination with clip fascia. Please order threaded end insert for upper track **5** and mounting rails **16** and **17** separately, below.

### Installation Reference

Slide in threaded end insert at rail ends. When the running track and the mounting rail are installed between walls the threaded end inserts cannot be used; instead use glue points to fix the running track to the mounting rail.





### Mounting Brackets and Accessories

|                                                                                               | Description                                                                                                      | Area of application                                                 | Material | Finish     | Length          | Item No.   |
|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|----------|------------|-----------------|------------|
| <b>10</b>  | Mounting bracket, with screw and nut                                                                             | For upper track <b>1</b>                                            | Steel    | galvanized | 36 mm (1 7/16") | 940.42.061 |
|                                                                                               |                                                                                                                  |                                                                     |          |            | 44 mm (1 3/4")  | 940.62.061 |
|                                                                                               |                                                                                                                  |                                                                     |          |            | 64 mm (2 1/2")  | 940.42.063 |
| –                                                                                             |  Wrench for height adjustment | –                                                                   | Steel    | galvanized | –               | 940.43.032 |
| –                                                                                             |  Threaded end insert          | For upper track <b>5</b> and mounting rails <b>16</b> and <b>17</b> | Steel    | galvanized | 1 set           | 941.25.090 |

### Note

Install wall mounting bracket **10** every 400 mm (15 3/4")

**Slido Classic 80-L to 120-L, upper tracks, mounting rails and fixed glass fixing profiles**

|                                                                                               | Description                                                                                 | For door weights                                                                                                                                                                                          | Material | Finish            | Length              | Item No.   |
|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------------|---------------------|------------|
| <b>1</b>     | Single upper track, pre-drilled<br>W x H: 31 x 33 mm<br>(1 1/4" x 1 5/16")                  | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | mill              | 2 m (6' 6 3/4")     | 940.43.921 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 940.43.931 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 940.43.961 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          | clear<br>anodized | 2 m (6' 6 3/4")     | 940.43.922 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 940.43.932 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 940.43.962 |
| <b>2</b>     | Single upper track, pre-drilled<br>W x H: 47.5 x 47 mm<br>(1 7/8" x 1 27/32"), wall mounted | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 940.43.920 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 940.43.930 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 940.43.960 |
| <b>3</b>     | Double upper track, pre-drilled<br>W x H: 70 x 33 mm<br>(2 3/4" x 1 5/16")                  | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.02.920 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.02.930 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 941.02.960 |
| <b>5</b>     | Single upper track, wall mounted                                                            | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.25.602 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.25.603 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 941.25.606 |
| <b>16</b>    | Mounting rail, width 19 mm<br>(3/4") for track #5                                           | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.25.821 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.25.831 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 941.25.861 |
| <b>17</b>    | Mounting rail, width 8 mm<br>(5/16") for track #5                                           | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.25.820 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.25.830 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 941.25.860 |
| <b>18</b>    | Mounting rail, high, width 19 mm<br>(3/4") for track #5                                     | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.25.823 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.25.833 |
| <b>19</b>   | Mounting rail, high, width 8 mm<br>(5/16") for track #5                                     | 40 – 120 kg<br>(88 – 264 lbs.)                                                                                                                                                                            | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 941.25.822 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 941.25.832 |
|            | Retaining bolts and retaining<br>screws, for single upper track                             | For upper track <b>5</b> and<br>mounting rail <b>16, 17, 18</b><br>or <b>19</b>                                                                                                                           | Steel    | zinc-plated       | –                   | 941.25.090 |
| <b>6</b>   | Fixed glass fixing profile                                                                  | For upper track <b>1, 2, 3</b> ,<br>for glass thickness<br>10 – 12.7 mm<br>(3/8" – 1/2")                                                                                                                  | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 940.43.820 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 940.43.830 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 940.43.860 |
|            | Cover for unused aperture<br>in fixed glass fixing profile                                  | –                                                                                                                                                                                                         | Rubber   | gray              | 5 m (10' 4 7/8")    | 940.43.038 |
| <b>14</b>  | Fixed glass fixing profile                                                                  | For wall or floor, for<br>glass thickness 10 –<br>12.7 mm (3/8" – 1/2").<br><b>Note</b><br>Gasket available for<br>glass thickness 10 mm<br>(3/8"), wet glazing for<br>glass thickness<br>12.7 mm (1/2"). | Aluminum | clear<br>anodized | 2 m (6' 6 3/4")     | 940.43.822 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 3 m (9' 10 1/8")    | 940.43.832 |
|                                                                                               |                                                                                             |                                                                                                                                                                                                           |          |                   | 6 m (19' 8 1/4")    | 940.43.862 |
| <b>15</b>  | Gasket                                                                                      | For glass thickness<br>10 mm (3/8")                                                                                                                                                                       | Rubber   | transparent       | 10 m (32' 9 11/16") | 940.43.035 |
|                                                                                               | End cap for fixed glass fixing<br>profile (1 pc.)                                           | –                                                                                                                                                                                                         | Plastic  | silver colored    | –                   | 940.43.059 |

**Note**

Aluminum mill finish upper tracks cannot be used in combination with clip-on fascia.

Please order retaining bolts and screws for upper track **5** and mounting rails **16, 17, 18** and **19** separately. When using the retaining bolts these bolts have to be glued in place while the retaining screws have to be countersunk before they are screwed in. For wall to wall applications the upper track and the mounting rail have to be fixed in place with glue points. Either two retaining bolts or two retaining screws are needed to hold one upper track in place.