

## EKU Porta 60/100 HMT Set


- For 1 sliding door without upper track

| Door Weight        | Item No.   |
|--------------------|------------|
| ≤60 kg (132 lbs.)  | 940.60.117 |
| ≤100 kg (220 lbs.) | 941.00.117 |

## Set Components

|                                                                                   | Description                                                          | Material | Finish     | Qty.   |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------|----------|------------|--------|
|  | Running gear, with four wheels, with hexagon bolt M8 x 36 mm (1 pc.) | –        | –          | 2 pcs. |
|  | Support profile                                                      | Steel    | galvanized | 2 pcs. |
|  | Support profile with cover cap and engaging pin                      | Plastic  | anthracite | 1 pc.  |
|  | Support profile with cover cap and spring                            | Plastic  | anthracite | 1 pc.  |
|  | Track stopper, with retaining spring                                 | –        | –          | 2 pcs. |
|  | Floor guide, adjustable                                              | Plastic  | anthracite | 1 pc.  |
|  | Fixing screws                                                        | –        | –          | 1 set  |
|  | Cylinder screw, M8 x 35 mm                                           | –        | –          | 1 pc.  |

## Individual Components

|                                                                                     | Description                                              | Material | Finish     | Length             | Item No.   |
|-------------------------------------------------------------------------------------|----------------------------------------------------------|----------|------------|--------------------|------------|
|  | Upper track, pre-drilled, 30 x 31 mm (1 3/16" x 1 7/32") | Aluminum | mill       | 2 m (6' 6 3/4")    | 941.00.200 |
|                                                                                     |                                                          |          |            | 2.5 m (8' 2 7/16") | 941.00.250 |
|                                                                                     |                                                          |          |            | 6 m (19' 8 1/4")   | 941.00.600 |
|                                                                                     |                                                          |          | anodized   | 2 m (6' 6 3/4")    | 941.00.205 |
|                                                                                     |                                                          |          |            | 2.5 m (8' 2 7/16") | 941.00.255 |
|                                                                                     |                                                          |          |            | 6 m (19' 8 1/4")   | 941.00.605 |
|  | Disassembly key                                          | –        | –          | –                  | 940.60.097 |
|  | Floor guide, adjustable                                  | Plastic  | anthracite | 65 mm (2 9/16")    | 941.00.037 |