


Hawa Porta 60/100 HMD Acoustics

→ For 1 Sliding Door Without Upper Track

Model	Supplied with	Door weight	Item No.
Porta 60/100HMD/HMT Pocket Acoustics with SoftStop and track stopper, without soft close	2 running gears 2 carrier profiles with suspension plate and M8 suspension bolts 1 SoftStop Porta 100 Acoustics 1 track stopper with retaining spring 1 cover cap set, plastic, anthracite Accessories	≤ 60kg (132 lbs.)	940.60.076
		≤ 100 kg (220 lbs.)	940.60.077

→ Seal Set

Description		Supplied with	Handing	Size	Item No.
Horizontal seal set Hawa Acoustics		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460
				S	940.80.461
				M	940.80.462
				L	940.80.463
				XL	940.80.464
			Right	XS	940.80.465
				S	940.80.466
				M	940.80.467
				L	940.80.468
				XL	940.80.469

Seal selection for doors fully opened

Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–780 mm (29 1/2"–30 11/16")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	780–900 mm (30 11/16"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	900–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Seal selection for doors partially opened


Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–870 mm (29 1/2"–34 1/4")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	870–990 mm (34 1/4"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	990–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Hawa Porta 60/100 HMT Pocket Acoustics


→ For 1 Sliding Door Without Upper Track

Model	Supplied with	Door Weight	Item No.
Porta 60/100HMD/HMT Pocket Acoustics with SoftStop and track stopper, without soft close	2 running gears 2 carrier profiles with suspension plate and M8 suspension bolts 1 SoftStop Porta 100 Acoustics 1 track stopper with retaining spring 1 cover cap set, plastic, anthracite Accessories	≤ 60kg (132 lbs.)	940.60.076
		≤ 100 kg (220 lbs.)	940.60.077

→ Seal Set

Description		Supplied with	Handing	Size	Item No.	Seal selection for doors fully and partially opened	
Horizontal seal set Hawa Acoustics		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460	XS	750–850 mm (29 1/2"–33 7/16")
				S	940.80.461		
				M	940.80.462	S	850–970 mm (33 7/16"–38 3/16")
				L	940.80.463		
				XL	940.80.464		
			Right	XS	940.80.465	M	970–1100 mm (38 3/16"–43 5/16")
				S	940.80.466		
				M	940.80.467	L	1100–1220 mm (43 5/16"–48 1/16")
				L	940.80.468		
				XL	940.80.469	XL	1220–1250 mm (48 1/16"–49 3/16")

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	mill	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
			silver anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
Upper track assembly set, includes removable track, assembly blocks, and screws		Aluminum	silver anodized	2 m (6' 6 3/4")	941.00.622
				2.5 m (8' 2 7/16")	941.00.623
Dis-assembly key		Steel	zinc-plated	–	940.60.097
Vertical seal		Silicone	black	7.7 m (25' 3 1/8")	940.00.500
Spring-loaded track stopper		Steel	zinc-plated	–	941.00.404
Upper track cleaning tool		Plastic	gray	–	941.00.099
Push-to-open soft close mechanism 61–100 kg (134–220 lbs.)		–	–	–	941.00.403

Sliding door locks	pages 1.384–1.394
Door pulls	pages 2.3–2.29
Flush pulls	pages 1.395–1.396


Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Junior 100 B Acoustics Set

→ For 1 Sliding Door Without Upper Track

Model	Door Width	Supplied with	Item No.
Junior 100 B / B Pocket with SoftStop on both sides, without soft close	≥ 820 mm (32 5/16")	2 running gears 2 carrier profiles with suspension plate incl. M10 bolt 1 SoftStop, with retaining spring and ramp 1 SoftStop, with retaining spring 1 Cover cap set, plastic, aluminum finish 1 adjustment wrench	941.04.017

→ Seal Set

Description		Supplied with	Handing	Size	Item No.
Horizontal seal set Hawa Acoustics		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460
				S	940.80.461
				M	940.80.462
				L	940.80.463
				XL	940.80.464
			Right	XS	940.80.465
				S	940.80.466
				M	940.80.467
				L	940.80.468
				XL	940.80.469

Seal selection for doors fully opened

Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–780 mm (29 1/2"–30 11/16")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	780–900 mm (30 11/16"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	900–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Seal selection for doors partially opened


Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–870 mm (29 1/2"–34 1/4")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	870–990 mm (34 1/4"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	990–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Hawa Junior 100 B Pocket Acoustics







→ For 1 Sliding Door Without Upper Track

Model	Door width	Supplied with	Item No.
Junior 100 B / B Pocket with SoftStop on both sides, without soft close	≥ 800 mm (31 1/2")	2 running gears 2 carrier profiles with suspension plate incl. M10 bolt 1 SoftStop, with retaining spring and ramp 1 SoftStop, with retaining spring 1 Cover cap set, plastic, aluminum finish 1 adjustment wrench	941.04.017

→ Seal Set

Description		Supplied with	Handing	Size	Item No.	Seal selection for doors fully and partially opened	
Horizontal seal set		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460	XS	750–850 mm (29 1/2"–33 7/16")
				S	940.80.461		
				M	940.80.462	S	850–970 mm (33 7/16"–38 3/16")
				L	940.80.463		
				XL	940.80.464		
			Right	XS	940.80.465	M	970–1100 mm (38 3/16"–43 5/16")
				S	940.80.466		
				M	940.80.467	L	1100–1220 mm (43 5/16"–48 1/16")
				L	940.80.468		
				XL	940.80.469		
						XL	1220–1250 mm (48 1/16"–49 3/16")

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 34 x 40 mm (1 11/32" x 1 9/16")		Aluminum	clear anodized	1.6 m (5' 3")	940.80.160
				1.8 m (5' 10 7/8")	940.80.180
				2 m (6' 6 3/4")	940.80.200
				2.2 m (7' 2 5/8")	940.80.220
				2.5 m (8' 2 7/16")	940.80.250
				3 m (9' 10 1/8")	940.80.300
Fixing profile for upper track with bayonet lock, with mounting set (can be shortened to respective track length)		Aluminum	clear anodized	2 m (6' 6 3/4")	940.80.420
				2.5 m (8' 2 7/16")	940.80.421
				3 m (9' 10 1/8")	940.80.422
SoftStop track stopper with adjustable retaining spring and ramp		–	–	–	941.04.304
SoftStop track stopper with adjustable retaining spring		–	–	–	941.04.301
Vertical seal		Silicone	–	7.7 m (25' 3 1/8")	940.00.500
Junior 80/100 spring buffer, cannot be used in combination with SoftMove		Zinc Alloy	–	–	940.80.320