

Häfele Slido D-Line11 50I–120I Sets

	Version	Supplied with	Door width	50I ≤50 kg (110 lbs.) per door	80I ≤80 kg (176 lbs.) per door	120I ≤120 kg (264 lbs.) per door	
Running gear with axle bearing							
	Without soft and self-closing mechanism	Track stopper with retaining spring	2 running gears with support flange 2 support profiles with cover cap 1 rattle-free floor guide 2 track stoppers with retaining spring	≥500 (19 11/16")	940.44.004	940.83.053	941.25.044
	With soft and self-closing mechanism on one side	Track stopper with retaining spring	2 running gears with support flange (1 with soft and self closing mechanism) 2 support profiles with cover cap 1 rattle-free floor guide 1 track stopper with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥499 (19 5/8") (50 and 80 kg) ≥561 (22 1/16") (120 kg)	940.44.005	940.83.054	941.25.045
For 1 door							
	With soft and self-closing mechanism on one side	Shock absorber with retaining spring	2 running gears with support flange (1 with soft and self-closing mechanism) 2 support profiles with cover caps 1 rattle-free floor guide 1 shock absorber with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥538 (21 3/16") (50 and 80 kg) ≥600 (25 5/8") (120 kg)	940.44.006	940.83.055	941.25.046
	With soft and self-closing mechanism on both sides	-	2 running gears with support flange and soft and self-closing mechanism 2 support profiles with cover caps 1 rattle-free floor guide 2 release devices with stopper for soft and self-closing mechanism	≥744 (29 5/16") (50 and 80 kg) ≥868 (34 3/16") (120 kg)	940.44.007	940.83.056	941.25.047

Note

Please order track, fascia and accessories separately. Order 2 sets for bi-parting sliding doors. Please order adjustment aid for adjusting the running gears (height and position) separately.

Please note when using the shock absorber with retaining spring: The door may not close completely if the closing speed is too low, if it is too high, the door may bounce back slightly. Sets without or with soft and self-closing mechanism on one side can be retrofitted with soft and self-closing mechanism or shock absorber, if desired.

→ **Accessories for retrofitting**

		Weight capacity	Item No.
Soft and self-closing mechanism, with release device with stopper, for clamping onto running gear		50 kg (110 lbs.) 80 kg (172 lbs.) 120 kg (264 lbs.)	940.42.304 940.83.300 941.02.300
Shock absorber with retaining spring, for clamping onto running gear		50 kg (110 lbs.) 80 kg (172 lbs.) 120 kg (264 lbs.)	940.42.305 940.83.301 941.02.301

Häfele Slido D-Line11 50P–120P Sets

→ Complete Sets without Upper Track and Fascias

	Version		Supplied with	Door width	50P ≤50 kg (110 lbs.) per door	80P ≤80 kg (176 lbs.) per door	120P ≤120 kg (264 lbs.) per door
Running gear with axle bearing							
For 1 door	Without soft and self-closing mechanism	Track stopper with retaining spring	2 running gears 1 rattle-free floor guide 2 track stoppers with retaining spring	≥500 mm (19 11/16")	940.42.064	940.83.005	941.02.036
	With soft and self-closing mechanism on one side	Track stopper with retaining spring	2 running gears (1 with soft and self-closing mechanism) 1 rattle-free floor guide 1 track buffer with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥499 mm (19 5/8") (50 and 80 kg) ≥561 mm (22 1/16") (120 kg)	940.42.065	940.83.006	941.02.037
Running gear with ball bearing mounted rollers							
For 1 door	With soft and self-closing mechanism on one side	Shock absorber with retaining spring	2 running gears (1 with soft and self-closing mechanism) 1 rattle-free floor guide 1 shock absorber with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥558 mm (21 15/16") (50 and 80 kg) ≥620 mm (24 7/8") (120 kg)	940.42.066	940.83.007	941.02.038
	With soft and self-closing mechanism on both sides	–	2 running gears with soft and self-closing mechanism 1 rattle-free floor guide 2 release devices with stopper for soft and self-closing mechanism	≥744 mm (29 9/32") (50 and 80 kg) ≥868 mm (34 3/16") (120 kg)	940.42.067	940.83.008	941.02.039

Note

Please order track, fascias and accessories separately. Order 2 sets for bi-parting sliding doors.

When using the shock absorber with retaining spring the door may not close completely if the closing speed is too low; if it is too high, the door may bounce back slightly. For sets without or with soft and self-closing mechanism on one side: Soft and self-closing mechanism or shock absorber can be retrofitted, if desired.


→ Complete Sets with Upper Track for 1 sliding door

Door panel width		Door weight	Supplied with	Item No.
Up to 1000 mm (39 3/8")		50 kg (110 lbs.)	1 fitting set 940.42.064 and 1 upper track 940.43.921	499.72.110
			1 fitting set 940.42.065 and 1 upper track 940.43.921	499.72.111
			1 fitting set 940.42.067 and 1 upper track 940.43.921	499.72.112
		80 kg (176 lbs.)	1 fitting set 940.83.005 and 1 upper track 940.43.921	499.72.120
			1 fitting set 940.83.006 and 1 upper track 940.43.921	499.72.121
			1 fitting set 940.83.008 and 1 upper track 940.43.921	499.72.122

Note

Order 2 sets for a bi-parting or a bypassing sliding door application.

→ Accessories for retrofitting

		Weight capacity	Item No.
Soft and self-closing mechanism, with release device with stopper, for clamping onto running gear		50 kg (110 lbs.)	940.42.304
		80 kg (172 lbs.)	940.83.300
		120 kg (264 lbs.)	941.02.300
Shock absorber with retaining spring, for clamping onto running gear		50 kg (110 lbs.)	940.42.305
		80 kg (172 lbs.)	940.83.301
		120 kg (264 lbs.)	941.02.301

Häfele Slido D-Line11 50C–120C Sets


	Version		Supplied with	Door width	50C ≤50 kg (110 lbs.) per door	80C ≤80 kg (176 lbs.) per door	120C ≤120 kg (264 lbs.) per door
Running gear with axle bearing							
	Without soft and self-closing mechanism	Track stopper with retaining spring	2 running gears 1 rattle-free floor guide 2 track stoppers with retaining spring	≥500 mm (19 11/16")	940.42.076	940.83.014	941.02.046
	With soft and self-closing mechanism on one side	Track stopper with retaining spring	2 running gears (1 with soft and self-closing mechanism) 1 rattle-free floor guide 1 track buffer with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥499 mm (19 5/8") (50 and 80 kg) ≥561 mm (22 1/16") (120 kg)	940.42.077	940.83.015	941.02.047
For 1 door							
	With soft and self-closing mechanism on one side	Shock absorber with retaining spring	2 running gears (1 with soft and self-closing mechanism) 1 rattle-free floor guide 1 shock absorber with retaining spring 1 release device with stopper for soft and self-closing mechanism	≥558 mm (21 15/16") (50 and 80 kg) ≥620 mm (24 7/16") (120 kg)	940.42.078	940.83.016	941.02.048
	With soft and self-closing mechanism on both sides	–	2 running gears with soft and self-closing mechanism 1 rattle-free floor guide 2 release devices with stopper for soft and self-closing mechanism	≥744 mm (29 5/16") (50 and 80 kg) ≥868 mm (34 3/16") (120 kg)	940.42.079	940.83.017	941.02.049

Note

Please order track, fascias and accessories separately. Order 2 sets for bi-parting sliding doors.

When using the shock absorber with retaining spring the door may not close completely if the closing speed is too low; if it is too high, the door may bounce back slightly. For sets without or with soft and self-closing mechanism on one side, soft and self-closing mechanism or shock absorber can be retrofitted, if desired.

→ Accessories for retrofitting

			Weight capacity	Item No.
	Soft and self-closing mechanism, with release device with stopper, for clamping onto running gear		50 kg (110 lbs.) 80 kg (172 lbs.) 120 kg (264 lbs.)	940.42.304 940.83.300 941.02.300
	Shock absorber with retaining spring, for clamping onto running gear		50 kg (110 lbs.) 80 kg (172 lbs.) 120 kg (264 lbs.)	940.42.305 940.83.301 941.02.301

Häfele Slido D-Line11 80L and 120L


→ Glass Clamp Shoe Sets

Description		Material	Finish	Length	Item No.
Glass clamp shoe set for glass thickness 12.7 mm (1/2") Qty.: Length: 200 mm (7 7/8") - 2 clamps Length: 1000 mm (39 3/8") - 1 clamp Length: 1500 mm 59 1/16") - 1 clamp	–	Aluminum	silver colored anodized	200 mm (7 7/8")	940.43.067
Glass clamp shoe set for glass thickness 10 mm (3/8") Qty.: Length: 200 mm (7 7/8") - 2 clamps Length: 1000 mm (39 3/8") - 1 clamp Length: 1500 mm 59 1/16") - 1 clamp	–			1 m (39 3/8")	940.43.068
Clip panel set for glass clamp shoe (4 pcs.) Height: 52 mm (2 1/16")	(P)			1.5 m (59 1/16")	940.43.069
Clip panel set for glass clamp shoe (2 pcs.) Height: 52 mm (2 1/16")	(P)	Aluminum	silver colored anodized	200 mm (7 7/8")	940.43.041
Clip panel set for glass clamp shoe (2 pcs.) Height: 52 mm (2 1/16")	(P)			1 m (39 3/8")	940.43.043
End cap set for glass thickness 10 mm (3/8") and 12.7 mm (1/2")	–	Plastic	silver colored	1.5 m (59 1/16")	940.43.045

Note

Use continuous glass clamp shoe in combination with clip panel (P) and end cap set.

→ Accessories for retrofitting

Description		Weight capacity	Item No.
Soft and self-closing mechanism with release device with stopper, for clamping onto running gear		80 kg (176 lbs.)	940.83.300
		120 kg (264 lbs.)	941.02.300
Shock absorber with retaining spring, for clamping onto running gear		80 kg (176 lbs.)	940.83.301
		120 kg (264 lbs.)	941.02.301