

## Alu 80/A with Softmaster Set

• For 1 sliding door without upper track and lower guide channel

|  | Item No.   |
|--|------------|
|  | 940.84.003 |

## **Set Components**

|          | Description  | Material                   | Finish           | Qty.   | Item No.   |
|----------|--|----------------------------|------------------|--------|------------|
|          | Double roller running gear                         | Steel;<br>Rollers: Plastic | -                | 2 pcs. | 940.84.013 |
| 3/5/3    | Supporting flange, screw mounted                   | Steel                      | blue chromatized | 1 pc.  | 940.40.020 |
|          | Supporting flange, adjustable depth, with M8 screw | Steel                      | -                | 1 pc.  | 940.46.020 |
| <b>3</b> | Softmaster   | -                          | -                | 1 pc.  | 940.84.040 |
|          | Track stopper, with retainer                       | -                          | -                | 1 pc.  | 940.84.043 |
|          | Floor guide  | Plastic                    | -                | 1 pc.  | 940.40.030 |

## Note

Dimensional data not binding. We reserve the right to alter specifications without notice.

Item numbers are valid only for one piece, when ordering individual components, please state the desired amount For 2 bi-parting sliding doors, please order 2 sets

## **Individual Components**

|     | Description  | Material | Finish                | Length             | Item No.   |
|-----|--|----------|-----------------------|--------------------|------------|
|     | Upper tracks, pre-drilled                            |          | -<br>bright<br>-<br>- | 1.6 m (5' 3")      | 940.84.160 |
|     |  |          |                       | 2 m (6' 6 3/4")    | 940.84.200 |
|     |  | Aluminum |                       | 2.5 m (8' 2 7/16") | 940.84.250 |
|     |  |          |                       | 4 m (13' 1 1/2")   | 940.84.400 |
|     |  |          |                       | 6 m (19' 8 1/4")   | 940.84.600 |
| 000 | Wall mounting bracket Install every 400 mm (15 3/4") | Steel    | chrome-plated         | 27.5 mm (1 3/32")  | 940.84.071 |
| 000 | Wall mounting bracket Install every 400 mm (15 3/4") | Steel    | chrome-plated         | 41 mm (19/32")     | 940.84.072 |