

Alu 80/A Set

- For 1 sliding door without upper track and lower guide channel

	Item No.
	940.84.001

1


Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	Steel; Rollers: Plastic	–	2 pcs.	940.84.013
	Supporting flange, M8	Steel	blue chromatized	2 pcs.	940.40.020
	Track stopper	–	–	2 pcs.	940.84.041
	Bumper	Rubber	black	1 pc.	940.46.051
	Floor guide	Plastic	–	1 pc.	940.40.030

Note

Item numbers are valid only for one piece, when ordering individual components, please state the desired amount
For 2 bi-parting sliding doors, please order 2 sets

Individual Components

	Description	Material	Finish	Length	Item No.
	Upper tracks, pre-drilled	Aluminum	bright	1.6 m (5' 3")	940.84.160
				2 m (6' 6 3/4")	940.84.200
				2.5 m (8' 2 7/16")	940.84.250
				4 m (13' 1 1/2")	940.84.400
				6 m (19' 8 1/4")	940.84.600
	Wall mounting bracket Install every 400 mm (15 3/4")	Steel	chrome-plated	27.5 mm (1 3/32")	940.84.071
	Wall mounting bracket Install every 400 mm (15 3/4")	Steel	chrome-plated	41 mm (1 19/32")	940.84.072

Alu 80/A with Softmaster Set

- For 1 sliding door without upper track and lower guide channel

	Item No.
	940.84.003

1

Set Components

	Description	Material	Finish	Qty.	Item No.
	Double roller running gear	Steel; Rollers: Plastic	–	2 pcs.	940.84.013
	Supporting flange, screw mounted	Steel	blue chromatized	1 pc.	940.40.020
	Supporting flange, adjustable depth, with M8 screw	Steel	–	1 pc.	940.46.020
	Softmaster	–	–	1 pc.	940.84.040
	Track stopper, with retainer	–	–	1 pc.	940.84.043
	Floor guide	Plastic	–	1 pc.	940.40.030

Note

Item numbers are valid only for one piece, when ordering individual components, please state the desired amount
For 2 bi-parting sliding doors, please order 2 sets

Individual Components

	Description	Material	Finish	Length	Item No.
	Upper tracks, pre-drilled	Aluminum	bright	1.6 m (5' 3")	940.84.160
				2 m (6' 6 3/4")	940.84.200
				2.5 m (8' 2 7/16")	940.84.250
				4 m (13' 1 1/2")	940.84.400
				6 m (19' 8 1/4")	940.84.600
	Wall mounting bracket Install every 400 mm (15 3/4")	Steel	chrome-plated	27.5 mm (1 3/32")	940.84.071
	Wall mounting bracket Install every 400 mm (15 3/4")	Steel	chrome-plated	41 mm (19/32")	940.84.072