

EKU Divido 100 HM Set





- For 1 sliding door without upper track

	Item No.
	941.00.115

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels	Plastic	white	2 pcs.
	Suspension bolt, M8 x 35 mm	Steel	zinc-plated	2 pcs.
	Carrier block	Plastic	white	2 pcs.
	Suspension profile for carrier block	Aluminum	unanodized	2 pcs.
	Door stopper with adjustable retention spring	Plastic	gray	2 pcs.
	Lower guide	Plastic	anthracite gray	1 pc.
	Fixing screws	—	—	1 set

Individual Components


	Description	Material	Finish	Length	Item No.
	Single upper track, 30 x 31 mm (1 3/16" x 1 1/4")	Aluminum	unanodized	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
				6 m (19' 8 1/4")	941.00.600
	Dual upper track, 73 x 31 mm (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 13/16")	941.12.935
				6 m (19' 8 1/4")	941.12.960
	Triple upper track, 111 x 31 mm (4 3/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.425
				3.5 m (11' 5 13/16")	941.13.435
				6 m (19' 8 1/4")	941.13.460
	Track cleaning tool	Aluminum	silver	—	941.00.099
	Soft close	—	—	10 - 60 kg (22 - 132 lbs.)	940.60.045
				61 - 100 kg (133 - 200 lbs.)	940.60.010
	Cover cap, for soft close	—	—	—	940.60.094
	Milling jig, for soft close	—	—	—	940.60.095

Installation Plan

(Included in fitting set), mounting instructions for planning and execution available upon request.

EKU Stacking





Set Components

	Description	2 doors	3 doors	Item No.
	Lower guide set for installation on right	1 set	2 sets	941.12.063
	Lower guide set for installation on left	1 set	2 sets	941.12.062
	End plate set (for left and right installation)	1 set	1 set	941.12.064

Note

Order example, for a 3 door installation on the right order 2 sets of 941.12.063 and 1 set of 942.12.064.

Individual Components







	Description	Material	Finish	Length	Item No.
	Dual guide channel	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.926
				3.5 m (11' 5 13/16")	941.13.936
				6 m (19' 8 1/4")	941.13.961
	Dual upper track, 73 x 31 mm (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 13/16")	941.12.935
				6 m (19' 8 1/4")	941.12.960
	Triple upper track, 111 x 31 mm (4 3/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.425
				3.5 m (11' 5 13/16")	941.13.435
				6 m (19' 8 1/4")	941.13.460
	Clip profile, with notch, for wooden doors Note Only required in combination with vertical handle profile and safety clip	Aluminum	anodized	3 m (9' 10 1/8")	941.12.431
	Vertical handle profile	Aluminum	silver	3 m (9' 10 1/8")	940.93.330
	Safety clip Note Only required in conjunction with vertical handle profile	Aluminum	silver	–	940.92.090
	Track cleaning tool	Aluminum	silver	–	941.00.099

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm
Inches are approximate

EKU Divido 100 Stacking

Individual Components

	Description	Material	Finish	Length	Qty. 2 Doors	Qty. 3 Doors	Item No.
	Right arm with screws	-	-	-	1 pc.	2 pcs.	941.12.063
	Left arm with screws				1 pc.	2 pcs.	941.12.062
	End plate with screws	-	-	-	1 pc.	1 pc.	941.12.064
					1 pc.	1 pc.	
	Dual guide track	Aluminum	anodized	2.5 m (8' 2 7/16")	-		941.13.926
				3.5 m (11' 5 25/32")			941.13.936
				6 m (19' 8 1/4")			941.13.961
	Vertical frame profile, with notch	Aluminum	anodized	3 m (9' 10 1/8")	-		941.12.231
	Vertical handle profile, with notch, 30 x 37.5 mm (1 3/16" x 1 7/16")	Aluminum	anodized	3 m (9' 10 1/8")	-		940.93.330
	Track cleaning tool	Plastic	gray	-	-		941.00.099
	Dual upper running track, 73 x 31 mm (2 7/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	-		941.12.925
				3.5 m (11' 5 25/32")			941.12.935
				6 m (19' 8 1/4")			941.12.960
	Triple upper running track, 111 x 31 mm (4 3/8" x 1 1/4")	Aluminum	anodized	2.5 m (8' 2 7/16")	-		941.13.425
				3.5 m (11' 5 25/32")			941.13.435
				6 m (19' 8 1/4")			941.13.460