




Hawa Divido 100 GRM Set

	Supplied with	Item No.
For 1 sliding door without upper track and aluminum frame profiles	2 running gears 2 suspension bolts M8 x 35 mm 2 suspension plates 2 door stoppers with retention spring 1 lower guide 1 set of mounting screws	941.12.001


→ Tracks

Description		Material	Finish	Length	Item No.
Single upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
				6 m (19' 8 1/4")	941.00.605
Single upper track with service notch, pre-drilled, 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	anodized	2.5 m (8' 2 7/16")	941.00.251
Dual upper track, pre-drilled 73 x 31 mm (2 7/8" x 1 7/32")		Aluminum	anodized	2.5 m (8' 2 7/16")	941.12.925
				3.5 m (11' 5 13/16")	941.12.935
				6 m (19' 8 1/4")	941.12.960
Triple upper track, pre-drilled 111 x 31 mm (4 3/8" x 1 7/32")		Aluminum	anodized	2.5 m (8' 2 7/16")	941.13.425
				3.5 m (11' 5 13/16")	941.13.435
				6 m (19' 8 1/4")	941.13.460

→ Accessories

Description		Material	Finish	Length	Item No.
Soft close 10–60 kg (22–132 lbs.)		–	–	–	940.60.045
Soft close 61–100 kg (133–200 lbs.)		–	–	–	940.60.010
Cover cap for notched service access in track		–	–	–	940.60.094
Milling jig for notched service access in track		–	–	–	940.60.095
Wall compensation profile, with sealing profile		Aluminum	anodized	3 m (9' 10 1/8")	940.93.230
				2.5 m (8' 2 7/16")	940.93.225





Wall compensation profile



Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Porta 60/100 HMT

→ Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	mill	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
				6 m (19' 8 1/4")	941.00.600
			silver anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
				6 m (19' 8 1/4")	941.00.605
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32"), with service notch		Aluminum	silver anodized	2.5 m (8' 2 7/16")	941.00.251
Upper track assembly set, includes removable track, assembly blocks, and screws		Aluminum	silver anodized	2 m (6' 6 3/4")	941.00.622
				2.5 m (8' 2 7/16")	941.00.623
Disassembly key		Steel	zinc-plated	—	940.60.097
Floor guide, adjustable		Plastic	anthracite	65 mm (2 9/16")	941.00.037
Spring-loaded track stopper		Steel	zinc-plated	—	941.00.404
Upper track cleaning tool		Plastic	gray	—	941.00.099
Push-to-open soft close mechanism, 61–100 kg (134–220 lbs.)		—	—	—	941.00.403

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.