


Hawa Porta 100 GF Set

	Supplied with	Item No.
For 1 sliding door without the upper track	2 running gears 2 suspension bolts 2 set nuts, M8 2 clamp shoes with hex screw and hex nut, adjustable from 6–12.7 mm (1/4"–1/2") 2 track stoppers (1 with retaining spring, 1 without retaining spring) 1 track stopper 1 rattle-free floor guide, adjustable from 6–12.7 mm (1/4"–1/2") 1 rubber wall buffer	941.00.007

Note

For 2 bi-parting sliding doors order 2 sets

→ Tracks and Accessories

Description		Material	Finish	Length	Item No.
Running track, pre-drilled		Aluminum	mill	2.5 m (8' 2 7/16") 6 m (19' 8 1/4")	941.00.254 941.00.604
Clip-on fascia 94.5 x 6 mm (3 23/32" x 1/4")		Aluminum	anodized	2.5 m (8' 2 7/16") 6 m (19' 8 1/4")	941.00.825 941.00.860
Support profile for fixed glass, pre-drilled 53 x 19 mm (2 3/32" x 3/4")		Aluminum	anodized	2.5 m (8' 2 7/16") 6 m (19' 8 1/4")	941.01.825 941.01.860
Fixed glazing profile/lower guide channel, pre-drilled, 30 x 20 mm (1 3/16" x 25/32")		Aluminum	anodized	2.5 m (8' 2 7/16") 6 m (19' 8 1/4")	941.01.725 941.01.760
Fixing set for support profile and fixed glazing profile		Aluminum	anodized	–	941.01.899
End cap to clip-on fascia, wall mounted, 1 pc.		Aluminum	anodized	64.5 mm (2 17/32")	941.00.068
End cap to clip-on fascia, ceiling mounted, 1 pc.		Aluminum	anodized	70.5 mm (2 25/32")	941.00.069
Seal		Plastic	black	20 m (65' 7 3/8")	941.00.096
Sealing profile for glass thickness: 8–10 mm (5/16"–13/32") *12.7 mm (1/2")		Rubber	black	20 m (65' 7 3/8")	941.00.104
Upper track cleaning tool		Plastic	gray	–	941.00.099
Soft close 10–60 kg (22–132 lbs.)		–	–	–	940.60.045
Soft close 61–100 kg (133–200 lbs.)		–	–	–	940.60.010
Cover cap for notched service access in track		–	–	–	940.60.094
Milling jig for notched service access in track		–	–	–	940.60.095

Note

When using the end caps for the clip-on fascia, please observe the mounting instructions for cutting of the upper track and clip-on fascia.
*Wet glazing for fixed glass is required for glass thickness >10 mm (13/32")