

## EKU Porta 60/100 H Set

- For 1 sliding door without the upper track

| Door Weight        | Item No.   |
|--------------------|------------|
| ≤60 kg (132 lbs.)  | 940.60.111 |
| ≤100 kg (220 lbs.) | 941.00.111 |

### Note

Order 2 sets for bi-parting doors.

### Set Components

|                                                                                   | Description                                              | Material | Finish     | Qty.   |
|-----------------------------------------------------------------------------------|----------------------------------------------------------|----------|------------|--------|
|  | Running gear, with four wheels, suspension screw and nut | –        | –          | 2 pcs. |
|  | Support flange                                           | Steel    | galvanized | 2 pcs. |
|  | Track stopper, with retaining spring                     | –        | –          | 2 pcs. |
|  | Floor guide, adjustable                                  | Plastic  | anthracite | 1 pc.  |
|  | Fixing screws                                            | –        | –          | 1 set  |

### Individual Components

|                                                                                     | Description                                                                                         | Material | Finish     | Length               | Item No.   |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|----------|------------|----------------------|------------|
|   | Upper track, pre-drilled,<br>30 x 31 mm (1 3/16" x 1 7/32")                                         | Aluminum | mill       | 2 m (6' 6 3/4")      | 941.00.200 |
|                                                                                     |                                                                                                     |          |            | 2.5 m (8' 2 7/16")   | 941.00.250 |
|                                                                                     |                                                                                                     |          |            | 6 m (19' 8 1/4")     | 941.00.600 |
|                                                                                     |                                                                                                     |          | anodized   | 2 m (6' 6 3/4")      | 941.00.205 |
|                                                                                     |                                                                                                     |          |            | 2.5 m (8' 2 7/16")   | 941.00.255 |
|                                                                                     |                                                                                                     |          |            | 6 m (19' 8 1/4")     | 941.00.605 |
|  | Combination track, pre-drilled,<br>for wall and ceiling mounting,<br>39 x 41 mm (1 17/32" x 1 5/8") | Aluminum | mill       | 2.5 m (8' 2 7/16")   | 941.00.253 |
|                                                                                     |                                                                                                     |          |            | 3.5 m (11' 5 25/32") | 941.00.353 |
|                                                                                     |                                                                                                     |          |            | 6 m (19' 8 1/4")     | 941.00.603 |
|  | Clip panel,<br>60 mm (2 3/8")                                                                       | Aluminum | anodized   | 2.5 m (8' 2 7/16")   | 941.12.425 |
|                                                                                     |                                                                                                     |          |            | 3.5 m (11' 5 25/32") | 941.12.435 |
|                                                                                     |                                                                                                     |          |            | 6 m (19' 8 1/4")     | 941.12.460 |
|  | Clip, for wood and aluminum panel,<br>pre-drilled                                                   | Aluminum | mill       | 97 mm (3 13/16")     | 940.60.065 |
|  | Floor guide, adjustable                                                                             | Plastic  | anthracite | 65 mm (2 9/16")      | 941.00.037 |
|  | Floor guide, with wall mounting bracket                                                             | Steel    | galvanized | 81.5 mm (3 7/32")    | 941.00.036 |

Dimensional data not binding. We reserve the right to alter specifications without notice.

Dimensions in mm  
Inches are approximate

## EKU Divido 100 H Set


- For 1 sliding door without upper track

| Item No.   |
|------------|
| 941.00.111 |

## Set Components

|                                                                                   | Description                                   | Material | Finish          | Qty.   |
|-----------------------------------------------------------------------------------|-----------------------------------------------|----------|-----------------|--------|
|  | Running gear, with four wheels                | Plastic  | white           | 2 pcs. |
|  | Suspension bolt, M8 x 32 mm                   | Steel    | zinc-plated     | 2 pcs. |
|  | Set nut, M8                                   | Steel    | zinc-plated     | 2 pcs. |
|  | Suspension plate                              | Steel    | zinc-plated     | 2 pcs. |
|  | Door stopper with adjustable retention spring | Plastic  | gray            | 2 pcs. |
|  | Lower guide                                   | Plastic  | anthracite gray | 1 pc.  |
|  | Fixing screws                                 | –        | –               | –      |

## Individual Components

|                                                                                     | Description                                                                                                  | Material | Finish     | Length                       | Item No.   |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|----------|------------|------------------------------|------------|
|    | Single upper track,<br>39 x 41 mm (1 9/16" x 1 5/8")                                                         | Aluminum | unanodized | 2.5 m (8' 2 7/16")           | 941.00.253 |
|                                                                                     |                                                                                                              |          |            | 3.5 m (11' 5 13/16")         | 941.00.353 |
|                                                                                     |                                                                                                              |          |            | 6 m (19' 8 1/4")             | 941.00.603 |
|   | Dual upper track,<br>73 x 31 mm (2 7/8" x 1 1/4")                                                            | Aluminum | anodized   | 2.5 m (8' 2 7/16")           | 941.12.925 |
|                                                                                     |                                                                                                              |          |            | 3.5 m (11' 5 13/16")         | 941.12.935 |
|                                                                                     |                                                                                                              |          |            | 6 m (19' 8 1/4")             | 941.12.960 |
|  | Triple upper track<br>111 x 31 mm (4 3/8" x 1 1/4")                                                          | Aluminum | anodized   | 2.5 m (8' 2 7/16")           | 941.13.425 |
|                                                                                     |                                                                                                              |          |            | 3.5 m (11' 5 13/16")         | 941.13.435 |
|                                                                                     |                                                                                                              |          |            | 6 m (19' 8 1/4")             | 941.13.460 |
|  | Spacer profile for wall mounting of single upper track<br>11 x 36 mm (7/16" x 1 7/16")                       | Plastic  | gray       | 2 m (6' 6 3/4")              | 941.13.220 |
|  | Clip-in skirt,<br>10 x 42 mm (3/8" x 1 11/16")                                                               | Aluminum | anodized   | 2.5 m (8' 2 7/16")           | 941.12.325 |
|                                                                                     |                                                                                                              |          |            | 3.5 m (11' 5 13/16")         | 941.12.335 |
|                                                                                     |                                                                                                              |          |            | 6 m (19' 8 1/4")             | 941.12.360 |
|  | Clip-on fascia to upper track,<br>7 x 60 mm (5/16" x 2 3/8")                                                 | Aluminum | anodized   | 2.5 m (8' 2 7/16")           | 941.12.425 |
|                                                                                     |                                                                                                              |          |            | 3.5 m (11' 5 13/16")         | 941.12.435 |
|                                                                                     |                                                                                                              |          |            | 6 m (19' 8 1/4")             | 941.12.460 |
|  | Brush seal for clip-on fascia,<br>5 x 5 mm (3/16" x 3/16")                                                   | Plastic  | gray       | 10 m (32' 9 11/16")          | 405.80.501 |
|  | End piece to fascia, one-sided, wall mounted,<br>51 x 60 mm (2" x 2 3/8")                                    | Aluminum | anodized   | –                            | 941.12.060 |
|  | Clip piece for wood fascia,<br>97 x 29 x 9.5 mm (3 13/16" x 1 1/8" x 3/8"), mounted every 500 mm (19 11/16") | Aluminum | unanodized | –                            | 940.60.065 |
|  | Soft close                                                                                                   | –        | –          | 10 - 60 kg (22 - 132 lbs.)   | 940.60.045 |
|                                                                                     |                                                                                                              |          |            | 61 - 100 kg (133 - 200 lbs.) | 940.60.010 |
|  | Cover cap, for soft close                                                                                    | –        | –          | –                            | 940.60.094 |
|  | Milling jig, for soft close                                                                                  | –        | –          | –                            | 940.60.095 |

Dimensional data not binding. We reserve the right to alter specifications without notice.


Dimensions in mm  
Inches are approximate

## EKU Divido 100 GR Set


- For 1 sliding door without upper track

| Item No.   |
|------------|
| 941.12.000 |

### Individual Components

|                                                                                   | Description                                   | Material | Finish      | Qty.   |
|-----------------------------------------------------------------------------------|-----------------------------------------------|----------|-------------|--------|
|  | Running gear with four wheels                 | Plastic  | white       | 2 pcs. |
|  | Suspension bolt, M8 x 35 mm                   | Steel    | zinc-plated | 2 pcs. |
|  | Set nut, M8                                   | Steel    | zinc-plated | 2 pcs. |
|  | Suspension plate                              | Aluminum | –           | 2 pcs. |
|  | Door stopper with adjustable retention spring | Plastic  | gray        | 2 pcs. |
|  | Lower guide with plastic horizontal wheels    | Steel    | zinc-plated | 1 pc.  |
|  | Fixing screws                                 | –        | –           | 1 set  |

### Individual Components

|                                                                                     | Description                                                                                     | Material | Finish     | Length               | Item No.   |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|----------|------------|----------------------|------------|
|  | Single upper track,<br>39 x 41 mm (1 9/16" x 1 5/8")                                            | Aluminum | unanodized | 2.5 m (8' 2 7/16")   | 941.00.253 |
|                                                                                     |                                                                                                 |          |            | 3.5 m (11' 5 25/32") | 941.00.353 |
|                                                                                     |                                                                                                 |          |            | 6 m (19' 8 1/4")     | 941.00.603 |
|  | Dual upper track,<br>73 x 31 mm (2 7/8" x 1 1/4")                                               | Aluminum | anodized   | 2.5 m (8' 2 7/16")   | 941.12.925 |
|                                                                                     |                                                                                                 |          |            | 3.5 m (11' 5 25/32") | 941.12.935 |
|                                                                                     |                                                                                                 |          |            | 6 m (19' 8 1/4")     | 941.12.960 |
|  | Spacer profile for wall mounting of single upper running track,<br>11 x 36 mm (7/16" x 1 7/16") | Plastic  | gray       | 2 m (6' 6 3/4")      | 941.13.220 |
|  | Clip-in skirt,<br>10 x 42 mm (13/32" x 1 11/16")                                                | Aluminum | anodized   | 2.5 m (8' 2 7/16")   | 941.12.325 |
|                                                                                     |                                                                                                 |          |            | 3.5 m (11' 5 25/32") | 941.12.335 |
|                                                                                     |                                                                                                 |          |            | 6 m (19' 8 1/4")     | 941.12.360 |
|  | Clip-on fascia to upper running track,<br>7 x 60 mm (5/16" x 2 3/8")                            | Aluminum | anodized   | 2.5 m (8' 2 7/16")   | 941.12.425 |
|                                                                                     |                                                                                                 |          |            | 3.5 m (11' 5 25/32") | 941.12.435 |
|                                                                                     |                                                                                                 |          |            | 6 m (19' 8 1/4")     | 941.12.460 |
|  | Brush seal for clip-on fascia,<br>5 x 5 mm (3/16" x 3/16")                                      | Plastic  | gray       | 10 m (32' 9 11/16")  | 405.80.501 |
|  | End piece to fascia, one-sided, wall mounted,<br>51 x 60 mm (2" x 2 3/8")                       | Aluminum | anodized   | –                    | 941.12.060 |
|  | Soft close 10 – 60 kg (22 – 132 lbs.)                                                           | –        | –          | –                    | 940.60.045 |
|                                                                                     | Soft close 61 – 100 kg (135 – 220 lbs.)                                                         |          |            |                      | 940.60.010 |
|                                                                                     | Cover cap for notched service access in track                                                   |          |            |                      | 940.60.094 |
|                                                                                     | Drill jig for notched service access in track                                                   |          |            |                      | 940.60.095 |

### Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.

Aluminum frame profiles pages 1.226-1.227