




Hawa Porta 60/100 HMT

→ Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	mill	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
				6 m (19' 8 1/4")	941.00.600
			silver anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
				6 m (19' 8 1/4")	941.00.605
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32"), with service notch		Aluminum	silver anodized	2.5 m (8' 2 7/16")	941.00.251
Upper track assembly set, includes removable track, assembly blocks, and screws		Aluminum	silver anodized	2 m (6' 6 3/4")	941.00.622
				2.5 m (8' 2 7/16")	941.00.623
Disassembly key		Steel	zinc-plated	—	940.60.097
Floor guide, adjustable		Plastic	anthracite	65 mm (2 9/16")	941.00.037
Spring-loaded track stopper		Steel	zinc-plated	—	941.00.404
Upper track cleaning tool		Plastic	gray	—	941.00.099
Push-to-open soft close mechanism, 61–100 kg (134–220 lbs.)		—	—	—	941.00.403


Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Porta 60/100 HMT Pocket Acoustics


→ For 1 Sliding Door Without Upper Track

Model	Supplied with	Door Weight	Item No.
Porta 60/100HMD/HMT Pocket Acoustics with SoftStop and track stopper, without soft close	2 running gears 2 carrier profiles with suspension plate and M8 suspension bolts 1 SoftStop Porta 100 Acoustics 1 track stopper with retaining spring 1 cover cap set, plastic, anthracite Accessories	≤ 60kg (132 lbs.)	940.60.076
		≤ 100 kg (220 lbs.)	940.60.077

→ Seal Set

Description		Supplied with	Handing	Size	Item No.	Seal selection for doors fully and partially opened	
Horizontal seal set Hawa Acoustics		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460	XS	750–850 mm (29 1/2"–33 7/16")
				S	940.80.461		
				M	940.80.462	S	850–970 mm (33 7/16"–38 3/16")
				L	940.80.463		
				XL	940.80.464		
			Right	XS	940.80.465	M	970–1100 mm (38 3/16"–43 5/16")
				S	940.80.466		
				M	940.80.467	L	1100–1220 mm (43 5/16"–48 1/16")
				L	940.80.468		
				XL	940.80.469	XL	1220–1250 mm (48 1/16"–49 3/16")

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 30 x 31 mm (1 3/16" x 1 7/32")		Aluminum	mill	2 m (6' 6 3/4")	941.00.200
				2.5 m (8' 2 7/16")	941.00.250
			silver anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
Upper track assembly set, includes removable track, assembly blocks, and screws		Aluminum	silver anodized	2 m (6' 6 3/4")	941.00.622
				2.5 m (8' 2 7/16")	941.00.623
Dis-assembly key		Steel	zinc-plated	–	940.60.097
Vertical seal		Silicone	black	7.7 m (25' 3 1/8")	940.00.500
Spring-loaded track stopper		Steel	zinc-plated	–	941.00.404
Upper track cleaning tool		Plastic	gray	–	941.00.099
Push-to-open soft close mechanism 61–100 kg (134–220 lbs.)		–	–	–	941.00.403

Sliding door locks	pages 1.384–1.394
Door pulls	pages 2.3–2.29
Flush pulls	pages 1.395–1.396

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.