HAFELE

EKU Porta 60/100 H Set

• For 1 sliding door without the upper track

Door Weight	Item No.
≤60 kg (132 lbs.)	940.60.111
≤100 kg (220 lbs.)	941.00.111

Note

Order 2 sets for bi-parting doors.

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels, suspension screw and nut	-	-	2 pcs.
63 CE3	Support flange	Steel	galvanized	2 pcs.
	Track stopper, with retaining spring	-	-	2 pcs.
G	Floor guide, adjustable	Plastic	anthracite	1 pc.
र्भ	Fixing screws	_	-	1 set

Individual Components

	Description	Material	Finish	Length	Item No.
				2 m (6' 6 3/4")	941.00.200
			mill	2.5 m (8' 2 7/16")	941.00.250
-	Upper track, pre-drilled,	A I		6 m (19' 8 1/4")	941.00.600
	30 x 31 mm (1 3/16" x 1 7/32")	Aluminum		2 m (6' 6 3/4")	941.00.205
			anodized	2.5 m (8' 2 7/16")	941.00.255
	Combination track, pre-drilled, for wall and ceiling mounting, 39 x 41 mm (1 17/32" x 1 5/8")			6 m (19' 8 1/4")	941.00.605
	Combination track, pre-drilled.			2.5 m (8' 2 7/16")	941.00.253
	for wall and ceiling mounting,	Aluminum	mill	3.5 m (11' 5 25/32")	941.00.353
	39 x 41 mm (1 17/32" x 1 5/8")			6 m (19' 8 1/4")	941.00.603
				2.5 m (8' 2 7/16")	941.12.425
1	Clip panel, 60 mm (2 3/8")	Aluminum	anodized	3.5 m (11' 5 25/32")	941.12.435
	00 11111 (2 3/6)			6 m (19' 8 1/4")	941.12.460
	Clip, for wood and aluminum panel, pre-drilled	Aluminum	mill	97 mm (3 13/16")	940.60.065
	Floor guide, adjustable	Plastic	anthracite	65 mm (2 9/16")	941.00.037
	Floor guide, with wall mounting bracket	Steel	galvanized	81.5 mm (3 7/32")	941.00.036

HAFELE

Top Hung System

EKU Porta 60/100 HM Set

• For 1 sliding door without the upper track

Door weight	Item No.
≤60 kg (132 lbs.)	940.60.115
≤100 kg (220 lbs.)	941.00.115

Note

For 2 bi-parting doors, please order 2 sets.

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels, suspension screw and nut	-	-	2 pcs.
	Support profile	Steel	galvanized	2 pcs.
A Contraction	Support profile with end cap	Plastic	anthracite	2 pcs.
	Track stopper, with retaining spring	-	-	2 pcs.
	Floor guide, adjustable	Plastic	anthracite	1 pc.
2	Fixing screws	_	-	1 set

Individual Components

	Description	Material	Finish	Length	Item No.
				2 m (6' 6 3/4")	941.00.200
			mill	2.5 m (8' 2 7/16")	941.00.250
	Upper track, pre-drilled,	Aluminum		6 m (19' 8 1/4")	941.00.600
	30 x 31 mm (1 3/16" x 1 7/32")	Aluminum	anodized	2 m (6' 6 3/4")	941.00.205
				2.5 m (8' 2 7/16")	941.00.255
				6 m (19' 8 1/4")	941.00.605
	Floor guide, adjustable	Plastic	anthracite	65 mm (2 9/16")	941.00.037

Top Hung System

EKU Porta 60/100 HMT Set

• For 1 sliding door without upper track

Door Weight	Item No.
≤60 kg (132 lbs.)	940.60.117
≤100 kg (220 lbs.)	941.00.117

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels, with hexagon bolt M8 x 36 mm (1 pc.)	-	-	2 pcs.
	Support profile	Steel	galvanized	2 pcs.
	Support profile with cover cap and engaging pin	Plastic	anthracite	1 pc.
A STATE OF THE STA	Support profile with cover cap and spring	Plastic	anthracite	1 pc.
	Track stopper, with retaining spring	_	-	2 pcs.
	Floor guide, adjustable	Plastic	anthracite	1 pc.
र्	Fixing screws	_	-	1 set
a	Cylinder screw, M8 x 35 mm	_	-	1 pc.

Individual Components

	Description	Material	Finish	Length	Item No.
				2 m (6' 6 3/4")	941.00.200
			mill	2.5 m (8' 2 7/16")	941.00.250
/ •/	Upper track, pre-drilled,	Aluminum -		6 m (19' 8 1/4")	941.00.600
	30 x 31 mm (1 3/16" x 1 7/32")	Aluminum -		2 m (6' 6 3/4")	941.00.205
			anodized	2.5 m (8' 2 7/16")	941.00.255
			6 m (19' 8 1/4")	941.00.605	
	Disassembly key	-	-	-	940.60.097
	Floor guide, adjustable	Plastic	anthracite	65 mm (2 9/16")	941.00.037



EKU Divido 100 HM Set

• For 1 sliding door without upper track

Item No.
941.00.115

Set Components

	Description	Material	Finish	Qty.
	Running gear, with four wheels	Plastic	white	2 pcs.
	Suspension bolt, M8 x 35 mm	Steel	zinc-plated	2 pcs.
A STATE OF THE STA	Carrier block	Plastic	white	2 pcs.
	Suspension profile for carrier block	Aluminum	unanodized	2 pcs.
	Door stopper with adjustable retention spring	Plastic	gray	2 pcs.
	Lower guide	Plastic	anthracite gray	1 pc.
Ź	Fixing screws	-	-	1 set

Individual Components

	Description		Material	Finish	Length	Item No.
	Describitori		iviateriai	1 11 11511		
	Single upper tra	ok			2 m (6' 6 3/4")	941.00.200
	30 x 31 mm (1 :		Aluminum	unanodized	2.5 m (8' 2 7/16")	941.00.250
					6 m (19' 8 1/4")	941.00.600
	Dual upper tree				2.5 m (8' 2 7/16")	941.12.925
Dual upper tra		Aluminum	anodized	3.5 m (11' 5 13/16")	941.12.935	
		70 X 0 1 11111 (E 170 X 1 174)			6 m (19' 8 1/4")	941.12.960
	///				2.5 m (8' 2 7/16")	941.13.425
	Triple upper trac	ack, (4 3/8" x 1 1/4")	Aluminum	anodized	3.5 m (11' 5 13/16")	941.13.435
	7 111 X 31 111111 (4 3/6 X 1 1/4)				6 m (19' 8 1/4")	941.13.460
5						
	Track cleaning t	cool	Aluminum	silver	-	941.00.099
•	Soft close	10 - 60 kg (22 - 132 lbs.)	-	-	-	940.60.045
	SUIT CIUSE	61 - 100 kg (133 - 200 lbs.)	_	_	-	940.60.010
	Cover cap, for s	ap, for soft close		-	_	940.60.094
	Milling jig, for so	oft close	-	-	-	940.60.095

Installation Plan

(Included in fitting set), mounting instructions for planning and execution available upon request.