



Hawa Porta 100 GFW Sets

	Supplied with	clear anodized	black anodized
For 1 sliding door without the upper track	2 running gears 2 suspension bolts 2 clamping shoes, adjustable from 8–12.7 mm (5/16"–1/2") 2 track stoppers (1 with retaining spring, 1 without retaining spring) 12 mounting clips for clip-on fascia 1 rattle-free floor guide, adjustable from 8–12.7 mm (5/16"–1/2") 1 rubber wall buffer 1 set of mounting screws	941.00.005	941.00.053



Note

For 2 bi-parting sliding doors order 2 sets

→ Tracks

Description		Material	Length	clear anodized	black anodized
Upper track, pre-drilled 86 x 58 mm (3 3/8" x 2 9/32")		Aluminum	2.5 m (8' 2 7/16")	941.00.256	941.00.614
			3.5 m (11' 5 13/16")	941.00.356	941.00.615
			6 m (19' 8 1/4")	941.00.606	–
Clip-on fascia to upper track 30 x 8 mm (1 3/16" x 5/16")		Aluminum	2.5 m (8' 2 7/16")	941.01.025	941.01.401
			3.5 m (11' 5 13/16")	941.01.035	941.01.402
			6 m (19' 8 1/4")	941.01.060	–
Cover profile (fills unused space of fixed glass opening) 15 x 15 mm (19/32" x 19/32")		Aluminum	2.5 m (8' 2 7/16")	941.12.525	941.12.402
			3.5 m (11' 5 13/16")	941.12.530	–
			6 m (19' 8 1/4")	941.12.560	–
Fixed glazing profile/lower guide channel, pre-drilled 30 x 20 mm (1 3/16" x 25/32")		Aluminum	2.5 m (8' 2 7/16")	941.01.725	941.01.800
			3.5 m (11' 5 13/16")	941.01.735	941.01.801
			6 m (19' 8 1/4")	941.01.760	–
Fixing set for support profile and fixed glazing profile		Aluminum	–	941.01.899	941.01.400

→ Accessories

Description		Material	Finish	Length	Item No.
Sealing profile for glass thickness: 8–10 mm (5/16"–13/32") *12.7 mm (1/2")		Rubber	black	20 m (65' 7 3/8")	941.00.104
Seal		Plastic	black	20 m (65' 7 3/8")	941.00.096
Disposable cover		Plastic	–	2 m (6' 6 3/4")	941.00.207
Milling jig for notched service access in upper track, 43 mm (1 11/16")		–	–	–	941.00.095
Soft close 10–60 kg (22–132 lbs.)		–	–	–	940.60.045
Soft close 61–100 kg (133–200 lbs.)		–	–	–	940.60.010
Cover cap for notched service access in track		–	–	–	940.60.094
Milling jig for notched service access in track, for soft close, 62 mm (2 7/16")		–	–	–	940.60.095

*Note

Wet glazing for fixed glass is required for glass thickness >10 mm (13/32")

Hawa Toplock	pages 1.378–1.382
Flush pulls	pages 1.394–1.396
Pull handles	pages 2.3–2.29