


Slido Classic 40-I to 120-I Components

	Description	Material	Finish	For Version	Qty.	Item No.
	Floor guide, rattle-free	Plastic	black	A, B, E	1 pc.	940.42.030
	Track stopper with retaining spring and rubber bumper	Plastic/ Rubber	-	A for 40 – 60 kg (88 - 132 lbs.)	2 pcs.	940.42.040
				B for 40 – 60 kg (88 - 132 lbs.)	1 pc.	
				A for 80 – 120 kg (176 - 264 lbs.)	2 pcs.	940.42.041
				B for 80 – 120 kg (176 - 264 lbs.)	1 pc.	
	Release device with stopper	Steel	galvanized	B for 40 and 80 kg (88 - 176 lbs.)	1 pc.	940.42.042
				E for 40 and 80 kg (88 - 176 lbs.)	2 pcs.	
				B for 120 kg (264 lbs.)	1 pc.	940.42.082
				E for 120 kg (264 lbs.)	2 pcs.	

Note

Item numbers are valid only for 1 piece, when ordering individual components, please state the desired amount.

Upper Tracks

	Description	For door weights	Material	Finish	Length	Item No.
1 	Single upper track, pre-drilled W x H: 31 x 33 mm (1 1/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	mill	2 m (6' 6 3/4")	940.43.921
					3 m (9' 10 1/8")	940.43.931
					6 m (19' 8 1/4")	940.43.961
				clear anodized	2 m (6' 6 3/4")	940.43.922
					3 m (9' 10 1/8")	940.43.932
					6 m (19' 8 1/4")	940.43.962
3 	Double upper track, pre-drilled W x H: 70 x 33 mm (2 3/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.02.920
					3 m (9' 10 1/8")	941.02.930
					6 m (19' 8 1/4")	941.02.960
4 	Double upper track, pre-drilled W x H: 81 x 33 mm (3 3/16" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.02.820
					3 m (9' 10 1/8")	941.02.830
					6 m (19' 8 1/4")	941.02.860
5 	Single upper track, wall mounted	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.920
					3 m (9' 10 1/8")	941.25.930
					6 m (19' 8 1/4")	941.25.960
16 	Mounting rail, width 19 mm (3/4"), for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.821
					3 m (9' 10 1/8")	941.25.831
					6 m (19' 8 1/4")	941.25.861
17 	Mounting rail, width 8 mm (5/16"), for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.820
					3 m (9' 10 1/8")	941.25.830
					6 m (19' 8 1/4")	941.25.860

Note

Aluminum mill finish upper track cannot be used in combination with a clip-on fascia. Please order threaded end insert for upper track and mounting rail separately, refer to page **1.9**.

Installation Reference

Slide in threaded end insert at rail ends. When the running track and the mounting rail are installed between walls the threaded end inserts cannot be used; instead use glue points to fix the running track to the mounting rail.

Slido Classic Upper Tracks

	Description	For door weights	Material	Finish	Length/Qty.	Item No.
1 	Single upper track, pre-drilled W x H: 31 x 33 mm (1 1/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	mill	2 m (6' 6 3/4")	940.43.921
					3 m (9' 10 1/8")	940.43.931
					6 m (19' 8 1/4")	940.43.961
				clear anodized	2 m (6' 6 3/4")	940.43.922
					3 m (9' 10 1/8")	940.43.932
					6 m (19' 8 1/4")	940.43.962
2 	Single upper track, pre-drilled W x H: 47.5 x 47 mm (1 7/8" x 1 27/32"), wall mounted	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	940.43.920
					3 m (9' 10 1/8")	940.43.930
					6 m (19' 8 1/4")	940.43.960
3 	Double upper track, pre-drilled W x H: 70 x 33 mm (2 3/4" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.02.920
					3 m (9' 10 1/8")	941.02.930
					6 m (19' 8 1/4")	941.02.960
4 	Double upper track, pre-drilled W x H: 81 x 33 mm (3 3/16" x 1 5/16")	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.02.820
					3 m (9' 10 1/8")	941.02.830
					6 m (19' 8 1/4")	941.02.860
5 	Single upper track, wall mounted	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.602
					3 m (9' 10 1/8")	941.25.603
					6 m (19' 8 1/4")	941.25.606
16 	Mounting rail, width 19 mm (3/4"), for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.821
					3 m (9' 10 1/8")	941.25.831
					6 m (19' 8 1/4")	941.25.861
17 	Mounting rail, width 8 mm (5/16"), for track #5	40 – 120 kg (88 – 264 lbs.)	Aluminum	clear anodized	2 m (6' 6 3/4")	941.25.820
					3 m (9' 10 1/8")	941.25.830
					6 m (19' 8 1/4")	941.25.860




Note

Aluminum mill finish upper track cannot be used in combination with clip fascia. Please order threaded end insert for upper track **5** and mounting rails **16** and **17** separately, below.

Installation Reference

Slide in threaded end insert at rail ends. When the running track and the mounting rail are installed between walls the threaded end inserts cannot be used; instead use glue points to fix the running track to the mounting rail.

Mounting Brackets and Accessories

	Description	Area of application	Material	Finish	Length	Item No.
10 	Mounting bracket, with screw and nut	For upper track 1	Steel	galvanized	36 mm (1 7/16")	940.42.061
					44 mm (1 3/4")	940.62.061
					64 mm (2 1/2")	940.42.063
–	 Wrench for height adjustment	–	Steel	galvanized	–	940.43.032
–	 Threaded end insert	For upper track 5 and mounting rails 16 and 17	Steel	galvanized	1 set	941.25.090

Note

Install wall mounting bracket **10** every 400 mm (15 3/4")