


Hawa Junior 100 B Acoustics Set

→ For 1 Sliding Door Without Upper Track

Model	Door Width	Supplied with	Item No.
Junior 100 B / B Pocket with SoftStop on both sides, without soft close	≥ 820 mm (32 5/16")	2 running gears 2 carrier profiles with suspension plate incl. M10 bolt 1 SoftStop, with retaining spring and ramp 1 SoftStop, with retaining spring 1 Cover cap set, plastic, aluminum finish 1 adjustment wrench	941.04.017

→ Seal Set

Description		Supplied with	Handing	Size	Item No.
Horizontal seal set Hawa Acoustics		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460
				S	940.80.461
				M	940.80.462
				L	940.80.463
				XL	940.80.464
			Right	XS	940.80.465
				S	940.80.466
				M	940.80.467
				L	940.80.468
				XL	940.80.469

Seal selection for doors fully opened

Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–780 mm (29 1/2"–30 11/16")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	780–900 mm (30 11/16"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	900–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Seal selection for doors partially opened


Dim. X	30 mm (1 3/16")	40 mm (1 9/16")	50 mm (2")	60 mm (2 3/8")
Seal size	Clear opening width			
XS	750–870 mm (29 1/2"–34 1/4")	750–770 mm (29 1/2"–30 5/16")	750–760 mm (29 1/2"–29 15/16")	750 mm (29 1/2")
S	870–990 mm (34 1/4"–35 7/16")	770–890 mm (30 5/16"–35 1/16")	760–880 mm (29 15/16"–34 5/8")	750–870 mm (29 1/2"–34 1/4")
M	990–1030 mm (35 7/16"–40 9/16")	890–1020 mm (35 1/16"–40 3/16")	880–1010 mm (34 5/8"–39 3/4")	870–1000 mm (34 1/4"–39 3/8")
L	1030–1150 mm (40 9/16"–45 1/4")	1020–1140 mm (40 3/16"–44 7/8")	1010–1130 mm (39 3/4"–44 1/2")	1000–1120 mm (39 3/8"–44 1/8")
XL	1150–1250 mm (45 1/4"–49 3/16")	1140–1250 mm (44 7/8"–49 3/16")	1130–1250 mm (44 1/2"–49 3/16")	1120–1250 mm (44 1/8"–49 3/16")

Hawa Junior 100 B Pocket Acoustics






→ For 1 Sliding Door Without Upper Track

Model	Door width	Supplied with	Item No.
Junior 100 B / B Pocket with SoftStop on both sides, without soft close	≥ 800 mm (31 1/2")	2 running gears 2 carrier profiles with suspension plate incl. M10 bolt 1 SoftStop, with retaining spring and ramp 1 SoftStop, with retaining spring 1 Cover cap set, plastic, aluminum finish 1 adjustment wrench	941.04.017

→ Seal Set

Description		Supplied with	Handing	Size	Item No.	Seal selection for doors fully and partially opened	
Horizontal seal set		1 upper seal 1 lower seal 1 small part set, top 1 small part set, bottom 1 pocket door adapter	Left	XS	940.80.460	XS	750–850 mm (29 1/2"–33 7/16")
				S	940.80.461		
				M	940.80.462	S	850–970 mm (33 7/16"–38 3/16")
				L	940.80.463		
				XL	940.80.464		
			Right	XS	940.80.465	M	970–1100 mm (38 3/16"–43 5/16")
				S	940.80.466		
				M	940.80.467	L	1100–1220 mm (43 5/16"–48 1/16")
				L	940.80.468		
				XL	940.80.469		
						XL	1220–1250 mm (48 1/16"–49 3/16")

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled 34 x 40 mm (1 11/32" x 1 9/16")		Aluminum	clear anodized	1.6 m (5' 3")	940.80.160
				1.8 m (5' 10 7/8")	940.80.180
				2 m (6' 6 3/4")	940.80.200
				2.2 m (7' 2 5/8")	940.80.220
				2.5 m (8' 2 7/16")	940.80.250
				3 m (9' 10 1/8")	940.80.300
Fixing profile for upper track with bayonet lock, with mounting set (can be shortened to respective track length)		Aluminum	clear anodized	2 m (6' 6 3/4")	940.80.420
				2.5 m (8' 2 7/16")	940.80.421
				3 m (9' 10 1/8")	940.80.422
SoftStop track stopper with adjustable retaining spring and ramp		–	–	–	941.04.304
SoftStop track stopper with adjustable retaining spring		–	–	–	941.04.301
Vertical seal		Silicone	–	7.7 m (25' 3 1/8")	940.00.500
Junior 80/100 spring buffer, cannot be used in combination with SoftMove		Zinc Alloy	–	–	940.80.320

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.