







**Hawa Junior 100 Z**








→ Upper Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled 34 x 40 mm (1 11/32" x 1 9/16")		Aluminum	clear anodized	1.4 m (4' 7 1/8")	-	940.80.140
				1.6 m (5' 3")	-	940.80.160
				1.8 m (5' 10 7/8")	-	940.80.180
				2 m (6' 6 3/4")	-	940.80.200
				2.2 m (7' 2 5/8")	-	940.80.220
				2.5 m (8' 2 7/16")	-	940.80.250
				3 m (9' 10 1/8")	-	940.80.300
				4 m (13' 1 1/2")	-	940.80.400
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	-	941.04.600
				2.5 m (8' 2 7/16")	-	941.04.601
				3 m (9' 10 1/8")	-	941.04.602
				4 m (13' 1 1/2")	-	941.04.603
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	-	941.04.604
				2 m (6' 6 3/4")	-	941.04.605
				2.5 m (8' 2 7/16")	-	941.04.606
				3 m (9' 10 1/8")	-	941.04.607
Clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	4 m (13' 1 1/2")	-	941.04.608
				6 m (19' 8 1/4")	-	941.04.609
				2 m (6' 6 3/4")	-	941.04.700
				2.5 m (8' 2 7/16")	-	941.04.701
Clip for wood and aluminum fascia, Mount every 400-600 mm (15 3/4"-23 5/8")		Aluminum	mill	3 m (9' 10 1/8")	-	941.04.702
				4 m (13' 1 1/2")	-	941.04.703
				6 m (19' 8 1/4")	-	941.04.704
Spacer profile for wall mounted tracks		Plastic	gray	2 m (6' 6 3/4")	-	941.13.220
End cap for clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	59 mm (2 5/16")	Left	941.04.400
				59 mm (2 5/16")	Right	941.04.401
				66 mm (2 19/32")	Left	941.04.402
				66 mm (2 19/32")	Right	941.04.403
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	-	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	-	-	940.80.021
Track stopper with adjustable retaining spring		-	-	-	-	941.04.300
SoftStop Junior 80/100 with adjustable retaining spring		-	-	-	-	941.04.301
SoftMove 100 soft close mechanism, maximum capacity 100 kg (220 lbs.); includes running gear and stopper		-	-	-	-	941.04.302
SoftMove 100 cover cap		Plastic	black	-	-	941.04.303

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

**Hawa Junior 100 B**





→ Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	-	940.80.140
				1.6 m (5' 3")	-	940.80.160
				1.8 m (5' 10 7/8")	-	940.80.180
				2 m (6' 6 3/4")	-	940.80.200
				2.2 m (7' 2 5/8")	-	940.80.220
				2.5 m (8' 2 7/16")	-	940.80.250
				3 m (9' 10 1/8")	-	940.80.300
				4 m (13' 1 1/2")	-	940.80.400
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	-	941.04.600
				2.5 m (8' 2 7/16")	-	941.04.601
				3 m (9' 10 1/8")	-	941.04.602
				4 m (13' 1 1/2")	-	941.04.603
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	-	941.04.604
				2 m (6' 6 3/4")	-	941.04.605
				2.5 m (8' 2 7/16")	-	941.04.606
				3 m (9' 10 1/8")	-	941.04.607
Upper track, top mounted, pre-drilled, for suspended ceilings		Aluminum	clear anodized	4 m (13' 1 1/2")	-	941.04.608
				6 m (19' 8 1/4")	-	941.04.609
				2.5 m (8' 2 7/16")	-	941.04.610
				4 m (13' 1 1/2")	-	941.04.611
Clip-on fascia Height: 40 mm (1 9/16")		-	-	6 m (19' 8 1/4")	-	941.04.612
				2 m (6' 6 3/4")	-	941.04.705
				2.5 m (8' 2 7/16")	-	941.04.706
				3 m (9' 10 1/8")	-	941.04.707
				4 m (13' 1 1/2")	-	941.04.708
Spacer profile, for wall mounted tracks		Plastic	gray	6 m (19' 8 1/4")	-	941.04.709
				2 m (6' 6 3/4")	-	941.13.220
				2.5 m (8' 2 7/16")	-	941.04.706
End cap for clip-on fascia Height: 40 mm (1 9/16")		Aluminum	clear anodized	53 mm (2 3/32")	Left	941.04.404
				53 mm (2 3/32")	Right	941.04.405
				60 mm (2 3/8")	Left	941.04.406
				60 mm (2 3/8")	Right	941.04.407
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	-	940.41.130
End cap for upper track		Steel	chrome matt	-	-	940.80.021
Track stopper with adjustable retaining spring		-	-	-	-	941.04.300
SoftStop track stopper with adjustable retaining spring		-	-	-	-	941.04.301
SoftMove 100 soft close mechanism, maximum capacity 100 kg (220 lbs.)		-	-	-	-	941.04.302
SoftMove 100 cover cap		Plastic	black	-	-	941.04.303

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

**Hawa Junior 100 B Acoustics Set**

→ Upper Tracks and Accessories








Description		Material	Finish	Length	Version	Item No.
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	-	941.04.600
				2.5 m (8' 2 7/16")	-	941.04.601
				3.0 m (9' 10 1/8")	-	941.04.602
				4.0 m (13' 1 1/2")	-	941.04.603
				6 m (19' 8 1/4")	-	941.04.604
Clip-on fascia Height: 40 mm (1 9/16")				2 m (6' 6 3/4")	-	941.04.705
				2.5 m (8' 2 7/16")	-	941.04.706
				3.0 m (9' 10 1/8")	-	941.04.707
				4.0 m (13' 1 1/2")	-	941.04.708
End cap for clip-on fascia Height: 40 mm (3 1/32"), cut-table		Aluminum	clear anodized	95 mm (3 3/4")	Left	941.04.408
				95 mm (3 3/4")	Right	941.04.409
SoftStop track stopper with adjustable retaining spring and ramp		-	-	-	-	941.04.304
SoftStop track stopper with adjustable retaining spring		-	-	-	-	941.04.301
Vertical seal		Silicone	black	7.7 m (25' 3 1/8")	-	940.00.500

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Soundproofing matrix	page
Sliding door locks	pages 1.384-1.394
Door pulls	pages 2.3-2.29
Flush pulls	pages 1.395-1.396

**Hawa Junior 80 Z**

→ Upper Tracks and Accessories






Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	-	940.80.140
				1.6 m (5' 3")	-	940.80.160
				1.8 m (5' 10 7/8")	-	940.80.180
				2 m (6' 6 3/4")	-	940.80.200
				2.2 m (7' 2 5/8")	-	940.80.220
				2.5 m (8' 2 7/16")	-	940.80.250
				3 m (9' 10 1/8")	-	940.80.300
				4 m (13' 1 1/2")	-	940.80.400
				6 m (19' 8 1/4")	-	940.80.600
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	-	941.04.600
				2.5 m (8' 2 7/16")	-	941.04.601
				3 m (9' 10 1/8")	-	941.04.602
				4 m (13' 1 1/2")	-	941.04.603
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	-	941.04.604
				2 m (6' 6 3/4")	-	941.04.605
				2.5 m (8' 2 7/16")	-	941.04.606
				3 m (9' 10 1/8")	-	941.04.607
Clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	4 m (13' 1 1/2")	-	941.04.608
				6 m (19' 8 1/4")	-	941.04.609
				2 m (6' 6 3/4")	-	941.04.700
				2.5 m (8' 2 7/16")	-	941.04.701
Clip for wood and aluminum fascia, mount every 400–600 mm (15 3/4"–23 5/8")		Aluminum	mill	3 m (9' 10 1/8")	-	941.04.702
				4 m (13' 1 1/2")	-	941.04.703
				6 m (19' 8 1/4")	-	941.04.704
Spacer profile for wall mounted tracks		Plastic	gray	2 m (6' 6 3/4")	-	941.13.220
End cap for clip-on fascia, Height: 77 mm (3 1/32")		Aluminum	clear anodized	59 mm (2 5/16")	Left	941.04.400
				59 mm (2 5/16")	Right	941.04.401
				66 mm (2 19/32")	Left	941.04.402
				66 mm (2 19/32")	Right	941.04.403
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	-	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	-	-	940.80.021
Track stopper with adjustable retaining spring		-	-	-	-	941.04.300
SoftStop track stopper with adjustable retaining spring		-	-	-	-	941.04.301
SoftMove 80 soft close mechanism, maximum capacity 80 kg (176 lbs.)		-	-	-	-	940.80.046

**Note**  
Each Hawa SoftMove 80 requires a track stopper. For applications that require a SoftMove in both directions either order the fitting set that includes two track stoppers or one additional track stopper. For additional information on SoftMove 80, see page 1.229.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

Hawa Junior 80 B (mod.)

→ Upper Tracks and Accessories

Description		Material	Finish	Length	Version	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	-	940.80.140
				1.6 m (5' 3")	-	940.80.160
				1.8 m (5' 10 7/8")	-	940.80.180
				2 m (6' 6 3/4")	-	940.80.200
				2.2 m (7' 2 5/8")	-	940.80.220
				2.5 m (8' 2 7/16")	-	940.80.250
				3 m (9' 10 1/8")	-	940.80.300
				4 m (13' 1 1/2")	-	940.80.400
				6 m (19' 8 1/4")	-	940.80.600
Upper track, wall mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	2 m (6' 6 3/4")	-	941.04.600
				2.5 m (8' 2 7/16")	-	941.04.601
				3 m (9' 10 1/8")	-	941.04.602
				4 m (13' 1 1/2")	-	941.04.603
Upper track, top mounted, pre-drilled, for wood and aluminum fascia		Aluminum	clear anodized	6 m (19' 8 1/4")	-	941.04.604
				2 m (6' 6 3/4")	-	941.04.605
				2.5 m (8' 2 7/16")	-	941.04.606
				3 m (9' 10 1/8")	-	941.04.607
Upper track, top mounted, pre-drilled, for suspended ceilings		Aluminum	clear anodized	4 m (13' 1 1/2")	-	941.04.608
				6 m (19' 8 1/4")	-	941.04.609
				2.5 m (8' 2 7/16")	-	941.04.610
				4 m (13' 1 1/2")	-	941.04.611
Clip-on fascia Height: 40 mm (1 9/16")				6 m (19' 8 1/4")	-	941.04.612
				2 m (6' 6 3/4")	-	941.04.705
				2.5 m (8' 2 7/16")	-	941.04.706
				3 m (9' 10 1/8")	-	941.04.707
Spacer profile for wall mounted tracks		Plastic	gray	4 m (13' 1 1/2")	-	941.04.708
				6 m (19' 8 1/4")	-	941.04.709
				2 m (6' 6 3/4")	-	941.13.220
				2.5 m (8' 2 7/16")	-	941.04.706
End cap for clip-on fascia, Height: 40 mm (3 1/32")		Aluminum	clear anodized	53 mm (2 3/32")	Left	941.04.404
				53 mm (2 3/32")	Right	941.04.405
				60 mm (2 3/8")	Left	941.04.406
				60 mm (2 3/8")	Right	941.04.407
Guide rail, glue-in type		Plastic	black	1.3 m (4' 3 3/16")	-	940.41.130
End cap for upper track, 940.80.series		Steel	chrome matt	-	-	940.80.021
Track stopper with adjustable retaining spring		-	-	-	-	941.04.300
SoftStop track stopper with adjustable retaining spring		-	-	-	-	941.04.301
SoftMove 80 soft close mechanism, maximum capacity 80 kg (176 lbs.)		-	-	-	-	940.80.046

Note

Each Hawa SoftMove 80 requires a track stopper. For applications that require a SoftMove in both directions either order the fitting set that includes two track stoppers or one additional track stopper. For additional information on SoftMove 80, see page 1.229.





Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.

**Hawa Junior 80 B (mod.) Pocket Sets**

	Model	Door weight	Supplied with	Item No.
For 1 door without upper track	Junior 80 B (mod.) Pocket	≤80 (176 lbs.)	2 running gears (2 rollers) with support profile, suspension plate and hanger bolt M10 1 track stopper with retaining spring 1 wall buffer 1 rattle-free floor guide 1 wrench for suspension carriage	940.80.014
	Junior 80 B (mod.) Pocket with longer hanger bolt (+20 mm (13/16"))	≤80 (176 lbs.)	2 running gears (2 rollers) with support profile, suspension plate and hanger bolt M10 1 track stopper with retaining spring 1 wall buffer 1 rattle-free floor guide 1 wrench for suspension carriage	940.80.120

**Note**  
For 2 bi-parting sliding doors, please order 2 sets and 2 track stoppers.

→ **Tracks and Accessories**

Description		Material	Finish	Length	Item No.
Upper track, pre-drilled		Aluminum	clear anodized	1.4 m (4' 7 1/8")	940.80.140
				1.6 m (5' 3")	940.80.160
				1.8 m (5' 10 7/8")	940.80.180
				2 m (6' 6 3/4")	940.80.200
				2.2 m (7' 2 5/8")	940.80.220
				2.5 m (8' 2 7/16")	940.80.250
				3 m (9' 10 1/8")	940.80.300
Fixing profile for running track with bayonet lock, with mounting set (can be shortened to respective track length)		Aluminum	clear anodized	2 m (6' 6 3/4")	940.80.420
				2.5 m (8' 2 7/16")	940.80.421
				3 m (9' 10 1/8")	940.80.422
Clip-on fascia for fixing profile, for transom facing		Aluminum	clear anodized	2 m (6' 6 3/4")	940.80.423
Spring buffer for door weight up to 80 kg (176 lbs.), cannot be used in combination with SoftMove 80		Zinc Alloy	–	–	940.80.320
Guide track for press fitting and glue fixing into groove		Plastic	black	1.3 m (4' 3 1/8")	940.41.130
Track stopper with adjustable retaining spring		Zinc Alloy	–	–	941.04.300
SoftStop track stopper with adjustable retaining spring		–	–	–	941.04.301

**Note**  
A second track stopper (941.04.300) is required when the soft and self-closing mechanism and spring buffer are not being used.

Dimensional data not binding. Dimensions in mm, inches are approximate. We reserve the right to alter specifications without notice.